

County Surveyor's Record, Douglas County, Oregon

Government Corners Renewed

T 31 S, R 5 W., W. M.

WEST COAST PRINTING & BINDING CO., PORTLAND 18725

James M. Byron,
Dep. County Surveyor
Ray Irving
John Fee
Surveyor County Lands
Dept. C.S. File 46/64.

1/4 section corner to secs. 5, T31S, R5W., and 32, T30S, R5W. **10**
Set an iron pipe with brass cap at midpoint and on true line between
Southeast corner sec. 32 and Southwest corner of sec. 32, and
marked
County
Surveyors Office
1954 T30S, R5W 32
T31S, R5W 5
Blazed and scribed:
A 5 inch R. Fir, S.37 1/2°W., 29.5 feet.
A 10 inch R. Fir, N.57 1/2°E., 41.0 feet.

NOT COMMON CORNER
1/4 COR. SEC. 32 ONLY 114
SEE COR # 158
IN T 30 S. R 5 W

1/4 sec. corner to secs. 9 and 10. **11**
Found original stone and 50 inch Fir, N.35°W., 41 lks. - checks for
bearing and distance.
Blazed and scribed new B. T.s.

7 inch Macrone, N.37°E., 13.7 feet dist. to center of tree at
scribe marks - tree leans to north mkd. 1/4 S 10 - BT.
7 inch Madrone, South 8.8 feet dist. to center of tree at
scribe marks - mkd. 1/4 S - 9 - BT. Copper tag - R.E. 2741.

1/4 sec. corner to secs. 10 and 15. **12**
Reset from old Cedar B. T. - 20 inch (now 32 inches) Cedar, S.45°W.,
12 lks.

Set 3 inch X 3 inch X 48 inch Fir stake for corner. **87**
Rescribe Old Cedar B. T., S.45°W., - remeasure to center of tree on
upper side, 9.9 feet, mkd. 1/4 S - 10 - B. T.
Blaze and scribe new B. T:
28 inch D. Fir, S.16°E., 5.0 feet dist. to center on lower side
mkd. 1/4 S - 15 - B. T. - copper tag - R. E. 2741.

Closing corner to secs. 5 and 6 only. (SEE ALSO #1) **13**
This corner was set by a projection of the line between the corner
of secs. 5-6-7-8 and the 1/4 corner of secs. 5 & 6, and its inter-
section with the township line between T30S, R5W. and T31S, R5W,
as established by Deputy County Surveyor. (C. S. File No. 44/151).
Set a 3/4 inch iron rod.

Blazed and scribed two B. T.s:
A 17 inch D. Fir, S.59 1/2°W., 60.0 feet mkd. T 31 S, R 5 W., S 6 B.T.
Copper tag R. E. 2741.
A 20 inch D. Fir, S.48°E., 54.8 feet mkd. T 31 S, R 5 W., S 5 B.T.
R. E. 2741.
(Distances to center of trees). FD. OK 1-30-79 L. MCKEAN
DUG. Co Surveyors C.S. 61/3

1/4 sec. corner to secs. 5 and 6. **14**
Found 2 O. B. T.s in good shape:

Live Oak (now 10 inches) N.59°E., 30 lks. (I cut into this).
Madrone (now 12 inches), N.67°W., 20 lks.
Set a 3 inch x 3 inch x 48 inch Fir stake for corner.
Reblaze Madrone B. T. in bark (1/4 S - 6 - B. T.) Copper tag R.E. 2741.
Blaze and scribe new B. T.
A 16 inch D. Fir, S.32 1/2°E., 44.8 feet (dist. to center) marked
1/4 S - 5 B. T. Copper tag R. E. 2741.

Closing corner to sec. 1 T31S, R5W, and Sec. 36, T30S, R5W. **15**
Found remains of old BTs to Northeast and Southeast badly rotted but,
scribe marks plainly visible. Clump of Laurel saplings & depression
in ground showing location of old tree fit for bearing and distance
to Laurel B.T. in Southwest quadrant.
Set an iron pipe (1 inch) with brass cap for corner stamped:

County Surveyor's
T30S R5W T31S R4W
36
T31S 1
1957
Office

From which:
12 inch Fir, S.18°E., 18.9 feet, mkd. T31S R4W S6 CS BT.
12 inch Fir, N.3°W., 28.2 feet, mkd. T30S R5W S36 CS BT.
6 inch Live Oak, S.29°W., 33.0 feet, mkd. T31S R5W S1 CS BT.

Arthur R. Evans - R. E. 2741.
Witness: Glen Murdock.
February 10, 1955.
For Umpqua Plywood Corp.
C. S. File No. 41/356.

Arthur R. Evans - R. E. No. 2741.
Witnesses: Glen Murdock - Milo Godfrey.
Feb. 16 and March 11, 1955.
C. S. File No. 41/367.

County Surveyor's Office
April 11, 1957
C. S. File No. 47/175.