

Douglas County Surveyor's Record of  
Government Corners Renewed

31

T. S.

5

R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21881

28

George J.  
Wenderoth,  
Deputy  
2/5/59  
C.S.#49/92

1/4 Corner between Sections 31 & 36, T.31 S., R. 5 & 6 W.  
Found - 15" Fir N.21°W. 16.5 ft., good shape.  
12" Hemlock S.82°24'E. 23.3 ft., Scribe as New B.T.  
Remains of Fir S.45°E. 19.5 ft. & Scribe marks plain.  
Drive 1" Iron Pipe for Corner.

29

Section Corner to Sections 34 & 35, T30S R5W, & Secs. 2 & 3, T31S.R5W  
Found - Mound of Stones & 4" Sq. Post.  
Original BT., 26" Fir scribed in Bark.  
Rescribed in Bark S34 T 30S R5W BT N.26°W. 9.2 ft.  
18" Live Oak, blown down (scribed).  
18" Fir, Orig. BT, rescribed in Bark S 2 T31S R5W BT S54°E. 45.7 ft.  
Set - 6" Fir S.22°W. 30.9 ft. scribed S 3 T 31 S R 5 W BT.  
24" Fir N.15°E. 42.6 ft. scribed S 35 T30 S R 5 W BT. in bark.  
Rescribed the 2 Original BT's. as noted above.

RE-RENEWED CORNER NO. 49

30

Section Corner to Secs. 1 & 2, T31S R5W, & Secs. 36 & 35, T30S R5W.  
Found - Clump of Dogwood N.28°W. 9.9 ft.  
Original BT., 16" Fir N.40°E. 17.2 ft.  
rescribed in Bark S 36 T 30 S R 5 W BT.  
Original BT, 40" Fir, bark scribed, S.20°W. 37.0 ft.  
rescribed in Bark S 2 T31 S R 5 W BT.  
Set - 3" Square Dogwood Post  
4" Dogwood N.19°W. 7.3 ft. scribed S35 T 30 S R 5W BT.  
40" Fir, bark scribed, S 1 T 30 S R 5 W BT.  
Rescribed in bark 2 Original BT's, noted above.

RE-RENEWED CORNER NO. #53

31

Section Corner to Sections 2, 3, 10, & 11.  
Found - 2 Fir Snag Bearing Trees, both bark scribed.  
38" Fir Snag S. 35° E. 19.8 ft.  
Set - 1" Steel Reinforcing Rod 42" Long, 34" in ground.

MAY, 1966  
CORNER FOUND  
J.M. POWELL

Scribed 4 New BT's. as follows:  
6" W. Fir N.44°W. 9.1 ft. scribed S 3 T 31 S R 5 W BT.  
4" W. Fir S.88°W. 9.9 ft. scribed S10 T 31 S R 5 W BT.  
8" W. Fir N.87°E. 30.1 ft. scribed S 2 T 31 S R 5 W BT.  
6" W. Fir S.09°E. 15.5 ft. scribed S11 T 31 S R 5 W BT.

32

Section Corner to Secs. 3 & 4, T31S R5W, & ~~Secs. 33 & 34, T30S R5W~~  
Found - Orig. 20", now 36" Fir S.38°W. 13.2 ft., previously opened  
shows good scribing "S 4 T".  
Orig. 6", now 10" Fir Snag N.83°W. 11.9 ft., shows old  
scar, face burned, no scribing found.  
No evidence of other Orig. BT's.  
Pointed Sandstone at Corner 12"x 12"x 18" above ground marked,  
6 notches on South & 4 notches on East.  
26" R. Fir, bark scribed, S 3 T31S R5W CC CS BT. bears  
S.85°E. 28.8 ft.  
R. Fir, bark scribed S 4 T31S R5W CC CS BT. S.35°W. 34.0 ft.  
(Note - These last 2 trees scribed 10 yrs. or so ago.)  
New BT's: 15" R. Fir bears N.87°W. 17.2 ft. scribed S33 T30S R5W CS BT.  
36" R. Fir bears S.38°W. 14.5 ft. scribed S 4 CS (bark scribed BT)  
80 ft. West to Creek  
55 ft. North to Creek.

CORNER  
NOT COMMON  
SEE 1966  
DEPENDENT  
RESURVEY

Ren. #4

FD. 9/43 M.119-3

33

1/4 Section Corner to Sections 17/16.  
Found - Original BT with scribing: 30" Fir S.75°W. 41 lks.  
Set - 3" Fir Post.  
New BT 34" Fir S.78°E. 34.0 ft. scribed, S 16, T31S R5W, BT.

RE-RENEWED CORNER NO. 84

Victor S. King, LS 442  
April 8, 1959  
C. S. File No. 42/425  
For Bate Lumber Company, Medin, Ore.

James W. Byron, Deputy  
Milo Godfrey  
C. Putnam  
Work done for C. & D. Lumber Co.  
July 23, 1959  
C. S. File No. 49/168 Map M 15-33

C.S. File No. 51/56  
See back of this  
page.