

Douglas County Surveyor's Record of
Government Corners Renewed

31

T. S.

5

R. W. W. M.

MOORE-CHAPMAN CO., EUGENE, ORE. 97101

38

SECTION CORNER $\frac{21}{28} | \frac{22}{27}$ T31S, R5W, WM
FOUND: 1 Original bearing tree with scribing
S.30°E. 9.9 ft. #83
SET: 4" Fir post from which, I set the following
New Bearing Trees:
16" Fir N.66°E. 29.0 ft. scribed S22, T31S, R5W, BT.
30" Fir N.32°W. 54.3 ft. scribed S21, T31S, R5W, BT.
14" W.Fir S.51°W. 19.5' scribed S28, T31S, R5W, BT.
32" Fir O.B.T. S.30°E. 9.9 ft. rescribed,
S 27 T31S, R5W, BT.

$\frac{1}{4}$ CORNER 28/27 T31S, R5W, WM. 39
FOUND: Both Original Bearing Trees:
The Sugar Pine showed no scribing.
The original corner 8"x 13"x 30" Stone with
 $\frac{1}{4}$ on West face. 81
SET: Reset the Stone. Rescribed the O.B.T.'s.:
46" Fir N.80°E. 17.8 ft. rescribed in bark,
 $\frac{1}{4}$ S 27 BT.
54" Sugar Pine N.60°W. 30.4 ft. rescribed,
 $\frac{1}{4}$ S 28 BT.

$\frac{1}{4}$ CORNER 21/22 T31S, R5W, WM 40
FOUND: 2" square post and 2 Original Bearing
Trees with scribing.
SET: Rescribed original bearing trees in bark,
44" Cedar N.25°E. 12.5 ft.
rescribed $\frac{1}{4}$ S 22 BT.
32" Cedar S.35°W. 22.4 ft.
rescribed $\frac{1}{4}$ S21 BT. 82

SECTION CORNER $\frac{30}{31} | \frac{29}{32}$ T31S, R5W, WM. 41
FOUND: 2" Post and 1 O.B.T. with scribing. 46
SET: 12" Fir N.89°E. 93.3 ft. scribed S 29, T31S, R5W, BT.
14" Fir N.63 $\frac{1}{2}$ °W. 103.8'. scribed S30, T31S, R5W, BT.
48" Fir O.B.T. S45°W. 56.1', rescribed in bark,
S31, T31S, R5W, BT.
18" Fir S.10°E. 68.4 ft. scribed S32, T31S, R5W, BT.

Section Corner to Secs. 4 & 5, T31S R5W, & Secs. 32 & 33, T30S R5W. 42
Found - All of Boyer's BT's. The S.W. BT., now snag only. Ren.#1
All show good scars and all check bearing & distance.
Also find $\frac{1}{2}$ " x 12" Iron Rod at Corner. #50
Set Brass Cap alongside Iron Rod & Mark Cap. S32 | S33 | T30S
County Surveyor's Office, 1959 S35 | S4 T31S R5W
New BT's: 16" R.Fir bears West 70.5 ft. scribed S32 T30S R5W CSBT.
9" Laurel " S.87°E. 79.2 ft. " S 4 T31S R5W CSBT.
48" Cedar bears S.38°W. 100.7 ft. " S 5 T31S R5W CS BT.
Note - This area badly burned this year.

Section Corner to Sections 9, 10, 15 and 16. 43
Found - Orig. B. T. - 52" Fir - no scribing - N.15°E. 62 lks. Ren.#16
Orig. B. T. - 8" Laurel with scribing very faintly visible;
blaze for scribing plainly visible. This B. T. is dead
& down, S.70°E. 7 lks.
Original line blazes to the South and West.
Set - 1 $\frac{1}{2}$ " Iron Pipe 42" long, 30" in ground, from which
the following new bearing trees:
10" Chinq. N.50 $\frac{1}{2}$ °W. 11.3 ft., scribed T31S R5W S7 BT.
12" Chinq. S.15 $\frac{1}{2}$ °W. 31.7 ft. scribed T31S R5W S16 BT.
48" Fir S.69°E. 37.0 ft., scribed T31S R5W S15 BT.
Rescribed Orig. BT. in bark - 52" Fir N.15°E. 62 lks.

VICTOR S. KING, Engineer
For Bate Lumber Company
October 30, 1959
C. S. File No. 51/56

James W. Bryon
Milo Godfrey
Clete Putnam
Nov. 12, 1959
C.S. File No. 46/64
Ms. Sec 41-9

Victor S. Kine
For Bate Lumber Co.
August 11, 1960
C. S. File No. 51/56