

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

TOWNSHIP CORNER

T31S  
R6W S 36 | S 31 R5W  
S 1 | S 6

56

Geo. J. Wenderoth  
For C. & D. Lumber  
Feb. 1964  
C. S. 49/92

Set - 1" Iron Pipe at Corner.  
Scribed - 52" Fir S. 35° 35' E. 13.6 feet. 100  
12" Hemlock S. 46° 12' W. 32.2 feet.  
16" Yew N. 79° 40' W. 97.4 feet

57

1/4 Corner to Sections 30, T31-5W. & Sec. 25, T31-6W.  
Found - No evidence of Original Corner.  
Note - As the corner I wanted to set fell in a 6 ft. wide stream, I set no corner, but from the corner location point a:

93

New BT's: 34" D. Fir Stump, I scribe "T31S R5W 1/4 S S30 BT", bears S. 35° E., 11.5 feet.  
36" D. Fir Snag, I scribe "T31S R6W S25 1/4 S BT", bears N. 82° W., 38.1 feet.

Bruce Shaner  
For Bate Lumber Co.  
February 1964  
Map File M 27 - 36

58

Sec. Cor. Common to Secs. 19 & 30, T31-5W. & Secs. 24 & 25, T31-6W.  
Set - 5/8" x 36" Iron Rod, from which a:  
44" D. Fir Stump, Orig. BT. with scribes vis., bears N. 62° W. 46.9 ft.  
42" D. Fir Stump, Orig. BT. with old rotten face, bears S. 68° E. 33.0 feet.  
Scribed - 48" D. Fir, I scribed "T31S R6W S25 BT", bears S. 45° E. 58.6 ft.  
14" D. Fir, I scribed "T31S R5W S19 BT", bears N. 46° E., 56.5 ft.  
12" D. Fir, I scribed "T31S R5W S30 BT", bears S. 20° E. 37.3 ft.

91

59

Sec. Cor. common to Secs. 30 & 31, T31-5W. & Secs. 25 & 36, T31-6W.  
Found - 3/4" Iron Pipe. (This Cor. found by Shaner, See M 27 - 36)  
Orig. BT. stump with scribes "S25" vis. bears N. 38° W. 10.6 ft.  
New BT's: 42" D. Fir with scribes vis., N. 86° W., 26.3 ft.  
18" Yew BT., Orig. BT., scribes vis., bears N. 31° E. 42.2 ft.  
38" D. Fir BT. with scribes visible bears S. 22° W. 63.2 ft.

Cor. Set by  
Geo. Wenderoth  
Reported by  
B. Shaner  
Feb. 1964  
M 27 - 36

60

1/4 Corner to Sec. 31, T31-5W. & Sec. 31, T32-5W. *ONLY 1/15/92*  
Orig. - Post, now missing, from which a:  
7" Fir bears N. 73 1/2° W. 24 lks.; 18" down rotted log, portion of cast of scribe remaining.  
6" Fir bears S. 35° E. 14 lks.; missing, burnt out.  
Orig. (109 yr. old) line blazes on Township line west.  
67 year old line blazes on same line west and north.  
Very burnt, old cruiser marks on large Firs in the SE, SW & NE.  
X on down Cedar 34 feet West.  
N. & S. ridge 12 lks. E; in place. Ravine S. 2.28 ch. W.; in place.  
Set - 1 1/2" x 36" Gal I. P. with 3" br. cap mkd: "ORE. ST. BD. OF FORESTRY 1/4 S31 S6 1964 RS 359", 30" in ground and from which a:  
10" Fir bears S. 6 1/2° W. 18.5 ft.; scribed 1/4 S6 BT.  
38" Fir bears N. 18 1/2° W. 50.4 ft.; scribed 1/4 S31 BT RS359.  
Set 4x4x72" white painted Cedar Post 1.5 ft. NW of corner pipe.  
Ore. St. Forestry Dept. metal location poster on 24" Fir S. 12° W. 14.0 ft.

Ore. State Bd. of Forestry  
Arnold G. Gibson  
Wit: D. Ray & R. Olson  
April 7, 1964  
C. S. File No. 51/264

61

Wit. Point (line tree) common to Secs. 36 & 31, T31-5&6W.  
Orig. - 48" Sugar Pine 68.20 ch. orig. meas. (now 48", uncovered 2 notches on A. & 1 on N. sides, another on N. still sealed.  
Note - Orig. must have been about 36", as there is 6" new wood on each side showing 109 years of growth.  
Scribed W. side of Line Tree W. S36 RS 359 & E. side S31, from which:  
22" Fir bears N. 76 1/2° W. 18.8 ft. scribed WP S36 BT.  
21" Fir bears N. 32 1/2° E. 22.5 ft.; scribed WP S31 BT.  
Ore. St. Forestry Dept. metal location poster on 30" Fir N. 58° W. 20.0'

Ore. St. Bd. of Forestry  
Arnold G. Gibson  
C. S. File No. 51/264

Dated July 22, 1964