

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 5 W. R.W.W.M.

KONE-CHAPMAN CO., EUGENE, ORE. 21887

62

Sec. Cor. to Sections 18 & 19 only, T31-4W.
Found - 14x10x5 Stone, 3 notches on N. & S. Edge.
Orig. 10" Laurel, now 26", N.65°E. 66.0 ft., rotten but parts
of scribe visible.
Orig. 9" Cedar, now 34", S.54°E. 40.9 ft., shows scar.
Orig. 30" D. Fir S. 14½° W. 21.8 ft., down & rotten.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

R	T31S	R
5	S 13	4
W	S 19	W

New BT: 10" D. Fir N. 69° E. 23.6 ft. scribed T31S R4W S18 CS BT.

63

Sec. Cor. to T31S S 18

R	S 19	R
5	S 13	4
W	S 24	W

Found - Orig. 24" D. Fir, now Snag, S. 58° W. 13.2 ft.; opened for scribe.
Orig. 24" D. Fir, now Snag, N. 81° W. 38.3 ft.,.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

R	T31S	R
5	S 13	4
W	S 24	S 19 W

New BT's:
6" Cedar N. 20° E. 20.8 ft. scribed T31S S19 CS BT.
5" D.Fir N. 36° W. 20.2 ft. scribed S13 CS BT.

64

¼ Corner to Section 18 only, T31-4W.
Found - Iron Pipe at ¼ Corner; See Ren. #66, T31-4W.
13" D. Fir, now 14", N. 46½° E. 52.2 ft., scribe visible, "S18",
rest pitched over.
12" D. Fir, now 16", S. 24½° E. 25.3 ft., good scars.
(Both distances to the face of trees)
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office, 1966
(alongside I. Pipe)

R	T31S	R
5	¼ S 18	4
W		W

Bearing Trees in good condition. I. Pipe Rusty.

65

Sec. Cor. to Sections 7 & 18 only, T31-4W.
Found - No trace of 3 Orig. BT's. as called for in notes.
7" Laurel, now 7", N. 44½° E. 4.4 ft., with alum. tag., not scribed.
24" D. Fir N. 84° W. 21.8 ft. Opened tree for scribe, found scribe
marks, could not make out.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

R	T 31 S	R
5	S 12	4
W	S 18	W

New BT's: 7" Laurel N. 44½° E. 4.4 ft. scribed T31S R4W S 7 CS BT.
8" Laurel S. 56° E. 23.6 ft. scribed.

66

Sec. Cor. to Section 30 and 31 only, T31-4W.
Found - 36" Fir, now dead snag, N. 74° E. 48.2 ft., shows scar
20" Fir, now blown down, S. 81½° E. 40.3 ft.
33" Fir, now stump, S. 39¼° W. 19.1 ft., scribe visible "S3".
No trace of Stone at Corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

R	T 31 S	R
5	S 30	4
W	S 31	W

New BTF 3" Fir N. 79½° E. 19.4 ft., scribed S30 BT.
Reblazed & Rescrbd: 39" Fir Stump S. 39¼° W. 19.1 ft. scribed T31SR5WS25 CS BT.
Note - This corner lies in large cut unit.

67

Sec. Cor. to Secs. 25 & 36 only, T31-5W.
Found - 24" Fir, now stump, N. 54° W. 20.5 ft., "BT" scribe visible.
24" Fir, now dead snag, S. 36° W. 23.1 ft., shows good scar.
30" Fir, now 38", S. 32° E. 27.1 ft., shows scar.
24" Fir, now dead snag, N. 50° E. 29.7 ft., shows scar.
No trace of Stone at Sec. Corner.
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966

R	T 31 S	R
5	S 25	4
W	S 36	W

New BT's: 51" D. Fir N. 60° E. 49.0 ft. scribed T31S R4W S31 CS BT.
12" Cedar S. 51° E. 51.5 ft. scribed T31S R4W S31 CS BT.

John M. Powell
Frank Jones & Joe Brady
March 1966
C. S. File No. 54/20

April 1966