

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

68

Sec. Cor. to Sections 24 and 25 only, T31-5W.

Found - No trace of Stone at Corner.

8" D. Fir, now down & rotten, N. 60° W. 7.3 ft., opened for scribing "31S B".

12" D. Fir, now stump, S. 68° W. 27.1 ft.

10" D. Fir, now 13", S. 10° E. 41.0 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966

R	T 31 S	R
5	S 24	4
W	S 25	S30 W

New BT's: 24" D. Fir N. 5° E. 15.1 ft. scribed T31S R4W S30 CS BT.

10" D. Fir S. 24° W. 4.5 ft., scribed T31S R5W S25 CS BT.

Note - This corner lies on the west edge of power line R/W.

69

Sec. Cor. to Sections 6 and 7 only, T31-4W.

Found - 1" Steel Drill at Corner, See Ren. #76, T31-4W.

Orig. 34" Fir, now 37", N. 86° E. 168.3 ft., shows good scar.

5", now 7" Laurel S. 15° W. 5.8 ft., bark scribed "BT".

4", now 6" Laurel N. 44° W. 8.8 ft., bark scribed "S1T31SR5W".

4", now 6" Laurel N. 22° E. 12.5 ft., bark scribed.

4", now 6" D. Fir N. 1° E. 16.9 ft., shows good scar.

Reblzd. & Rescrbd: 7" Laurel S. 15° W. 5.8 ft. scrbd. T31S R5W S1 CS BT.

6" Laurel N. 44° W. 8.8 ft. scrbd. T31S R5W S1 CS BT.

S 1	S 6
S 12	S 7

70

Sec. Cor. to Sections 1 and 12, T31-5W.

Found - 32" Fir, now 36", S. 13° W. 72.2 ft., opened tree for scribe.

No trace of N. W. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966

R	T 31 S	R
5	S 1	4
W	S 12	S 7 W

New BT's: 8" D. Fir S. 17 1/2° W. 9.0 ft. scribed T31S R5W S12 CS BT.

12" D. Fir N. 50° W. 11.0 ft. scribed T31S R5W S 1 CS BT.

John M. Powell  
Frank Jones and Joe Brady  
April and May 1966  
C. S. File No. 54/20

71

Sec. Corner to Sections 3 - 4 - 9 - 10.

Found - Mound of Stone and old scribed Stake.

Also 1/2" Iron Rod, See Ren. #18.

Two BT's. found in 1957, but no record of them.

36" Fir S. 71° W. 28.5 ft. bark scribed.

26" Fir N. 29° W. 38.5 ft., bark scribed.

New BT's: 6" D. Fir N. 21° E. 48.0 ft. scribed T31S R5W S 3 CS BT.

4" Live Oak S. 69° E. 32.0 ft. scribed T31S R5W S10 CS BT.

Reblzld & Rescrbd: 36" D. Fir S. 71° W. 28.5 ft. mkd: T31S R5W S 9 CS BT.

26" D. Fir N. 29° W. 38.5 ft. mkd: T31S R5W S4 CS BT.

John M. Powell  
Frank Jones & Joe Brady  
May 1966  
C. S. File No. 54/25

72

1/4 Corner to Sections 30 and 31.

Found - 23" Cedar, now 24", N. 24° E. 28.1 ft. scribed 1/4 S30 BT.

(Top half of tree broken out)

23" Hemlock, now stump, S. 26° W. 25.8 ft., "BT" scribe visible.

Oregon State Board of Forestry Brass Cap at 1/4 Corner, See Ren. #47.

New BT's: 15" Hemlock S. 21° W. 31.3 ft. scribed 1/4 S31 CS BT.

14" Hemlock N. 29° W. 61.9 ft. scribed 1/4 S30 CS BT.

Note - Logging Road bears West. 160.0 ft., put location tag on road.

73

Section Corner to Sections 29 - 30 - 31 - 32.

Found - 26" Fir, now stump, S. 13° W. 59.6 ft., pitched over face.

22" Fir, now blow down, S. 74° E. 180.0 ft., scribe visible.

26" Fir Stump N. 12° E. 12.0 ft. scribe visible T31SR5W S29BT.

St. Bd. of Forestry Brass Cap at Sec. Cor., See Ren. #46.

New BT's: 4" Chinq. bears N. 79° E. 23.7 ft. scribed S29 CS BT.

5" Fir S. 80° W. 70.2 ft. scribed T31S R5W S31 CS BT.

5" Fir S. 8° E. 82.4 ft. scribed S32 CS BT.

Note - Logging Road bears South 30.0 feet.

FD OK  
BY BRUCE S HANNEE  
7-20-93 CS  
63/153