

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 5 W. R.W.W.M.

HOKE-CHAPMAN CO. EUGENE, ORE. 91881

74

Section Corner to Sections 22 - 23 - 26 - 27.
Found - Cadastral Brass Cap, 1955.
Orig. D. Fir S. 45° E. 19.8 ft., Had been opened for scribe.
28" D. Fir S. 12° E. 23.1 ft., shows good scar.
36" D. Fir N. 70° W. 23.1 ft., shows good scar.
19" D. Fir Stump S. 31° W. 28.2 ft., opened for scribe.
N. E. BT. gone.
New BT's: 18" D. Fir S. 25° W. 30.0 ft. scribed T31S R5W S27 CS BT.
17" Laurel N. 5° W. 21.8 ft. scribed T31S R5W S22 CS BT.
Note - This corner lies about 60.0 ft. N. of small draw, & is
now on E. - W. cutting line.

RE-RENEWED, SEE CORNER NO. #124

75

1/4 Corner to Sections 15 and 14.
Found - Orig. Stone & 1 1/4" Iron Pipe at 1/4 Cor. (See Ren. #24)
12" Yew, now 13", S. 33° E. 34.5 ft. scribe visible.
18" Fir, now 20", N. 41° W. 23.5 ft., shows good scar.
12" Yew is on edge of cut bank & the appearance is bad.
New BT: 7" D. Fir S. 59° E. 11.2 ft. scribed 1/4 S14 CS BT.

76

Section Corner to Sections 14 - 15 - 22 - 23.
Found - 1 1/2" Iron Pipe at Sec. Cor. (See Ren. #25)
Orig. 14" L. Oak N. 25° W. 33.0 ft., shows good scar.
Orig. 9" Laurel N. 5° E. 13.2 ft., tree has rotten face.
Orig. 32" D. Fir, now 35", S. 50° W. 23.1 ft., shows good scar.
10" S. Pine N. 10° E. 32.0 ft., Tree now dead, scribe visible, BT.
15" D. Fir, now 18", S. 49° E. 28.7 ft., good scar.
New BT: 8" Laurel N. 7° E. 15.1 ft. scribed T31S R5W S14 CS BT.
Note - Also at corner is 4" x 4" White Post marked S.W. Cor. of Cl. #8.

FD OK
6/19/2
B. SHANER
M112-A9

77

1/4 Corner to Sections 29 and 32.
Found - 2-1 1/4" Iron Rods at 1/4 Cor. (See Ren. #9)
24" Fir, now stump, S. 6° W. 15.8 ft. This tree had old axe
work & location tag, but no scribe marks.
24" Fir N. 5° W. 35.0 ft., not found, this tree lies inside
gas line boundary.
New BT's: 3" Fir N. 78° W. 11.7 ft. scribed 1/4 S29 CS BT.
3" Fir S. 21° W. 20.2 ft. scribed 1/4 S32 BT.
Note - Power line bears East 100.0 ft. - Gas Line bears West 30.0 ft.

FD OK BY BRUCE
Shaner 7-20-03
C.S. 163/153

78

1/4 Corner to Sections 32 and 33.
Found - 1 1/2" Iron Pipe in Mound of Stone - See Ren. #22.
Orig. 8" Fir, now 16", S. 75° W. 11.8 ft., Tree opened for scribe.
12" Fir, now broken, S. 38° E. 3.6 ft., shows good scar.
24" Fir, now down, N. 75° W. 16.0 ft., shows good scar.
New BT's: 16" D. Fir N. 70° W. 19.8 ft. scribed 1/4 S32 CS BT.
16" D. Fir S. 13° E. 29.6 ft. scribed 1/4 S33 CS BT.
Note - Road bears West 80.0 ft.

79

Sec. Corner to Sections 16 - 17 - 20 - 21.
Found - Sq. Stake at Sec. Cor., scribed "S44" legible, See Ren. #37.
3" D. Fir, now 6", N. 55° W. 18.2 ft., shows good scar.
6" D. Fir, now 9", N. 56° E. 10.4 ft. scribe visible "16".
6" D. Fir, now 9", S. 83° E. 39.6 ft., shows good scar.
22" D. Fir S. 46° W. 20.8 ft., scribe visible but pitched over
too good to read.
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's T31S S 17 | S 16
Office, 1966 R5W S 20 | S 21
All Bearing Trees in good condition.

John M. Powell
Frank Jones & Joe Brady
May 1966
C. S. File No. 54/25