

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 5 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

91

Sec. Cor. to Secs. 19 & 30, R5W. & Secs. 24 & 25, R6W.
 Found - 48" Fir, S. 45° E. 58.6 ft., scribe visible. (S.B. S. 45° W)
 14" Fir N. 46° E. 56.5 ft. scribed T31S R5W S19 CS BT.
 12" Fir S. 20° E. 37.3 ft. scribed T31S R5W S30 BT.
 Orig. 44" Fir stump N. 62° W. 46.9 ft., opened for scribing.
 Iron Rod at Sec. Cor. flush with ground, See Ren. #58.
 Set @ Brass Cap at Cor. Mkd: County Surveyor's R T31S R
 (alongside I. Rod) Office 6 S 24 | S 19 5
 1966 W S 25 | S 30 W

See Blm
1982 Renewal
Vol. 45 P. 17793

All BT's. in good condition, logging road is North 25.0 ft.

92

Sec. Cor. to Secs. 18 & 19, R5W. & Secs. 13 & 24, R6W.
 Found - 1 1/2" Iron Pipe at Corner, See Ren. #27.
 Orig. 10" Live Oak N. 43° E. 26.4 ft., opened for scribe "BT". #128
 Orig. 8" Laurel, dead, N. 41° W. 27.1 ft., opened for parts of scribe.
 10" Live Oak N. 43° E. 24.7 ft. scribed "BT".
 8" Laurel N. 44 1/2° W. 28.1 ft., scribe marks.
 5" Fir, now 6", N. 44° E. 28.9 ft., pitched over scribing.
 11" Live Oak, now 12", S. 61° E. 35.7 ft. scribed T31SR5WS19BT.
 10" Live Oak S. 46° W. 15.4 ft. scribed T31SR6W S24BT.
 Set - Brass Cap at Cor. Mkd: County Surveyor's R T31S R
 Office 6 S 13 | S 18 5
 1966 W S 24 | S 19 W

New BT's: King's 1 1/2" Iron Pipe N. 43° E. 1.7 ft.
 6" Fir N. 44° E. 30.4 ft., shows good scribing.
 12" Live Oak S. 65° E. 36.1 ft., shows good scribing.
 11" Live Oak North 25.7 ft. scribed T31S R6 S13 CS BT.
 11" Live Oak S. 42° W. 14.1 ft., shows good scribing.

John M. Powell
Frank Jones and Joe Brady
May and June 1966
C. S. File No. 54/25

93

Wit. Corner to:
 1/4 Corner to Sec. 30, R5W. & Sec. 25, R6W.
 Found - 34" Fir Stump S. 35° E. 11.5 ft., scribed T31S R5W 1/4 S30 BT.
 36" Fir Snag N. 82° W. 38.1 ft. scribed T31S R6W 1/4 S25 BT.
 As notes in Ren. #57 corner falls in creek, therefore no
 corner was set.
 Set - Brass Cap for Wit. Cor. Mkd: R T31S R
 County Surveyor's 6 W.C. 25' N. to 5
 Office, 1966 W 1/4 S 25/S 30 W
 New BT's: 40" Fir Stump S. 40° E. 12.3 ft. scribed W.C. 1/4 S 30 CS BT.
 7" Alder S. 80° W. 19.0 ft. scribed W.C. 1/4 S 25 CS BT.
 Note - Brass Cap lies about 25.0 ft. south of stream and 28.6 ft.
 west of spring branch.

94

Cl. Corner Sections 6 and 5, T32-5W.
 Found - Iron Pipe & Brass Cap at Cor., See Ren. #114A, T32-5W.
 (Cadastral Brass Cap, 1962)
 The Corner of Secs. 31/32 T31-5W bears West 114.7 ft.
 30" D. Fir, now stump, S. 39° E. 21.8 ft.
 8" Yew, now stump, S. 63° W. 25.7 ft.
 23" Cedar N. 8° 53' W. 36.0 ft. scribed "CC S6 CS BT.
 7" Fir S. 70 1/2° W. 38.5 ft. scribed T31S R5W S6 H BT.
 New BT: 12" Hemlock S. 78 1/2° E. 27.5 ft. scribed T32SR5WS5CS BT.

95

1/4 Corner to Sections 24 and 25.
 Found - No trace of Laurel Tree.
 15" D. Fir, now stump, N. 23° E. 48.8 ft., bark scribed, not
 all there; curved part of "B" and "G".
 Set Stone at Corner, approx. record size, no markings visible.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 5 W
 Office 1/4 S 24
 1966 S 25
 New BT's: 23" D. Fir N. 43° E. 20.0 ft. mkd. 1/4 S24 CS BT.
 7" Cedar S. 38° W. 32.4 ft. mkd. 1/4 S 25 CS BT.
 Note - This corner lies on east slope about 140.0 ft. from top of ridge.