

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 31 S. T.S. R. 5 W. R.W.W.M.

ROSE-CHAPMAN CO., EUGENE, ORE. 21981

96

$\frac{1}{4}$ Corner to Sections 22 and 27.
Found - Orig. 16" D. Fir, now 24", S. 29° W. 17.2 ft., faint bark scrbd. vis.
Orig. 22", now 30" D. Fir N. 30° E. 4.0 ft., no scribing visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966 T 31 S R 5 W
 $\frac{1}{4}$ S 22
 $\frac{1}{4}$ S 27
Reblzd. & Rescrbd. - 24" D. Fir S. 29° W. 17.2 ft. mkd. $\frac{1}{4}$ S27 CS BT.
30" D. Fir N. 30° E. 4.0 ft. mkd. $\frac{1}{4}$ S22 CS BT.
Note - This corner lies 20.0 ft. east of top of ridge.

97

$\frac{1}{4}$ Corner to Sections 33 and 34.
Found - 1 $\frac{1}{2}$ " Iron Pipe at Corner.
40" Fir, blown down, S. 67° W. 41.6 ft.
26" Fir, now 38", S. 56° E. 31.7 ft., bark scribe visible.
Set - Brass Cap alongside I. Pipe mkd: County Surveyor's Office, 1966 T 31 S R 5 W
 $\frac{1}{4}$ S 33 / S 34
New BT's: 9" Maple S. 44° W. 22.1 ft. mkd. $\frac{1}{4}$ S 33 CS BT.
9" Live Oak N. 48° E. 39.3 ft. mkd. $\frac{1}{4}$ S 34 CS BT.

98

$\frac{1}{4}$ Corner to Sections 5 and 6.
Found - Scribed Stake mkd. $\frac{1}{4}$ S 6 - $\frac{1}{4}$ S 5. See Ren. #14
12" Laurel, now 15", N. 67° W. 13.2 ft., bark scribe visible.
16" D. Fir, now 19", S. 32 $\frac{1}{2}$ ° E. 44.8 ft., shows good scar.
10" Live Oak N. 59° E. 19.8 ft. Had been opened, no scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T 31 S R 5 W
 $\frac{1}{4}$ S 6/S 5
Reblzd. & Rescrbd. - 15" Laurel N. 67° W. 13.2 ft. mkd. $\frac{1}{4}$ S6 CS BT.
Note - This corner lies on small spur about 80.0 ft. north of Rocky Ravine.

99

$\frac{1}{4}$ Corner to Sections 15 and 16.
Found - 16", now 38" D. Fir N. 40° W. 4.0 ft., bark scribed. Dist. from face.
No trace of S. E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T 31 S R 5 W
 $\frac{1}{4}$ S 16/S 15
New BT's: 14" D. Fir N. 66° E. 22.0 ft. mkd. $\frac{1}{4}$ S15 CS BT.
Reblz. - 38" D. Fir N. 40° W. 4.0 ft. scribed $\frac{1}{4}$ S16 CS BT.
Note - $\frac{1}{4}$ Corner lies about 66.0 ft. south of ravine.

100

Township Corner common to: R S 36 | S 31 R T 31 S
6W S 1 | S 6 5W T 32 S
Original - No evidence of Orig. record corner post or BT's. could be identified.
Found - Fir described in Ren. #56, C.S. File No. 49/92 by Dep. Cor. Surv., Geo. J. Wenderoth, April 11, 1959, stating that a 52" Fir with scribes on N. face was found, near which the Township corner was set by a straight line intersection of lines N & S and E & W. The Sugar Pine line trees N. & S. were not used for control, nor was the S $\frac{1}{4}$ Corner of Sec. 31, which has been subsequently identified and restored.
The above 52", now 55", Fir has very old bark scribed "T32 R6W S1 BT", facing N. 15° E. They are similar in size, shape & style to other Lake and Hyde work in this area.
Orig. line blazes were found on line E. of this tree. Line blazes were found S. & the dist. to the ridge top matches the record. The E & W creek at 2.00 ch. N. is in place. (Approx. 60 ft. W. & on a line N. across the creek to the main ridge numerous blazes were found. None of them were exposed. They appeared very old & ended North of Creek. A search at a point S. of these blazes & 2.00 ch. S. of the creek disclosed only a 40" Fir in the NW & a 16" Yew in the SW which did not match each other or the point. No scribes or axe marks were found on either tree, although both were green.)
Restored: Set 1 $\frac{1}{2}$ " x 36" gal. I. Pipe with 3" br. cap mkd: "ORE. ST. BD. OF FORSTRY T31SR6WR5WS36 S31 S6 S1 T32S 1966 RS359", from which:

(continued over)

John M. Powell
Frank Jones & Terry Connell
June, 1966
C. S. File No. 54/25

Oregon St. Bd. of Forestry
Arnold G. Gibson
July 15, 1966
C. S. File No. 55/6

