

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 5 R.W.W.M.

KONE-CHAPMAN CO., EUGENE, ORE. 91881

112

C O N T-----

Doug. Co. Surveyors
Office
Gary Langlitz
L.E. Monrean
K. Reed; P. Earle
June 4, 1979
RM 3 - 26
C.S. 61/3

A 12" D. Fir scribed "T30S R6W S36 CS BT" on a double blaze bears N.74 1/2°W., 83.6 ft.
A 28" D.Fir scribed "T31S R5W S6 CS BT" on a double blaze bears S.52 1/2°E., 32.1 ft.
Found - From Wenderoth's I.P. Ren. #2 we find the following BT's:
A 26" Fir, now a 20" rotted stump with no marks visible on open double blaze bears N.81 1/2°E., 16.7 ft. (Rec. N.81°28'E. 16.0 ft.)
An 8" now 12" I.Cedar, alive with well healed double blaze bears S.5 1/2°E., 41.6 ft. (Rec. S.5°35'E., 41.6 ft.)
An 18" Fir now an 18" stump with scribing "5 CS S36 BT" visible on an open double blaze bears N.27°W., 26.6 ft. (Rec. N.26°53'W., 26.6 ft.)
A 26" now 28" D.Fir alive with well healed double blaze bears S.80°W., 44.5 ft. (Rec. S.80°00'W., 44.5 ft.)
Bearing trees marked by J.W. Byron, 1963, Ren. #52 referencing monument set by Wenderoth:
A 14" Maple alive with well healed single blaze bears North 37.6 ft
A 6" now 10" D.Fir alive with well healed double blaze bears N.70°E., 30.9 ft.
We chop out and destroy entirely all markings found on Wenderoth's 1946 bearing trees and on Byrons 1963 BT's. We leave the I.P. set by Wenderoth at its found location

6/79

113

1/4 Corner for Sec. 6; and Sec. 1 of T.31-6 - WITNESS CORNER

Found - Orig. 1855 4" diam. Fir now an 11" snag. We opened blaze on West face and find scribing "1/4 S" marked on corner tree.
Orig. 6" now 28" Fir with well healed blaze (not visible) bears S.87°W., 5.3 ft.

Other Orig., A Laurel to the Northeast not found.

Also find a bearing tree scribed to reference the 1/4 corner set in 1878 survey scribed "S" visible on previously opened blaze on 10" now 11" Fir (now a snag) bearing S.37 1/2°E., 11.9 ft.

The 1878 1/4 Corner position bears N.19°59'13"W., 74.76 feet from the original 1855 1/4 corner position.

Set - A witness corner: A 1"x36" I.P. with brass cap attached on line with orig. southerly line tree). Cap bears S.1°08'37"W., 5.00 ft. from orig. 1/4 corner tree. Cap is stamped "Douglas County Surveyor T31S WC R6W 1/4 S1 S6 R5W 1979".

New BT's - (NOTE: NEW TREES BEARINGS AND DISTANCES REFER TO ORIGINAL 1/4 CORNER POSITION, NOT THE WITNESS CORNER)

A 20" D. Fir scribed "1/4 S6 CS BT" on a double blaze bears N.41°E. 8.9 ft..

A 18" D. Fir scribed "1/4 S6 CS BT" on a double blaze bears S.34°E., 28.3 ft.

A 26" D. Fir, bark scribed "1/4 S1 CS BT" bears S.18°W., 44.3 ft.

5/30/79

114

1/4 Corner for Sec. 32 only, T.30-5.

Found - Original post not found. Brass cap monument set by Byron mkd. "County Surveyors Office T30S R5W 1/4 S32 T31S R5W 1954" found

Ren. #10. As this monument was set by measurement dependent on position determined by Wenderoth survey C.S. 39/118 for the southerly section corner of sections 31 and 32 (see C.S. 46/64 of the County Surveyors record). We do not find the position of this monument acceptable to mark the south 1/4 corner of S.32.

A 5" Fir now dead, bears S.37 1/2°W., 29.5 ft. We open single blaze find scribing "1/4 S5 T31S R5W CS BT". Ren. #10

A 10" Fir now dead with a burnt out blaze with no scribing visible bears N.56 1/2°E., 41.0 ft. (Rec. N.57 1/2°E.,) Ren. #10

A chisled "+ BO" on south face of rock out crop bears N.48°E., 6.7 ft. Ren. #158 of T.30-5

A 40" R. Fir scribed "1/4 S32 CS BT" on a double blaze bears North 91.6 ft. Ren. #158 of T.30-5

No original bearing trees found.

C O N T. N E X T P A G E