

Douglas County Surveyor's Record of  
Government Corners Renewed

T 31 T. S. R 5 R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

114

C O N T. - - - -

Set - A 1" x 36" I.P. at position determined by proportional measurement to mark the quarter corner position. Attached brass cap on I.P. is stamped "Douglas County Surveyor T30S R5W 1/4 S32 T31S 1979". Cap set by Byron bears S.73°27'02"E., 190.24 ft.

New Accessories:

- A D. Fir 16" scribed "1/4 S32 CS BT" on a double blaze bears N.4 3/4°E., 123.8 ft.
- A 9" Madrone scribed "S 5 CS BT" on a double blaze (oriented N.19°E.,) bears S.62°W., 26.7 ft.
- A 20" D. Fir scribed "1/4 S32 CS BT" on a double blaze bears N.76°W., 47.5 ft.

We return to the monument set by Byron, We obliterate the marks on the cap and remove scribing and marks from all references.

Corner lies on a steep slope running N.55°E.

6/19/79

115

1/16 Corner to Sections 3 and 4 (South)

- Found - A 1966 GLO brass cap properly marked, on a 2 1/2" x 28" I.P. loosely set & protruding 19" from ground. Monument leans 10" off of perpendicular to the NW.
- A 31" DBH D. Fir bears S.50°E., 29.4 ft. (rec. S.52°E., 29.0 ft.) Tree has well healed single blaze. no scribing visible & is tagged with 2 BLM BT tags.

The Orig. 35" D. Fir has been removed during road work.

- Set - We dig to base of monument and find its measurement to the orig. Southeast bearing tree is 29.0 ft. (as per record), bearing remains S.50°E., We plumb monument, firm soil about it's base and add a rough pile of stone around monument, 16" x 18" x 10" high. Brass cap is level with top of pile of stone.

- New BT's- A 8" D. Fir bears N.48°E., 35.8 ft. tree is scribed "S 1/16 S3 CS BT" on a double blaze.
- A 13" D. Fir bears S.22°W., 44.0 ft. tree is scribed "S 1/16 S4 CS BT" on a double blaze.
- A 12" D. Fir bears N.53 1/2°W., 50.00 ft. Tree is scribed "S 1/16 S 4 CS BT" on a double blaze.

9/10/80

116

Section corner for Secs. 17, 18, 19 and 20.

- Found - 1966 BLM brass cap on a 2 1/2" I.P. firmly set and protruding 10" above ground properly marked.

An orig. 14" now a 36" DBH D. Fir bears N.18°E., 21.8 ft. This tree has evidence of an opened and now rehealed blaze and is bark scribed RS 442 S17 BT.

A search is made for the other orig. bearing trees, none are found.

- A 7" now a 12" DBH W. Fir bears S.72°E., 12.8 ft. (rec. 13.4 ft.) Tree has healed single blaze and bark scribing RS 442. Ren. #26

No evidence of 9" W. Fir is found.

- A 12" now an 18" DBH W. Fir bears N.40°W., 6.9 ft. dist. Tree has fully healed single blaze, bark scribing RS 442 is visible.

A 14" now an 18" DBH W. Fir bears S.86°W., 37.0 ft. (Rec. 37.6 ft) Tree has partially healed upper blaze and a fully healed lower blaze. The upper blaze is opened and found to read as recorded in 1966 BLM notes. Notes in Ren. #90 record both bearing tree scribing incorrectly as reading "1/4 S - - -"

- An 8" now a 10" DBH W. Fir bears N.51°E., 40.8 ft. (rec. 41.4 ft.) Tree has a well healed double blaze.

Monument location is accepted and all bearing trees are tagged with DCSO BT tags. Tags are marked with bearings and distances measured in this renewal.

2/5/81

117

Witness corner for Section corner for 1, 2, 11 and 12.

- Found - 1969 County disk on a I.P., protrudes 6" above ground marked as noted per Ren. #105

8" now an 11" dia. D. fir with a double well healed blaze bears N.51°W., 15.9 ft. (Rec. N.48°W., 16.9 ft. dist. is a slope dist)

10" now a 12" dia. D. fir with a double well healed blaze bears S.86 1/2°E., 29.9 ft. (Rec. N.85°E., 30.4 ft. Brg. is in wrong quad. dist. is a slope dist. to face of blaze.)

5/8" I.R. R/W. pin at sta. 188+64.57 bears S.71°E., 26.35 ft. (Rec. S.65°E., 26.35 ft.) (A R/W. sign and post is north 0.5 ft. from 5/8" I.R.)

- - O V E R - -

Stephen Flause  
Deputy, Doug. Co.  
Surveyors Office  
Bill Stewart  
Karen Mosely  
Sept. 10, 1980  
C.S. 61/11

L. E. Monrean, Deputy  
Doug. Co. Surveyor  
Office  
S.J. Flause  
Feb. 5, 1981  
C.S. 61/19

Douglas Co. Surveyors  
Office  
R. Smith - R. Flause  
Aug. 21, 1985  
C.S. 62/29

RE-RENEWED SEE CORNER NO. #120