

Douglas County Surveyor's Record of  
Government Corners Renewed

31 T. S. 5 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

127

1/4 Corner for Sections 27 & 28

Found - Both original corner stone (24" x 12" x 8" with "1/4" scribed on it) and brass cap lying loose on steep rocky slope. I placed them in ground at proper position, and from which brass cap a: See renewal # 81.

Original corner stone (as above) lies in ground on north side of brass cap.

60" (orig. 44") D.Fir BT, bark scribes visible, bears N.80°E., 17.2 ft. (orig. 17.8 ft.) to face of tree.

54" Pine BT stump, scribes visible, bears N.60°W., (Powell erroneously called it N.65°E.,) 30.4 ft. to face of stump.

20" W.Fir BT, face overgrown, bears N.39°W., (rec. N.43°W), 103.3 ft. to center of tree. (rec. 104.3 ft.)

New Accessories -

16" W.Fir, scribed "1/4 S27 BT" bears N.6°E., 43.2 ft. to center of tree.

Set steel fence post south, 0.5 ft. of brass cap.

Note - See aerial photo. Presently on west edge of old growth D.Fir stand.

128

Cor. Secs. 18 & 19 T31-5; 13 & 24 T31-6

Found - 2 1/2" Brass cap on a 1" Iron Pipe (Ren. # 92) from which:

1 1/2" Iron Pipe bears N.44°E., 1.7'.

8" D.Fir, face overgrown, bears N.47°E., 29.7' (rec. N.44°E., 30.4'.

12" Live Oak, face overgrown, bears S.65°E., 36.1'.

11" Live Oak, scribes visible, bears N.7°E., 25.1' (rec. North, 25.7'.

11" Live Oak, stump, scribes visible, bears S.42°W., 14.1'.

12" Live Oak, face rotted out, bears N.47°E., 25.4' (rec. N.43°E., 26.4')

New Accessories -

12" D.Fir, scribed "T31S R6W S24 BT", bears S.68°W., 60.4'.

10" Live Oak, scribed "T31S R6W S13 BT", bears N.32W., 48.6'.

Note - Corner lies North 230' above spur logging road.

129

Bruce Shaner  
May 19 1993  
C.S. File 63/153

Bruce Shaner, L.S. 430  
For: Richard McKenzie  
John Wright -  
Clem Berlier  
M 117-76  
C.S. File 63/153