

County Surveyor's Record, Douglas County, Oregon
Gov't. corners Renewed

T 31 S, R 6 W, WM.

Geo. J. Wendroth
Dep. Co. Surv.
March 1946

George Vaughn)
Bill Vaughn) Witness

CHAINS
SEE ALSO
F.B. 1250
R. 2-1949

John Markham - Surveyor

Dec. 1949 - Jan. 1950
C.S. 40/233

C.S. 40/231

John H. Markham Jr
Reg. Eng'r. # 2880
Wit. D.E. Brown.
June 9, 1951.

C.S. 40/231

COR. NORTH SIDE SEC. 1

Old B.T. badly rotted.
Set $\frac{3}{4}$ " iron pipe.
marked 14" Fir N $33^{\circ}17'$ W 11.2 ft.
10" Cedar S $43^{\circ}04'$ W 25.9 ft.

SEE CORNER NO. 61 1

TOWNSHIP COR.

NE COR. SEC. 1

Set by running West, East & North.
Set $\frac{3}{4}$ " iron pipe.
Mark 26" Fir N $81^{\circ}28'$ E 16.0 ft.
8" Cedar S $5^{\circ}35'$ E 41.6 ft.
18" Fir N $26^{\circ}53'$ W 26.6 ft.
26" Fir S $80^{\circ}00'$ W 44.5 ft.

SEE CORNER NO. 59 2

SEC. COR. 1-2-11-12

Determined from remains of O. B. T., 33" Fir S 21° E, 26 ft.
remark S 12 B T. A 15" Fir N 62° W 45 ft. has legible scribe
remark S 2 B T. - SEPT. 1966 - SEARCHED FOR, NOT FOUND JMP
At corner point found 4" x 4" wood post scribed S 1-2-11-12.
Set a $\frac{3}{4}$ " x 24" I.P. 18" in ground from which
6" Laurel bears S 49° W 53 ft., mkd. S 11 2880 B T.
4" Laurel bears N 36° E 26 ft., mkd. S 1 2880 B T.

$\frac{1}{4}$ SEC. COR. 2-11 4

As determined from remains of O. B. T., an ^{live oak} Ash (not Oak) 8" diam.
which bears S 15° E 16.5 ft.
At corner set $\frac{3}{4}$ " x 24" I. P. 12" in the ground from which
10" Fir bears N 27° E 17.0 ft. mkd. $\frac{1}{4}$ S 2880 B T.
6" Fir bears S 4° W 8.6 ft. mkd. $\frac{1}{4}$ S 2880 B T.
This corner sets just West of an 80 ft. rock bluff

SEC. COR. 2-3-10-11

Determined from remains of O. B. T's., 27" Laurel bears S 80° E
46 $\frac{1}{2}$ ft. dist., scribe legible, 16" Laurel bears N 60° E 42 $\frac{1}{2}$ ft.
rescribed this O. B. T. S 2 2880 B T., dead Pine snag
N 28° W 41.0 ft.

$\frac{1}{4}$ SEC. COR. 2-3 6

Determined from remains of O. B. T's., 20" Laurel N 67° E 33.0 ft.
rescribe $\frac{1}{4}$ S, S 2, 2880 B.T. and a stump hole N 12° W 35.0 ft.
At corner point found 3" x 3" wood stake mkd. $\frac{1}{4}$ S 3, $\frac{1}{4}$ S 2 at
which point I set a $\frac{3}{4}$ " x 36" I.P. 18" ins. the ground, from which
26" Laurel bears S 68° W 53.0 ft. mkd. $\frac{1}{4}$ S 3 2880 B T.

SEE CORNER NO. 125

$\frac{1}{4}$ sec. cor. 1-12

Location determined from Old BT a
Fir 10" dia. bears S 49° W 31.0 ft.
Fir 37" dia. " N 20° E 26.0 ft. bark scribed. 98
Set $\frac{1}{2}$ " x 20" iron rod for corner from which a
Fir 7" dia. bears N _____ W 15.0 ft scribed $\frac{1}{4}$ S BT
remarked both Olds BTs.
Trail bears West 330 ft.

$\frac{1}{4}$ sec. cor. 12-13

Location determined from Old BT. a
Fir 15" bears S 68° W 17.0 ft. with scribe marks.
which I remark $\frac{1}{4}$ S BT
At the corner point I found a stone and made a large pile
of rocks. from which a
Laurel 12" dia. bears S 77° E 7.0 ft. scribed $\frac{1}{4}$ S BT
a spring bears South 5.0 ft.

SEE CORNER NO. 97 8