

Douglas County Surveyor's Record of  
Government Corners Renewed

31 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

21

$\frac{1}{4}$  Corner between Sections 31 & 36, T.31S., R.5 & 6 W.  
Found - 15" Fir N.21°W. 16.5 ft., good shape.  
12" Hemlock S.82°24'E. 23.3 ft., Scribe as New BT.  
Remains of Fir S.45°E. 19.5 ft. & scribe marks plain.  
Drive 1" Iron Pipe for Corner.

Geo. J. Wenderoth  
Wenderoth,  
Deputy  
2/5/59  
CS.File #49/92

22

$\frac{1}{4}$  Section Corner between Sec. 36, T31S R6W, & Sec. 1, T32S R6W.  
6.7 ft. North.  
Found remains of 14" Madrone N.58°E. 9.9 ft.  
Old live Oak Stump S.53°W. 3.3 ft., no scribe marks,  
Top of ridge 297 ft. West on old blazed line.  
From all indications corner is right.  
Set 3" Live Oak Stake for Corner.  
Scribe - 8" Live Oak N. 5°16'W. 31.1 ft.  
12" Live Oak N.63°56'W. 17.3 ft.

Geo. Wenderoth  
For C.&D. Lumber Co.  
April 11, 1959  
C.S. File No. 49/92

23

$\frac{1}{4}$  Section Corner between Sections 26 and 35.  
Found - 50" Fir S.88°W. 9.9 ft. Bark scribed but  
dead and broken off.  
Other Tree gone.  
Drive 1" Iron Pipe and Scrib New Trees:  
14" Fir S.54°16'E. 13.5 ft.  
22" Maple N.46°05'W. 65.8 ft.

Geo. Wenderoth  
Nov. 18, 1959  
C.S. File  
No. 49/92

24

Sec. Cor. Secs. 31 & 32, T31S R6W, & Secs. 5 & 6, T32S R6W.  
Set  $\frac{3}{4}$ " x 18" I. P. in Rk. Md. From Orig. BT's:  
8" Fir N.17°W 58.0 ft. (down, scribe visible.)  
6" Fir N.17°E. 57.8 ft. (Stump)  
New BT's: 13" D.Fir N.81 $\frac{1}{2}$ °W. 36.0 feet.  
9" D.Fir N. 8°E. 69.9 feet.  
6" D.Fir S.59°E. 45.0 feet.  
8" D.Fir S.1 $\frac{1}{2}$ °W. 68.7 feet.

Clifford M. Bryden  
For Roseburg Lumber Co.  
February 1960  
Map File M 17 - 34

25

Sec. Cor. to Secs. 32 & 33, T31S R6W, & Secs 5 & 4, T32S R6W.  
Orig. BT's: 5" Laurel N.47°E. 21.1 feet  
18" Fir S.34°W. 21.7 feet.  
Scribed BT's: 24" D.Fir N. 6°W. 35.0 feet.  
14" D.Fir N.54°E. 87.3 feet.  
16" D.Fir S.63°E. 38.0 feet.

26

$\frac{1}{4}$  Corner to Sections 29 & 32.  
Set  $\frac{3}{4}$ " x 18" Iron Pipe from Orig. BT's.  
Scribed BT's: 17" D.Fir N.56°W. 6.5 feet  
32" Cedar S.72°E. 19.0 feet.

27

Section Corner to Sections 30, 29, 32, & 31.  
Set  $\frac{3}{4}$ " x 18" Iron Pipe from Original BT's.

28

$\frac{1}{4}$  Corner to Sections 31 and 32.  
Set:  $\frac{3}{4}$ " x 18" Iron Pipe at Mid-Distance between Section Corners.  
Scribed BT's: 17" D.Fir N.27 $\frac{3}{4}$ °E. 25.0 feet.  
15" D.Fir S.16 $\frac{1}{2}$ °W. 12.3 feet.

29

Center  $\frac{1}{4}$  Corner to Section 32.  
Set:  $\frac{3}{4}$ " x 18" Iron Pipe  
Scribed BT's: 12" D.Fir N.26°W. 30.9 feet.  
20" Cedar S.39 $\frac{1}{2}$ °E. 51.1 feet  
5" Cedar N.21°E. 16.8 feet.

(continued next page)