

Douglas County Surveyor's Record of  
Government Corners Renewed

31 T. S. 6 R. W. W. M.

KORR-CHAPMAN CO., EUGENE, ORE. 21881

Clifford M. Bryden  
For Roseburg Lumber Co.  
February 1960  
Map File M 17 - 34

Section Corner to Sections 19, 20, 29, and 30. 30  
Set 4 x 4 Cedar Post from Original BT's.  
Scribed New BT's: 5" Fir N.71°W. 39.7 feet  
12" Fir S.11°W. 15.0 feet  
12" Fir N.12°E. 20.8 feet  
10" Fir S.62°E. 43.3 feet

RE-RENEWED CORNER NO. #90 31  
1/4 Section Corner to Section Sections 29 & 30  
Original BT: 10" Laurel  
Scribed New BT's: 10" D. Fir N.77°E. 31.4 feet  
30" I. Cedar S.64°W. 28.5 feet.

Center 1/4 Corner Section 29. 32  
Set 3/4" x 20" Iron Pipe.  
12" D. Fir S.70°W. 29.0 feet  
12" I. Cedar N.20°W. 27.1 feet.

Fd. I.P. #1 BT.  
B.L.M. 1977 ADMIN.  
SURVEY. SEE  
GIS FILES

Geo. J.  
Wenderoth  
May, 1960  
C.S. 49/92

1/4 Corner between Sections 3 and 10. 33  
Found Yew Stake & 10" Fir S.45°E. 8.6 feet, rotten scribe marked.  
Scribe New Trees: 15" Yew S.77°17'E. 47.3 feet.  
10" Yew N.55°38'E. 36.5 feet.

1/4 Corner to Sections 3 and 4. 34  
Found - Rotted Fir Stump, new 23", N.58°W.-record N.68°W. 13.2 ft.,  
showing bark scribe "BT".  
Fir Stump, New 25", S.40°E. 32.3 ft. Showing bark scribe "BT"  
Set Iron Pipe with Brass Cap Mkd: "County Surveyor's Office, 1960  
T.31S. R.6W. 1/4 S4/S3.  
Blaze & Scribe New Trees: 10" Red Fir S.19°W. 35.9 ft. Mkd: "1/4 S4 CS BT."  
20" Red Fir S.39°E. 35.2 ft. Mkd: "1/4 S3 CS BT".

Fd. ok 8/8/61  
G. Gross  
M 28-67

Section Corner to Sections 3, 4, 9, and 10. 35  
Found - Fir, new 24", alive & standing. Some bark scribing &  
notches still visible.  
Fir, new 21", N.28°E. 6 ft., alive & standing, shows bark  
scribing "3S BT".  
Fir, new 24", S.80°E. 16.5 ft., shows good scar. Do not open.  
Fir, new 28", S.25°W. 10 ft. bark scribing still visible, "8S BT"  
& fragments of other scribing, alive & standing.  
No trace of N. W. Bearing Tree.  
Set Witness Corner to Section Corner 4.3 ft. East of True Corner.  
Set Iron Pipe with brass cap Mkd: "County Surveyor's Office, 1960, W.C.  
T.31S. R.6W. S4 | S3 4.3 to Cor.  
S9 | S10  
Blaze & Scribe 16" R. Fir N.8°W. 48.0 ft. scribed "T31S R6W WC S4 CS BT".

James W. Byren, Deputy  
Mile Godfrey  
Clete Putnam  
May 23, 1960  
C. S. File No. 52/25

1/4 Sec. Cor. to Sec. 3, T31S R6W, & Sec. 34, T30S R6W. 36  
Found - Fir Snag, new 30", N.10°W. 19.1 ft. Opened & found good scribe "TW"  
No trace of other B.T.  
Set Iron Pipe with Brass Cap Mkd: "County Surveyor's Office, 1960  
T30S R6W 1/4 S34  
S3  
Blaze & Scribe New Trees:  
18" R. Fir N.89°W. 20.0 ft. ("1/4 S34 CS BT")  
11" Maple S. 9°W. 51.0 ft. (1/4 S 3 CS BT).

Fd. ok 8/8/61  
G. Gross  
M 28-67

Section Corner to Secs. 3 & 4, T31-6 and Secs. 33 & 34, T30-6. 37  
Found 3/4" Pipe Set by Markham. 14" Laurel N.74°E. 46.5 ft. scribe visible.  
14" Laurel N.35°W. 29.0 ft. scribing visible. Ren. #17  
15" Laurel N.22°E. 17 ft., down & dead.  
Blazed & Scribed 2 New Trees: 9" Fir S.2°E. 79.2 ft. Mkd. T31SR6W S3 CS BT."  
9" W.Oak S.10°W. 97.4 ft. Mkd: "T31S R6W S4 CS BT".  
No trace of Orig. BT's, except Stump holes & a few remnants of charred  
wood.  
Note-All trees in vicinity, incl. BT's, are badly damaged by fire, 1959.

Fd. ok 8/8/61  
G. Gross  
M 28-67