

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Section Corner to Sections 19 and 18.
Set 3 x 3 Cedar Post 1/4 Corner from Original Bearing Trees.
New BT's: I. Cedar S.14°E. 57.5 feet
D. Fir N.25°W. 68.0 feet

38

1/4 Section Corner to Section 19 and 20.
Found 3 x 3 Cedar Post and Original B.T. 18" D. Fir S.70°W. 22.4 feet.
Set New B.T.: 8" D. Fir S.47°E. 14.6 feet.

39

1/4 Section Corner to Sections 19 and 30.
Set 3 x 3 Cedar Post 1/4 Corner from remains of Orig. B.T.'s.
New BT's: 7" D. Fir N.10°E. 8.3 feet
7" D. Fir S.48°E. 28.5 feet

40

Section Corner to Sections 19 & 30, 31-6 & Secs. 24 & 25, 31-7.
Set Section Corner - 1 1/2" x 24" Iron Pipe.
6" D. Fir S.88°W. 32.8 feet.
14" D. Fir S.63°E. 35.0 feet.
30" D. Fir N.10°E. 55.1 feet.
7" S. Pine N.55°W. 23.9 feet

41

1/4 Section Corner to Sec. 19, 31-6 & Sec. 24, 31-7.
Set 1/4 Corner - 1" x 24" Iron Pipe
15" D. Fir S.31°E. 25.1 feet
7" D. Fir S.66°W. 29.2 feet.

42

Section Cor. common to Secs. 30 & 31, T31-6W. &
Secs. 25 & 36, T31-7".
Found - 6" Madrone N.66°W. 31.1 ft., scribe visible.
6" Madrone S.34°W. 26.4 ft., down.
Set - 4" x 4" Cedar Post
20" D. Fir S.57°W. 32.5 ft.
8" D. Fir S.18°E. 24.0 ft.
16" D. Fir N.46 1/2°W. 57.0 ft.
6" D. Fir N.78°E. 38.0 ft.

43

Howard W.
Johnstone
For Roseburg
Lumber
Jan. 4, 1961
C.S. File
No. 51/163

RE-RENEWED, SEE CORNER NO. 49
1/4 Section Corner for Sections 26 and 27.
Found - Large D. Fir BT., N.86°W. for 34 lks.
An Oak Stake 3" x 4" was set from this B.T. and
a new B.T. was marked. This new B.T. is a
16" D. Fir bears S.77°W. for 12.4 ft., which
was inscribed on the face 1/4 S.26.

44

Claude Kerr
April, 1961
C. S. File
No. 51/193

RE-RENEWED, SEE CORNER NO. 156
1/4 Section Corner to Sections 25 and 26.
Found - Orig. 30", now 40" R. Fir S. 5°E. 23.8 ft., shows good bark
scribing "S" BT. No trace of Orig. NW BT found.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1961
1/4 S26/S25 T31S R6W
New BT's: 16" R. Fir bears N.85°E. 26.8 ft. scribed 1/4 S25 CS BT.
14" R. Fir bears N.85°E. 65.0 ft. scribed 1/4 S25 CS BT.
Note - No live Trees near to West.

45

James W. Byron, Deputy
Milo Godfrey
Clete Putnam
June 1, 1961
C. S. File No. 52/25

Section Corner to Sections 23 - 24 - 25 - 26.
Found - Rock Mound & 1" Drill Steel Set by Cole in 1924.
50" Fir N.42°E. 47.5 ft., alive & standing.
16" Fir, now 34", S.64°W. 47.5 ft., alive & standing.
12" Chinq., now 30", N.53°W. 63.4 ft., alive & in good cond.
Rotted Stump of 48" Fir S.45°E. 12.5 ft.
Did Not Set Brass Cap.
New BT's: 5" Fir N.13 1/2°E. 36.3 ft. Mkd: S24 CS BT.
6" Fir S.66 1/2°W. 6.2 ft. Mkd: S26 CS BT.
18" Fir S.82°E. 28.1 ft. Mkd: T31S R6W S25 CS BT.

46

REN #15