

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 6 W. R. W. W. M.

ROKS-CHAPMAN CO., EUGENE, ORE. 21881

Arnold G.
Gibson
July 1964
C. S. File
No. 51/264

Witness Point (Line Tree) common to Secs. 36 and 31, T31-5&6W. 74
Orig-48" Sugar Pine at 68.20 ch. orig. meas. (now 48", uncovered 2 notches
on S. & 1 on N., another on N. still sealed).
Note-Orig. must have been about 36", as there is 6" of new wood on each
side showing 109 years of growth.
Restored - Scribed W. side of Line Tree WP S36 RS359 & E. side S.31,
22" Fir bears N.76 $\frac{1}{2}$ °W. 18.8 ft.; scribed WP S36 BT.
21" Fir bears N.32 $\frac{1}{2}$ °E. 22.5 ft.; scribed WP S31 BT.
Ore.St. For.Dept. metal location poster on 30" Fir N.58°W. 20.0 feet.

Wit. Corner Section Corner to Sections 15 - 16 - 21 - 22. 75

Found - 38", new 38" Corner Tree, Fir Snag, badly fire scarred #147
22", new 30" Fir, burned snag, N.57°W. 44.0 ft. Open, find nothing.
40", new 48" Fir, burned snag, S.35°E. 44.2 ft. Open, find nothing.
5", new 8" Fir, burned snag, N.36°E. 10.6 ft., recorded as
8" orig. Open & find "T31S R6W S15" scribe.

No trace of Laurel BT.

RE-REVIEWED
Set - Wit. Corner 4.0 ft. West, Brass Cap Mkd: County Surveyor's
Office, 1964 T31S R6W W.C. 4 ft. E.

S 16	S 15
S 21	S 22

New BT's: 5" D.Fir N.42°W. 24.6 ft. Mkd: W.C. S16 CS BT.
3" D.Fir N. 6°E. 4.0 ft. Mkd: W.C. S15 CS BT.
4" D.Fir S.58°E. 14.3 ft. Mkd: W.C. S22 CS BT.
5" D.Fir S.10°W. 23.4 ft. Mkd: T31S R6W S21 CS BT.
No larger trees available.

Section Corner to Sections 17 - 18 - 19 - 20. 76

Found - Orig. 50", new 54" D.Fir N.55°E. 15.2 ft., recorded as 13 lks.,
shows old faint bark scribe "T31S R6W 7" & new "BT" in bark.
Orig. 6", new 8" D.Fir S.47°E. 15.2 ft. (dead) recorded as S.53°E.,
shows good scars.

Orig. 20", new 20" Laurel S.35°W. 38.9 ft., down & dead, found
" \ " reverse scribe in rotted remains.

Orig. 6", new 9" D.Fir N.55°W. 12.5 ft., open & shows "BT".

Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R6W

S 18	S 17
S 19	S 20

Office, 1964

New BT's: 16" D.Fir S.79°E. 32.9 ft. Mkd: T31S R6W S20 CS BT.
17" D.Fir S.52°W. 35.4 ft. Mkd: T31S R6W S19 CS BT.
16" D.Fir N.22°E. 34.2 ft. Mkd: T31S R6W S17 CS BT.

$\frac{1}{4}$ Section Corner to Sections 17 and 20. 77

Found - Orig. 12", new 28" Pine N.80°W. 58.1 ft., open & shows " $\frac{1}{4}$ S BT".
Orig. 40", new 40" Pine Snag S.40°E. 44.9 ft., recorded S.45°E.
Did not Open.

Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R6W $\frac{1}{4}$

S 17	S 20
------	------

Office, 1964

New BT's: 6" D.Fir S. 9° E. 7.8 ft. Mkd: $\frac{1}{4}$ S20 CS BT.
6" D.Fir N. 6° W. 23.4 ft. Mkd: $\frac{1}{4}$ S17 CS BT.

$\frac{1}{4}$ Corner to Sections 15 and 22. 78

Found - 22", new 30" D.Fir S.72°W. 15.8 ft., badly burned snag.
22", new 34" D.Fir N.60°E. 7.9 ft., alive & shows " $\frac{1}{4}$ S" in bark.

Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R6W $\frac{1}{4}$

S15	S22
-----	-----

Office, 1964

New BT's: 19" D.Fir S.40°W. 27.9 ft. Mkd: $\frac{1}{4}$ S22 CS BT.
12" D.Fir N.10°W. 47.5 ft. Mkd: $\frac{1}{4}$ S15 CS BT.

Nov. 5, 1964

$\frac{1}{4}$ Corner to Sections 20 and 21. 79

Found - Squared Post as recorded in Ren. #19.
Orig. 6", now 19" Cedar S.65°W. 8.6 ft., open & fd. " $\frac{1}{4}$ " Scribe.
No trace of other Orig. BT., nor BT. recorded in Ren. #19.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T31S R6W $\frac{1}{4}$

S 20	S 21
------	------

New BT's: 19" D.Fir N.55°E. 72.0 ft. Mkd: $\frac{1}{4}$ S21 CS BT.
22" Cedar N.66°W. 21.6 ft. Mkd: $\frac{1}{4}$ S20 CS BT.

Note - This corner lies approx. 60 ft. S. of spring branch flowing N. W.
March 5, 1965

Vernon "Ray" Tracy
Mike Darby & Jack Barnett
October 1964
C. S. File No. 52/25

Fd 82. #387
BLM ADMIN.
SUNWAY 1977
GIS FILES