

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 6 W. R. W. W. M.

NOKE-CHAPMAN CO., EUGENE, ORE. 21881

80

1/4 Corner to Sections 18 and 19.

Found - Orig. 60", now 65" Fir S. 55° W. 21.8 ft., shows "S" scribe (bark)

24" I. Cedar S. 14° E. 57.5 ft., shows "1/4 S BT" on unhealed face, See Ren. #38.

45" D. Fir N. 25° W. 68.0 ft., shows "1/4 SBT" on partially healed face. See Ren. #38.

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1965 T31S R6W 1/4 S 18 S 19

Note - This corner lies on steep S. E. slope.

5/25/65

E. S.
File No.
52/25

81

S.E. 1/16 Sec. Cor. to Sec. 5, T31-6W. and
Sec. 32, T30-6W.

19.91 - Point for the E. 1/16 at proportionate distance.

Set - 1" I. Pipe 3 ft. long, 28" in the ground, from which:

6" D. Fir bears N. 30° E. 17 lks. dist., mkd. E1/16 S32 R6W BT.

16" D. Fir bears S. 68° W. 13 lks. dist., mkd. E1/16 S5 R6W BT.

July 21, 1965

Marvin C.
Ramsey
For J.H.
Baxter
C.S. File
No. 51/316

82

Section Corner to Sections 7 - 8 - 17 - 18.

Found - Orig. 40" D. Fir, now 59" N. 45° W. 5 lks., shows bark scribe. Good Tree.

Orig. 24" D. Fir, now Snag, N. 42° E. 50 lks., shows bark scribe.

Orig. 12" Yew, now 18" S. 1° W. 74 lks., scribe visible. Good Tree.

Orig. 20" D. Fir, now burned snag, S. 50° E. 45 lks.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965 S 7 | S 8 T31S R6W S 18 | S 17

New BT's: 59" D. Fir N. 45° W. 4.6 ft. scribed T31S R6W S7 BT.

36" D. Fir N. 31° E. 68.0 ft. scribed T31S R6W S8 BT.

49" D. Fir S. 21° E. 77.5 ft. scribed T31S R6W S17 BT.

John M. Powell
Joe Brady
Sept. 1965
C. S. File #2/25

83

1/4 Corner to Sections 17 and 18.

Found - Orig. 6", now 12" D. Fir S. 45° E. 11 lks., Tree opened and BT. scribe visible.

Orig. 8", now 12" D. Fir S. 46° W. 22 lks., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965 T31S R6W. 1/4 S18/S17

New BT: 12" Doug. Fir S. 45° E. 7.3 ft. scribed 1/4 S17 CS BT.

Sept. 21, 1965

84

Sec. Cor. to Secs. 13 & 24, R6W. & Sec. 18 & 19, R5W.

Found - 1 1/2" Iron Pipe (See Ren. #27) from which:

Orig. 10" Live Oak N. 43° E. 26.4 ft., opened for scribe "BT".

Orig. Laurel, dead, N. 41° W. 27.1 ft. opnd. for parts of scribe.

5" Fir, now 6", N. 44° E. 28.9 ft., pitched over scribing.

11" Live Oak, now 12", S. 61° E. 35.7 ft. scribed T31SR5W S19BT.

10" Live Oak, now 11", S. 46° W. 15.4 ft. scribed T31SR6WS24BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T31S R6W S 13 | S 18 | S 19 | S 24 | S 25 | S 30 | W

New BT's: 6" Fir N. 44° E. 30.4 ft., shows good scribing.

12" Live Oak S. 65° E. 36.1 ft., shows good scribing.

11" Live Oak, North 25.7 ft. scribed T31S R6W S13 CS BT.

11" Live Oak S. 42° W. 14.1 ft., shows good scribing.

John M. Powell
Frank Jones & Joe Brady
June 1, 1966
C. S. File No. 54/25

85

Sec. Cor. to Secs. 24 & 25, R6W. & Secs. 19 & 30, R5W.

Found - Iron Rod at Sec. Cor., flush with ground, See Ren. #64.

Orig. 44" Fir Stump N. 62° W. 46.9 ft., opened for scribing.

48" Fir S. 45° E. 58.6 ft., scribe visible (Bearing S.B. S. 45° W.)

12" Fir, now 12", S. 20° E. 37.3 ft. scribed T31S R5W S30 BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 R T 31 S R 6 S 24 | S 19 | S 25 | S 30 | W

SEE 1982 BLM
Renewal
Vol. 45 Pt. 174-93

All Bearing Trees in Good Condition - Logging Rd. is North 25 ft.