

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

86

John M.
Powell &
Crew
June, 1966
C. S. File
No. 54/25

Witness Corner to:

1/4 Corner to Sec. 25, R6W. & Sec. 30, R5W.

Found - 34" Fir Stump S. 35° E. 11.5 ft. scribed T31S R5W 1/4 S30 BT.

36" Fir Snag N. 82° W. 38.1 ft., scribed T31S R6W 1/4 S25 BT.

As notes in Ren. #65, corner falls in creek, therefore
no corner was set.

Set - Brass Cap, Wit. Cor. Mkd: County Surveyor's R T31S R
Office 6 W. C. 5
1966 W 25' Northto W

(Brass Cap lies about 25.0' S. of Stream,
(and 28.0' West of spring branch.)
1/4 S 25/S 30

New BT's: 40" Fir Stump S. 40° E. 12.3 ft. scribed W.C. 1/4 S30 CS BT.

7" Alder S. 80° W. 19.0 ft. scribed W. C. 1/4 S25 CS BT.

Township Corner Common to: R S 36 | S 31 R T 31 S
6W S 1 | S 6 5W T 32 S

87

Original- No evidence of Orig. record corner post nor BT's could
be identified.

Found- Fir described in C.S. File No. 49/92 by Dep. Co. Surv. #160
Geo. J. Wenderoth, Ren. #62, April 11, 1959, stating that a 52" Fir with
scribes on N. face was found, near which the Twp. corner was set by a
straight line intersection of lines N & S and E & W. The sugar pine line
trees N. & S were not used for control, nor was the corner of Sec. 31,
which has been subsequently identified & restored.

The above 52", now 55" Fir has very old base scribed "T32 R6W S1 BT",
facing N. 15° E. They are similar in size, shape and style to other
Lake and Hyde work in this area.

Orig. line blazes were found on line E. of this tree. Line blazes
were found S. & the dist. to the ridge top matches the record. The
E & W creek at 2.00 ch. N. is in place. (Approx. 60 ft. W. & on a line
N. across the creek to the main ridge, numerous blazes were found. None
of them were exposed. They appeared very old & ended N. of the Creek.
A search at a point S. of these blazes and 2.00 ch. S. of the creek,
disclosed only a 40" Fir in the NW and a 16" Yew in the SW which did not
match each other or the point. No scribes or axe marks were found on
either tree, although both were green.)

Restored - Set 4" x 36" gal. I. Pipe with 3" br. cap mkd. "Ore. St. Bd. of
Forestry T31S R6W R5W S36 S31 S6 S1 T 32S 1966 RS359".
and from which a:

55" Fir bears S. 15° W. 11.5 ft.; scribed T32 R6W S1 BT. (Also
scribes S6 CS BT by Wenderoth).

6" Fir bears N. 86° W. 54.5 ft.; scribed T31S R6W S36 BT.

4" Hemlock bears S. 58° E. 28.3 ft.; scribed X.

4" Fir bears N. 9° E. 19.0 ft.; scribed X.

Wenderoth's 7" Pipe bears West 13.3 ft.

Set 4" x 4" x 72" white painted Cedar post, 2.0 ft. S. of corner pipe.

Ore. St. Forestry Dept. metal location poster on 55" Fir BT.

Also BLM poster on 36" Fir 150.0 ft. North on N. side of creek.

88

1/4 Corner to Sec. 7, T31-5W. & Sec. 12, T31-6W.

Found - Orig. 6" fir S. 48° W. 8.6 ft., now remains of old Fir,
shows old axe work. No scribing found. See Statement

signed by James Combs in file, to wit:

I, James Combs, state that the remains of old Fir Stump found and
used on this date for the Orig. S.E. BT. did show good wood
scribing in 1952.

Found - Base of Orig. N.E. BT., no scribing.

Tag set by Haines on now down 30" Fir, see forest appraisal
record.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's R T 31 S R
Office 6 S 12/S 7 5
1966 W W

New BT's: 22" D. Fir S. 28° W. 68.2 ft. scribed 1/4 S12 CS BT.

10" Yew S. 59° E. 26.4 ft. scribed 1/4 S 7 CS BT.

Aug. 4, 1966

Oregon State Board of Forestry
Arnold C. Gibson
July 15, 1966
C. S. File No. 55/6

James W.
Byron, Co. Surv.
John Powell
& Crew
Aug., 1966
C. S. File
No.
54/25