Douglas County Surveyor's Record of Government Corners Renewed

T. 31 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

94

Sec. Cor. to Sections 10 - 11 - 14 - 15.
Found - Post scribed S10,S11,S14,S15.
12",now 15" D. Fir, N. 60° E. 11.9 ft., shows good scar.
14" D. Fir, now stump, N. 30° W. 19.8 ft., Opened log for scribing @BT", scribing very high,non on stump.
No trace of S.E. nor S. W. Trees.
Set - Brass Cap at Cor. Mkd: County Surveyors Office 1966

T 31 S	R 6 W
S 10	S 11
S 15	S 14

New BT's: 22" D.Fir N. 51° W. 64.0 ft. mkd. T31S R6W S10 CS BT.
25" D.Fir S. 8° W. 39.6 ft. mkd. T31S R6W S15 CS BT.
5" D. Fir S. 57° E. 45.0 ft. mkd. T31S R6W S14 CS BT.
Note - This corner lies in corner of cut unit. No trees in SE Quad.

\- - - - - - - -

95

Wit. Cor.
Sec. Cor. to Sections 11 - 12 - 13 - 14.
Found - 8" Corner Tree, now stob, under 56" Fir, scribe visible on East Side.
10" D.Fir, now snag, S. 45° E. 19.1 ft., shows good scar.
10", now 15" D. Fir S. 60° W/ 4.6 ft. , shows good scar.
12", now 15" Laurel N. 72° E. 42.9 ft., shows old scar, rotten center.
No trace of N.W. Laurel.
Set-Brass Cap for Wit. Cor. Mkd: County Surveyors Office 1966

T 31 S	R 6 W
S 11	S 12
S 14	S 13

New BT's: 6@ Cedar N. 54° W. 25.9 ft. mkd. T31S R6W S11 CS BT.
10" Laurel N. 22½° E. 36.0 ft. mkd. T31S R6W S12 CS BT.
No trees in SE Quad.
Note - This corner lies i notch in large blow down 12.0 ft. East of roots. Also, about 125 ft. N. of small ravine, running NE.

John M. Powell
Frank Jones & Cliff Stone
Sept. & Oct. 1966
C. S. File No. 54/31

\- - - - - - - - -

96

¼ Corner to Sections 13 and 14.
Found - 18", now 33" D. Fir Snag, S.22° E. 7.9 ft., faint bark scribe visible @¼S@.
No trace of N.W. Chinq. BT., however part of this tree(?) nailed to D. Fir, shows @S" scribe.
Set - Brass Cap at Cor. Mkd: County Surveyors Office, 1966 — T 31 S R 6 W, ¼ S 12/S 13
New BT*s: 29" D.Fir S. 85° E. 26.1 ft. mkd. ¼ S13 CS BT.
42" D. Fir Stump S. 49° W. 30.7 ft. mkd. ¼ S12 CS BT.
No trees in Sections 12, cut unit.
Note - This corner lies north of old logging road about 250 ft. & North of small ravine about 100 ft.

\- - - - - - -

97

¼ Corner to Sections 12 and 13.
Found - Mound of Stones & 1" Iron Pipe 1" x 24", & stone with "¼" which has been moved. See Ren. #8.
15", now 20" D. Fir S. 68° W. 17.0 ft., (to face) bark scribed.
No trace of S.E. Laurel BT.
Set - Brass Cap at Cor. Mkd: County Surveyors Office 1966

T 31 S	R 6 W
¼ S 12	
S 13	

Reblazed & Rescribed: 20" D.Fir S.68° W.17.7 ft. mkd. ¼ S13 CS BT.
New BT: 18" Laurel N. 49° E. 45.4 ft. mkd. ¼ S12 CS BT.
Note - Spring bears South 5.0 ft.

\- - - - - - -

98

¼ Corner to Sections 1 and 12.
Found - No trace of Iron Rod mentioned in Ren. #7.
Orig. 10" D.Fir,now snag, S.49°W. 31.0 ft. Tree opened & burnt Re-open lower for scribe "T".(Find dist. to be 25.8 ft.)
Orig. 7" Fir, now down, N.-W. 15.0 ft., scribe marks visible "¼S". (This tree pushed out by skid trail)
By using the 2 orig.bear.& 1 dist., of 26.0, I renew this corner:
Set - Brass Cap at Cor. Mkd: County Surveyors Office 1966

T 31 S	R 6 W
¼ S 1	
S 12	

New BT: 20" D. Fir S. 5° E. 63.6 ft. mkd. ¼ S 12 CS BT.
Note - This corner lies in cut unit about 300 ft. E. of Road.