

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

105

Sec. Cor. to Sections 25 - 26 - 35 - 36.
Found - 1961 Co. Surveyor Brass Cap at Cor. mkd. accordingly. Ren. #47
Orig. 36" Fir, now stump, S. 65° E. 37.0 ft.
Orig. 40", now stump(Fir), S. 55° W. 52.8 ft.
7" Fir, now snag, S. 31° E. 25.2 ft., shows pitched over face.
Orig. 40" Fir, now 40" N. 15° W. 8.6 ft., scribe marks visible.
50" Fir N. 51° E. 46.7 ft., shows pitched over scribing.
6", now 7" D. Fir S. 23° W. 18.6 ft., shows good scar.
6", now 7" D. Fir N. 50° E. 79.7 ft., shows good scar.
New BT: 7" D. Fir S. 24° W. 27.3 ft. scribed T31S R6W S36 CS BT.

106

1/4 Corner to Sections 26 and 35.
Found - 1" Iron Pipe at 1/4 Corner. Ren. #23.
Orig. Fir Snag, S. 85° W. 9.9 ft., no scribe visible.
14" Fir S. 54° E. 13.5 ft., scribe visible "1/4 35 CS BT" (I find this tree to be a Yewwood, dist. to face of tree.)
No trace of NW Maple BT.
Unrecorded 20" D. Fir N. 36° W. 65.6 ft., opened for scribe "1/4 S26 CS BT.
(By ring count, I find scribing on D. Fir to be 1959, 7 yrs., This is the time G. Wenderoth renewed this corner.)

" 1966 BRASS Cap Set
Almanac I.P. -
This 14" Fir. Left out of
Typed Notes - Added
3/20/66 J.R.

RE-RENEWED - SEE CORNER NO. #157

107

Sec. Cor. to Secs. 28 - 29 - 32 - 33.
Found - 1/2" Iron Pipe, torn out of ground. See Ren. #18.
4", now 6" W. Fir, S. 77 1/2° E. 74.8 ft., scribe marks visible.
4", now 7" D. Fir, N. 38° E. 36.5 ft., shows good scar.
4", now 6" D. Fir N. 4° W. 76.4 ft., scribe marks visible.
6" Fir, blown down, S. 12 1/2° W. 66.1 ft.
Set - Brass Cap at Cor. Mkd: County Surveyors Office
1966
New BT: 40" D. Fir N. 84, W. 89.4 ft. scribed T31S R6W S29 CS BT.
Note - This corner lies on south edge of road. Squared Stake at Brass Cap.

JOHN M. POWELL
Frank Jones and Cliff Stone
October, 1966
C. S. File No. 54/31

RE-RENEWED - SEE CORNER NO. #137

108

Sec. Cor. to Secs. 22 - 23 - 26 - 27.
Found - 1" Steel Drill at Corner, See Ren. #14.
Orig. 8", now 17" Laurel N. 52° E. 16.5 ft., shows old scar but rotten.
Orig. 10", now 13" Laurel S. 20° E. 20.5 ft., opened scribe visible @R6W S26".
Orig. 8", now 12" Laurel, N. 60° W. 36.3 ft., shows old scar.
20" D. Fir, now 22", S. 76 1/2° W. 77.8 ft.
40" D. Fir, now 40", N. 45° W. 58.0 ft.
18" D. Fir, now 18", N. 59 1/2° W. 68.5 ft. (find this bear. to be N. 59 1/2° E.)
(Trees have been blazed but no scribing present.)
Set - Brass Cap at Cor. Mkd: County Surveyors Office
1966
New BT's: 24" D. Fir S. 3° E. 24.5 ft. scribed T31S R6W S26 CS BT.
4" D. Fir S. 53° W. 14.6 ft. scribed S 27 CS BT.
10" D. Fir N. 20° W. 15.3 ft. scribed T31S R6W S22 CS BT.
Reblzd. & Rescrbd: 17" Laurel N. 52° E. 16.5 ft. mkd. T31S R6W S23 CS BT.

SEE M 96-32
(Baughman - Mar. 1984)

CAP STAMPED PAGE
CORRECTLY
G. GIBSON
9/81 D.C. 50.

109

Sec. Cor. to Sections 26 - 27 - 34 - 35.
Found - Orig. 16", now 29" D. Fir S. 30° E. 11.2 ft., faint bark scribe @T3".
Orig. 16", now 21" D. Fir S. 65° W. 31.0 ft., shows good scar.
10", now 21" D. Fir, N. 66° W. 27.1 ft., shows good scar.
No trace of NE BT.
Set - Brass Cap at Cor. Mkd: County Surveyors Office
1966
Reblzd. & Rescrbd: 29" D. Fir S. 30° E. 11.2 ft. mkd. T31SR6W S35 CS BT.
New BT: 10" D. Fir N. 39° E. 25.5 ft. mkd. T31S R6W S26 CS BT.