

Douglas County Surveyor's Record of  
Government Corners Renewed

T 31 T. S. R 6 R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

139

C O N T - - - - -

Douglas Co. Surveyor  
Office  
Gary Langlitz, Party Chief  
Karen Reed; L.E. Monrean  
Peter Earle  
June 4, 1979  
RM 3 - 26 C.S. 61/3

A 12" D. Fir scribed "T30S R6W S36 CS BT" on a double blaze bears N.74 1/2°W., 83.6 ft.  
A 28" D. Fir scribed "T31S R5W S6 CS BT" on a double blaze bears S.52 1/2°E., 32.1 ft.  
Found - From Wenderoth's I.P. Ren. #2, we find the following BT's:  
A 26" Fir, now a 20" rotted stump with no marks visible on open double blaze bears N.81 1/2°E., 16.7 ft. (Rec. N.8-°28'E. 16.0 ft.)  
An 8" now 12" I. Cedar, alive with well healed double blaze bears S. 5 1/2°E., 41.6 ft. (Rec. S.5°35'E., 41.6 ft.)  
An 18" Fir now an 18" stump with scribing "5 CS S36 BT" visible on an open double blaze bears N.27°W., 26.6 ft. (rec. N.26°53'W., 26.6 ft.).  
A 26" now 28" D. Fir alive with well healed double blaze bears S.80°W., 44.5 ft. (Rec. S.80°00'W., 44.5 ft.)  
Bearing trees marked by J.W. Byron, 1963, Ren. #59 referencing monument set by Wenderoth:  
A 14" Maple alive with well healed single blaze bears North 37.6 ft.  
A 6" now 10" D. Fir alive with well healed double blaze bears N.70°E., 30.9 ft.  
We chop out and destroy entirely all markings found on Wenderoth's 1946 bearing trees and on Byrons 1963 BTs. We leave the I.P. set by Wenderoth at its found location.

6/4/79

140

Gary Langlitz, Party Chief  
L.E. Monrean; Peter Earle; S.J. Flause  
F.C. Silagy  
May 30, 1979  
RM 3 - 26  
C.S. 61/3

WITNESS CORNER - 1/4 Corner for Sec. 1; and Sec. 6 of T.31-5  
Found - Orig. 1855 4" diam. Fir now an 11" snag. We opened blaze on West face and find scribing "1/4 S" marked on corner tree.  
Orig. 6" now 28" Fir with well healed blaze (not visible" bears S.87°W., 5.3 ft.  
Other Orig., A Laurel to the Northeast not found.  
Also find a bearing tree scribed to reference the 1/4 corner set in 1878 survey scribed "S" visible on previously opened blaze on 10" now 11" Fir (now a snag) bearing S.37 1/2°E., 11.9 ft.  
The 1878 1/4 corner position bears N.19°59'13"W., 74.76 ft. from the Original 1855 1/4 corner position.  
Set - A witness corner: A 1"x36" I.P. with brass cap attached on line with orig. southerly line tree. Cap bears S.1°98'37"W., 5.00 ft. from orig. 1/4 corner tree. Cap is stamped "Douglas County Surveyor T31S WC R6W 1/4 S1 S6 R5W 1979"  
New BT's- (NOTE: NEW TREES BEARINGS AND DISTANCES REFER TO ORIGINAL 1/4 CORNER POSITION, NOT THE WITNESS CORNER)  
A 20" D. Fir scribed "1/4 S6 CS BT" on a double blaze bears N.41°E. 8.9 ft.  
A 18" D. Fir scribed "1/4 S6 CS BT" on a double blaze bears S.34°E. 28.3 ft.  
A 26" D. Fir, bark scribed "1/4 S1 CS BT" bears S.18°W., 44.3

5/30/79

141

1/4 Corner for Sec.1; and Sec. 36 of T.30-6  
Note - A careful search of the area reveals no trace of the original corner monument or accessories. We therefore proceed to determine a survey location by single proportionate measurement.  
Found - From our 1979 survey location, a 3/4" I. pipe set by Wenderoth in 1946 (Ren. #1 and O.S. 39/18) bears N.43°33'55"W., 16.50 ft. Wenderoth's 3/4" I.P. was set along the west side of the stump of a fir tree which was marked as the corner tree by Cain in 1919. (Ren. #8 in T.30-6). Neither Cain nor Wenderoth specifically describe the old bearing trees that they allegedly found and we cannot find conclusive evidence of the remains of the orig. BTs. The area around this corner is basically undisturbed except for scattered cutting of Fir and Oak trees. We do not accept the corner position adopted by Cain and Wenderoth.  
Set - At our 1979 survey location, we set a 1" x 36" I.P. 34" in the ground with brass cap attached marked: "Douglas County Surveyor" T30S R6W 1/4 S36 S1 T31S 1979.  
and mark the following bearing trees: (Note: During the month of May, 1979, we set a monument and marked new bearing trees for this corner position which

C O N T . N E X T P A G E