

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 6 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

Eugene A. Bloom
LS #492
For: U.S. Forest Ser.
April 1980
M 79 - 33

146

Center 1/4 Corner Section 6.
Set - 5/8" Iron rod with rock mound.
BT's - 6" D. Fir bears S.78°E., 13.1 feet scribed "C 1/4 S6 BT".
6" D. Fir bears N.19°E., 6.5 feet scribed " C 1/4 S6 BT".

147

Section Corner for Secs. 15,16,21 and 22
Fd.- 38" Douglas fir snag original corner tree.
30" Douglas fir original BT snag, no marks bears N.57°W., 14.0
ft. to face.
48" Douglas fir original BT snag, no marks bears S.35°E.,
44.2 ft. to face.
8" Douglas fir original BT down snag, scribes visable
bears N.36°E., 10.6 ft. to face.
Brass cap witness corner (per Ren. #75) bears West, 4.0 ft.
3" Douglas fir BT now down bears N.6°E., 4.0 ft.
4" Douglas fir BT now down bears S.58°E., 14.3 ft.
10" Douglas fir BT with face bears S.10°W., 23.4 ft.
New BT's - 10" Douglas fir scribed "T31S R6W WC S16 BT". bears N.48°W.,
4.1 ft.
10" Douglas fir scribed "T31S R6W WC S15 BT" bears N.26°E.,
18.0 ft.
8" Douglas fir scribed "T31S R6W WC S22 BT" bears S.38°E., 9.8
ft.
Note: Corner lies 60.0 ft. East from top of ridge and main access road.

148

1/4 Corner for Secs. 16 and 17
Set - Brass cap mkd. T31S R6W, W.M. 1/4S S17, S16 RLS 430 1980
BT's - 6" Douglas fir scribed "1/4 S S16 BT" bears S.78°E., 10.9 ft.
6" Douglas fir scribed "1/4S S17 BT" bears N.88°W., 16.2 ft.
Note - The brass cap falls snugly up against a 6" Douglas fir stump.

149

1/4 Corner for Secs. 9 and 16
Set - Brass cap mkd. "T31S R6W, W.M. 1/4S S9, S16 RLS 430 1980
BT's - 40" Douglas fir bears N.59°W., 16.0 ft. scribed "1/4S S9 BT".
5" madrone bears S.6°W., 21.4 ft. scribed "1/4S S16 BT".
42" Douglas fir bears S.26°E., 18.4 ft. scribed "1/4S S16 BT".

150

1/4 Corner for Secs. 15 and 16
Set = Brass cap mkd. "T31S, R6W, W.M. 1/4S S16, S15 RLS 430 1980.
BT's - 28" Douglas fir bears S.18°W., 19.8 ft. to face scribed "1/4S
S16 BT".
36" Douglas fir, original BT snag bears N.20°E., 32.3 ft. to
face.
30" Douglas fir bears S.8°E., 28.8 ft. to center scribed
"1/4S S15 BT".

151

Section corner for Secs. 3 & 2; and 34, 35 of T.30-6
Found - 1969 County brass cap properly marked. Ren. #129
22" now 23" oak, S.36°30'E., 70.0 ft. with visible "31S 6W
S2 CS BT" showing in rotted face. This tree has been cut into,
in a search for old scribing & will probably not live.
7" now 12" cedar with well healed double blaze bears N.81°W.,
37.6 ft.
23" now 25" fir with "30S R6W S34 CSBT" visible in partially
healed blaze bears N.15°W., 10.7 ft.
14" now 16" fir with "31S 6W S3 CS" visible in partially healed
blaze bears S.25°W., 40.5 ft.
New BT - 9" Fir bears S.11 1/2°E., 33.8 ft. scribed T31S R6W S2 CS BT in
double blaze.

fd OK - 2-94 - 1994 - 0012

4/23/81

Bruce A. Shaner LS#430
For: C & D Lumber Co.
June 1980
RM 3 - 32

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
April 23, 1981
C.S. 61/19