

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

166

Bruce Shaner L.S. 430
For: Richard McKenzie
John Wright -
Clem Berlier
Oct. 1993
M 117-76
C.S. File 63/153

Cor. Secs. 13 & 24 T31-6; 18 & 19 T31-5
Found - 2 1/2" Brass cap on a 1" Iron Pipe (Ren. # 84) from which:
1 1/2" Iron Pipe bears N.44°E., 1.7'.
8" D.Fir, face overgrown, bears N.47°E., 29.7' (rec. N.44°E., 30.4').
12" Live Oak, face overgrown, bears S.65°E., 36.1'.
11" Live Oak, scribes visible, bears N.7°E., 25.1' (rec. North, 25.7').
11" Live Oak, stump, scribes visible, bears S.42°W., 14.1'.
12" Live Oak, face rotted out, bears N.47°E., 25.4' (rec. N.43°E., 26.4')

New Accessories -

12" D.Fir, scribed "T31S R6W S24 BT", bears S.68°W., 60.4'.
10" Live Oak, scribed "T31S R6W S13 BT", bears N.32°W., 48.6'.

Note - Corner lies North 230' above spur logging road.

167

Mark Smalley, L.S. #2354
For: Kenneth Ford
July 1994
M 120-43

1/4 Cor. Secs. 31; 30 T31-7
Found - 1 1/2" IP & 1966 County BCIP (Not set) (REN # 112)
28" Fir, N.34°W., 15.2', stump.
16" Fir, N.58°E., 14.8' (19.8) Part. healed.
New BTs - 6" Yew, N.44°E., 24.0', "1/2 BT"
30" Fir, S.58°E., 23.5', "1/2 BT"
28" Fir, S.35°E., 47.6', "1/2 BT"

[Faint mirrored text from the reverse side of the page is visible through the paper, including details about corner locations and bearings.]