

Douglas County Surveyor's Record of  
Government Corners Renewed

31 T. S. 7 R. W. W. M.

ROSE-CHAPMAN CO., EUGENE, ORE. 97196

Claude Keir  
Reg. Eng. # 2125  
July 23, 1951  
C.S. 40/344

1  
Cor BET. 10-11-15-14  
All four BTs found. The BT bearing S 16° E for 36 Lks has part of the bark scribe showing. This is now a snag. The large 60" Fir, bearing N 56° W for 56 Lks. is now a windfall. I left my cruiser mark "K" on the two remaining BTS and set a 4' fir stake at the corner marked S10, S11, S14, and S15. **85**

2  
1/4 CORNER 14-15  
I also found both BTs for the 1/4 corner for 14 & 15, T 31 S, R 7 W. The 12" Fir (now a 24" Fir) bearing N 36° W for 21 Lks. is in good condition with the old face grown over. The 20" Fir (now a 38" Fir) bearing S 30° E for 30 Lks. has the legible bark scribe 1/4 S still on it. I left my cruiser mark "K" on both BTs. I reset the 1/4 corner stake from the notes. The 3"x4' stake was marked 1/4 S 14 on East side, and 1/4 S 15 on the west side. **84**

J. W. Byron, Deputy Co. Surveyor  
Ray Irving  
John Fee  
September 21, 1954  
Done for Robert M. King.  
Filed in 46/38.

3  
1/4 corner to secs. 3 and 4.  
Found:  
Brass Cap.  
8 inch Laurel, N.80°W., 11 lks dist., dead.  
24 inch Laurel, S.65°E., 30 lks dist., in good condition.  
(S.40°E., 30 lks per record)  
Blazed and Scribed:  
10 inch R. Fir, S.10°W., 49.2 feet dist., mkd. 1/4 S 4 CS BT.

FD. 2/6/61  
H. JOHNSTONE  
M8L-62  
M99-61

4  
1/4 corner to secs. 2 and 3.  
Found:  
Rock mound, N.27°E., 25 feet.  
O. B. T. - 32 inch pine, S.23°E., 35 lks dist. in good condition.  
(S.88°E., 30 lks per record).  
At point for corner found mound of rock. **65**  
Blazed and scribed two new trees:  
18 inch pine, N.77°E., 97.8 feet dist mkd. 1/4 S2 CS BT.  
12 inch pine, N.16 1/2°W., 44.3 feet dist mkd. 1/4 S3 CS BT.

Clifford M. Bryden  
For Roseburg Lumber Co.  
Feb. 14, 1957  
File 42/249.

5  
Sec. corner to secs. 25, 26, 35 and 36.  
Found Old B. T. - Y. Pine, 24 inches, N.29°W., 25.4 feet.  
4 inch x 4 inch x 4 foot post (squared) post at corner.  
New Witness trees:  
6 inch Fir, N.30°E., 11.0 feet.  
6 inch Fir, S.84°W., 13.5 feet.  
Scribed R. E. 3937 BT. **13**  
**39**

Howard W. Johnstone  
For Roseburg Lumber Co.  
May 31, 1960  
Map File M 18 - 66

6  
Section Corner to Secs. 24 & 25, 31-7 & Secs. 19 & 30, 31-6.  
Set Section Corner - 1 1/2" x 24" Iron Pipe.  
6" D. Fir S.88°W. 32.8 feet.  
14" D. Fir S.63°E. 35.0 feet.  
30" D. Fir N.10°E. 55.1 feet.  
7" S. Pine N.55°W. 23.9 feet. **99**

7  
1/4 Sec. Cor. to Sec. 24, 31-7 & Sec. 19, 31-6  
Set 1/4 Corner - 1" x 24" Iron Pipe  
15" D. Fir S.31°E. 25.1 feet  
7" D. Fir S.66°W. 29.2 feet

Howard W. Johnstone  
For Roseburg Lumber  
Jan. 4, 1961  
C. S. File No. 51/163

8  
Sec. Cor. to Secs. 25 - 36, T31-7W. & Secs. 30 - 31, T31S R6W.  
Found - 6" Madrone N.66°W. 21.1 ft., scribe visible.  
5" Madrone S.34°W. 26.4 ft., down.  
Set - 4" x 4" Cedar Post.  
20" D. Fir S.57°W. 32.5 ft.  
8" D. Fir S.18°E. 24.0 ft.  
16" D. Fir N.46 1/2°W. 57.0 ft.  
6" D. Fir N.78°E. 38.0 ft. **50**