

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

28

Section Corner to Sections 16 - 15 - 21 - 22.
Found - All Orig. Bearing Trees, all check record.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

S16	S15
S21	S22

 T31S R7W
New BT: 5" Fir bears East 3.8 ft. scribed S22 CS BT.

29

$\frac{1}{4}$ Corner to Sections 17 and 16.
Found - Orig. 16", now 36" Fir Snag N.6°E. 5.9 ft., shows good bark scribing " $\frac{1}{4}$ BT".
Stump Hole that checks for S.W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{1}{4}$ S17/S16 T31S R7W
New BT's: 7" R.Fir bears S.47°W. 26.5 ft. scribed $\frac{1}{4}$ S17 CS BT.
8" Live Oak bears S.78°E. 17.0 ft. scribed $\frac{1}{4}$ S16 CS BT.

30

Sec. Cor. to Secs. 13 & 24, T31-7 & Secs. 18 & 19, T31-6W.
Found - $\frac{3}{4}$ " I.P. at Cor. & all BT's. except S.E. BT.
N.E. & S.W. BT's. show scribe.
Set - Brass Cap alongside Cor. Pipe & Mkd:

S13	S18
S24	S19

New BT's: 14" R.Fir bears S. 6° E. 29.5 ft. scribed T31S R6W S19 CS BT.
12" R.Fir bears S.46°W. 45.9 ft. scribed S24 T31S R7W CSBT.
24" R.Fir, now R.Fir 13.8 ft. N.20°W. Rescribe T31SR7WSL3CSBT.

31

$\frac{1}{4}$ Corner to Sections 12 and 13.
Found - Both Orig. BT's. Orig. S.W. BT., previously opened, shows good scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{1}{4}$

S12
S13

 T31SR7W
New BT's; 23" Cedar bears S.59°E. 40.6 ft. scribed $\frac{1}{4}$ S13 CS BT.
Rescribe Orig. N.W. 36" R.Fir N.26°E. 17.2 FT. $\frac{1}{4}$ S12 CS BT.

32

$\frac{1}{4}$ Corner to Sections 2 and 11.
Found - Both Orig. BT's. Orig. 30", now 36" Pine, shows good scribing on old face S.55°W. 30.4 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{1}{4}$

S 2
S11

 T31S R7W
New BT's: 7" Laurel bears N.27°E. 15.7 ft. scribed $\frac{1}{4}$ S2 CS BT.
Rescribed, now 38" Pine S.55°W. 32.0 ft. $\frac{1}{4}$ S11 CS BT.

33

Sec. Cor. To Secs. 3 & 2, T31-7W. & Secs. 34 & 35, T30-7W.
Found - Orig. 15", now 26" Pine S.85°W. 19.8 ft., shows good scribng.
Orig. 24", now 38" Pine Snag, shows old axe work N.63°E. 139.9 ft.
Other Orig. BT's. not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962

S34	S35
S 3	S 2

 T30S R7W T31S
New BT's: 23" Cedar bears N.30°E. 13.6 ft. scribed S35 T30S R7W CS BT.
12" Pine bears S.31°E. 8.7 ft. scribed S2 T31SR7W CS BT.
9" Pine bears N. 3° W. 47.3 ft. scribed S34 CS BT.

34

Section Corner to Sections 23, 24, 25 and 26.
Found - 34" Fir S.40°E. 19.1 ft. (bark scribed and now a snag)
Set - 1" x 30" Iron Pipe.
Scribed - 12" Cedar N.62 $\frac{1}{2}$ °E. 25.9 ft.
6" Fir S.78°E. 11.2 ft.
34" Fir S. 6° W. 43.0 ft.
5" Fir N. 9° W. 20.7 ft.

James W. Byron, Deputy
John Powell and
Wm. Stoffel
Oct. 31, 1962
C.S. File No. 49/109

James W. Byron, Deputy County Surveyor
Mike Darby & Wm. Stoffel
December 1962
C. S. File No. 49/109

FD on 10/84
H. Johnson
M 97-26

Howard W. Johnstone
For Roseburg Lumber
Jan. 30, 1963
C. S. File No. 51/163