

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

41  
1/4 Section Corner to Sec. 34, T30 and Sec. 3, T31-7W.  
Found - 1" Iron Pipe & Mound of Stone at Corner.  
Now 16" Pine BT. S.49°E. 49.0 ft., All as recorded, See Cor. No. 7, T30-7W.  
New BT: 17" Cedar bears S.43°W. 99.8 ft. scribed 1/4 S8 CS BT.

James W.  
Byron  
& Crew  
Feb.  
1964  
C.S. File

42  
Section Corner to Secs. 3 & 4, T31-7W. & Sec. 33 & 34, T30-7W.  
Found - GLO Brass Cap at Corner. N.E. & SE BT's. O. K.  
S. W. BT., now Stump. N.W. BT., not found.  
New BT's: 14" R. Fir bears S.86°W. 24.7 ft. scribed T31S R7W S4 CS BT.  
7" Myrtle N.10 1/2°W. 12.9 ft. scribed T30S R7W S33 CS BT.

No. 53/40

43  
Section Corner to  
T30S  
R8W  $\frac{S\ 36\ | S\ 31}{S\ 1\ | S\ 6}$  R7W  
Found - Brass Cap at Cor. & all BT's. as recorded, GLO notes, 1918  
S. W. Bearing Tree, now rotted stump.  
New BT: 6" R. Fir bears S.29°W. 4.5 ft. scribed S1 T31S R8W CS BT.

44  
Section Corner to Secs. 34 & 35, T31-7W. & Secs. 3 & 2, T32-7W.  
Found - Cadastral Brass Cap and 4 BT's:  
20" D. Fir S.35°E. 44.4 ft. - 11" D. Fir N.36°E. 53.6 ft. *Ren. #17*  
Orig. 43" D. Fir N.54°W. 72.0 ft. - 15" D. Fir S.78°W. 65.0 ft.  
Set - Wit. Cor. 100.0 ft. South.  
Brass Cap Mkd: County Surveyor's Office, 1964  
T31S R7W  $\frac{S34\ | S35}{S\ 3\ | S\ 2}$   
W.C. 100 ft. N.  
New BT's: 11" D. Fir N.80°W. 14.6 ft. Mkd: W.C. T31S R7W S34 CS BT.  
9" D. Fir S.1°E. 20.4 ft. Mkd: WC T32S R7W S2 CS BT.  
10" Cedar S.15°W. 31.2 ft. Mkd: WC T32S R7W S3 CS BT.  
11" Laurel N.51°E. 15.0 ft. Mkd: W.C. T31S R7W S35 CS BT.  
The Wit. Cor. Lies on top of Small Spur.  
Sept. 1, 1964

V. R. Tracy  
Sept. 1964  
C.S. File 49/109

45  
1/4 Corner Section 33 only, South Bdry. T30S R7W.  
Found - GLO Brass Cap mkd: "1/4 S 33 1918 at Corner Point.  
24", now 28" Yellow Pine N.25°E. 14.5 ft., face burned,  
shows "S33" scribe.  
5" Fir rotted stump N.44 1/2°W. 16.5 ft., trace of  
reverse scribe.  
New BT's: 10" Pine N.12°W. 40.4 ft. Mkd: 1/4 S33 CS BT.  
26" Pine N.74°E. 33.7 ft. Mkd: 1/4 S33 CS BT.  
Note - This corner lies approx. 100 ft. W. of small creek  
flowing N. W.

Vernone "Ray" Tracy  
M. Darby & J. Berneth  
March 1965  
C. S. File 53/40

46  
1/4 Section Corner to Sections 20 and 21.  
Found - Orig. 14", now 17" Laurel S.39°E. 21.8 ft., open & find  
face had rotted before tree healed, face edges show axe marks.  
Orig. 12", now 16" Laurel N.78°W. 35.6 ft., down & dead,  
found reverse "1/4" scribe.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965  
T31S R7W 1/4 S 20/S 21  
New BT's: 10" D. Fir S.47°W. 23.0 ft. Mkd: 1/4 S20 CS BT.  
11" Pine N.47°E. 29.6 ft. Mkd: 1/4 S21 CS BT.  
Note - This corner lies on fairly steep S. W. slope of spur ridge  
approximately 200.0 ft. south of top.

C. S. FILE No. 54/3  
APRIL 1965

47  
Section Corner to Sections 16 - 17 - 20 - 21  
Found - Orig. 38", now 42" Fir S.25°W. 19.1 ft., shows "T3S" on old  
bark scribe. This BT now Snag approx. 60.0 ft. high.  
All other BT's. gone.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965  
T31S R7W  $\frac{S17\ | S16}{S20\ | S21}$   
Corner point falls on 14" Log, Set Brass Cap under Log.  
New BT's: 14" D. Fir N.10°W. 34.0 ft. Mkd: T31S R7W S17 CS BT.  
26" D. Fir N.70°E. 37.6 ft. Mkd: T31S R7W S16 CS BT.

(continued)