

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

New BT's: 24" D.Fir S.33°E. 43.6 ft. Mkd: T31S R7W S21 CS BT.
26" D.Fir S.46°W. 51.7 ft. Mkd: T31S R7W S20 CS BT.

Note - This corner lies in small ravine sloping N.40°E.
April 16, 1965

1/4 Corner to Sections 5 and 4.

Found-1918 GLO Brass Cap Mkd: "1/4 S5/S4 1918".
7", now 12" Fir S.5°E. 28.4 ft., down. Open & find "E" scribe.
24", now 18" Y. Pine N.71 1/4°W. 93.7 ft., down & badly rotted, &
shows "1/4 S" scribe.

No trace Orig. Madrone BT.

New BT's: 21" D. Fir S.21°W. 29.4 ft. Mkd: 1/4 S 5 CS BT. #
7" D.Fir S.84°E. 64.8 ft. Mkd: 1/4 S4 CS BT. #

Note - This corner lies 10.0 ft. west of dry ravine, course S. E.
May 17, 1965

1/4 Corner to Sections 30 and 31.

Found - Orig. 7", now 21" Fir S.70°W. 38.3 ft., shows "1/4" scribe
in opened tree.

No trace of other BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T31S 1/4 S 30 R7W
Office, 1965 S 31

New BT's: 6" D.Fir N.38°E. 1.8 ft. Mkd: 1/4 S30 CS BT.
10" D.Fir S.72°E. 38.3 ft. Mkd: 1/4 S31 CS BT.

Note - This corner lies approximately 200 ft. W. of ridge top.
June 7, 1965

Closing Corner Sections 6 and 5.

Found - GLO Brass Cap at Corner & BT's. as recorded in 1918.
14", now 18" Fir S.62°45'E. 66.7 ft., shows very good scar.
(alive & good condition)
6", now 8" B.Oak S.21°15'W. 29.0 ft., shows good scar, top
broken out, tree appears to be dying.

New BT: 16" D.Fir S.49°W. 7.4 ft. Mkd: T31S R7W S6 CS BT.
This corner lies on ridge top. S.E. BT. is on edge of bluffs running
N.E. & S.W. Approximately 103 ft. West of "A.P." corner.

Section Corner to Secs. 31 & 32, T30-7W.

Found - GLO Brass Cap mkd. in 1918 & BT's. as follows:
12", now 14" Live Oak N.32°E. 22.4 ft., scar is unhealed,
center rotted out.
12", now 26" Fir N.70°W. 7.9 ft., show very good scar, alive
& in good condition.

New BT: 26" D.Fir N.48°E. 38.1 ft. Mkd: T30S R7W S32 CS BT.
Note - This corner lies on very steep E. slope broken with bluffs &
rock outcrops approx. W. of Creek flowing south.

"AP" Corner between Above C.C. & Section Corner.

Found - GLO Brass Cap Mkd: AP & BT's. as follows:
1918
18", now 24" Fir S.37°W. 20.5 ft., shows very good scar, good cond.
5", now 9" Y.Pine N.1°W. 9.2 ft., shows scribe on unhealed scar.
This tree is now dead due to porcupine damage.

New BT: 8" D.Fir N.5°E. 12.3 ft. Mkd: "AP CS BT" (5 ft. off ground)
Note - This corner lies approx. 103.0 ft. E. of Cor. of S 6/S 5 on
S. boundary of Sec., T30-7W.

"AP" Brass Cap is set in rock mound at foot of overhanging
Rock Bluff approx. 30 ft. high.

Vernon R. Tracy
Mike Darby & Terry Connell
May - June 1965
C. S. File No. 54/3

Vernon "Ray" Tracy
Mike Darby & Terry Connell
June 1965
C. S. File No. 53/40

48

49

50

51

52

* PO. OK
2/6/81 H.
Johanna
N 82-62