

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

65

$\frac{1}{4}$  Corner to Sections 3 and 2.  
Found - Mound of Stone at  $\frac{1}{4}$  Corner, See Ren. #4.  
Orig. 32" Pine, now dead, S. 23° E. 23.1 ft.  
18", now 21" Pine, N. 77° E. 97.8 ft., pitched over, scrb. vis.  
12", now 14" Pine, N. 16 $\frac{1}{2}$ ° W. 44.3 ft., scribe visible "BT".  
Set - Brass Cap at Cor. Mkd: County Surveyors T31S R7W  
Office, 1966  $\frac{1}{4}$  S 3/S 2  
Bearing Trees are O.K. This corner lies on top of open ridge,  
running about east & west.

FD. OK. 10/80  
H. Johnson  
M 97-61

66

$\frac{1}{4}$  Corner to Section 18, T31-7W. & Sec. 13, T31-8W.  
Found - 16", now 36" D. Fir, S. 42° W. 18.5 ft. Some marks visible,  
I believe to be scribe marks. Also, notches in  
bark below face which is common to Byar's work.  
18" D. Fir, now down & burnt, S. 58° E. 46.2 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyors T31S $\frac{1}{4}$  R8W S13/S18 R7W  
Office, 1966  
New BT's: 7" Live Oak S. 1° W. 20.2 ft. mkd.  $\frac{1}{4}$  S 13 CS BT.  
9" Live Oak N. 5° E. 6.0 ft. mkd.  $\frac{1}{4}$  S18 CS BT.

67

$\frac{1}{4}$  Corner to Sec. 30, T31-7W. & Sec. 25, T31-8W.  
Found - 36", now 48" D. Fir, S. 25° W. 30.4 ft., bark scribed, faint.  
26", now 32" D. Fir, S. 85° E. 30.4 ft., shows old face  
opened for scribe "1 S".  
(Find this bearing & dist. to be S. 89° E. 26.4 ft.)  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S  
Office, 1966 R8W  $\frac{1}{4}$  S25/S30 R7W  
New BT's: 13" D. Fir N. 55 $\frac{1}{2}$ ° W. 26.0 ft. mkd.  $\frac{1}{4}$  S25 CS BT.  
10" D. Fir S. 63° E. 36.5 ft. mkd.  $\frac{1}{4}$  S 30 CS BT.

68

Sec. Corner to Sections 19 & 30, T31-7W. & Secs. 24 & 25, T31-8W.  
Found - Stone at Corner, 4 notches North, 2 notches, South.  
26", now 34" D. Fir, N. 66° E. 40.9 ft., no scribe  
visible, old face faint.  
14", now 20" D. Fir, S. 65° E. 7.9 ft., bark scribe faint.  
28", now 34" D. Fir, S. 45° W. 39.6 ft., bark scribed.  
20", now 24" D. Fir N. 42° W. 13.2 ft., bark scribed.  
Set - Brass Cap at Cor. Mkd: County Surveyors T 31 S  
Office R8W  $\frac{S}{S} \frac{24}{25} | \frac{S}{S} \frac{19}{30}$  R7W  
1966  
Reblazed & Rescribed: 20" D. Fir S. 65° E. 7.9 ft. scribed T31SR7WS30CS BT.  
34" D. Fir N. 66° E. 40.9 ft. mkd. T31SR7W S19 CS BT.

69

$\frac{1}{4}$  Corner to Sec. 33, T31-7 and Sec. 4, T32-7W.  
Found - Orig. 15", now 38" D. Fir, S. 70° E. 29.7 ft., bark  
scribed, faint "BT".  
Orig. 15", now 32" Fir, N. 70° W. 34.3 ft., bark scribed "1 S".  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's T 31 S  
Office  $\frac{1}{4}$  S 33 R7W  
1966 S 4  
Reblzd. & Rescribd. below Orig. Scribe: T 32 S  
38" D. Fir S. 70° E. 29.7 ft. mkd.  $\frac{1}{4}$  S 4 CS BT.  
7" D. Fir N. 42° E. 18.8 ft. mkd.  $\frac{1}{4}$  S 33 CS BT.  
G. L. O. Brass Cap bears S. 82° E. 19.1 ft. - REMOVED BRASS CAP (BACK) 1967  
Note - This corner lies in small draw about 400.0 ft. W. of creek.

RE-RENEWED, SEE CORNER NO. #118

70

$\frac{1}{4}$  Corner to Sections 14 and 13.  
Found - 42" D. Fir, now Snag, N. 50° E. 10.6 ft., bark scribed.  
36" D. Fir, now Snag, S. 45° W. 33.0 ft., old axe work, but no scribing.  
Set - Brass Cap at Corner Mkd: County Surveyor's T 31 S R 7 W  
Office, 1966  $\frac{1}{4}$  S 14/S 13  
New BT's: 8" Cedar S. 52 $\frac{1}{2}$ ° E. 11.2 ft. mkd.  $\frac{1}{4}$  S13 CS BT.  
9" D. Fir N. 61 $\frac{1}{2}$ ° W. 34.7 ft. mkd.  $\frac{1}{4}$  S 14 CS BT.

John M. Powell  
Frank Jones & Cliff Stone  
December, 1966  
C. S. File No. 54/36