

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE., 21881

71

$\frac{1}{4}$ Corner to Sections 13 and 24.
Found - 12", now 20" D. Fir, S. 26° E. 18.5 ft., opened for scribe "BT".
30", now 40" Cedar, N. 10° W. 23.8 ft. (bearing S. Be. N.10°E)
Tree had been opened, "S" visible
3/4" I. Pipe at Corner.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office 1966
T 31 S R 7 W
 $\frac{1}{4}$ S 13
S 24
New BT: 26" Fir S. 21° W. 18.3 ft. mkd. $\frac{1}{4}$ S 24 CS BT.
Note - Best way to reach corner is from cedar camp, down ridge running N. W. on old skid trail.

72

$\frac{1}{4}$ Corner to Sections 23 and 24.
Found - 12", now 14" Cedar, N. 39° W., (bearing should be N.27°W.)
Scribe visible, "S BT". Rings too fine to count.
34", now 46" Cedar, N. 80° E. 30.4 ft., shows good scar.
(find this bearing to be N.71 $\frac{1}{2}$ °E.)
16" Pine Corner Tree, now 27", Find no scribing on this tree.
Set - Brass Cap on West Side of Corner Tree Mkd: County Surveyor's Office, 1966
T 31 S R 7 W
 $\frac{1}{4}$ S 23 S 24
Bearing Trees O. K. and tagged. Corner lies very good for call at 45.50 chains, going north.

73

$\frac{1}{4}$ Corner to Sec. 7, T31-7W. & Sec. 12, T31-8W.
Found - 42", now 62" D. Fir, S. 75° E. 22.4 ft., faint scribe visible.
No trace of S. W. BT.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office 1966
R T 31 S R
8 S 12/S 7 7
W W
New BT's: 8" W. Fir N. 89 $\frac{1}{2}$ ° E. 53.2 ft. mkd. $\frac{1}{4}$ S 7 CS BT.
10" W. Fir N. 85° W. 32.9 ft. mkd. $\frac{1}{4}$ S 12 CS BT.

MICROFILM TO HERE 10/67

74

Township Corner
R T 31 S R
7 S 36 S 31 6
W S 1 S 6 W

Set - 5/8" x 30" Rod and Alum. Cap by double proportionate measurement.
Scribed: 16" D. F. S. 28° W. 42.3 ft.
8" D. F. S. 43° E. 44.6 ft.
9" D. F. N. 57° W. 10.2 ft.
9" D. F. N. 72° E. 56.2 ft.

February, 1969

75

$\frac{1}{4}$ Corner to Sec. 36, T31-7W. and Sec. 1, T32-7W.
Set - 1 $\frac{1}{2}$ " x 24" I. Pipe, set by proportionate measurement.
Scribed: 20" I. C. N. 25° E. 34.5 ft. #132
21" W. P. S. 24° E. 28.2 ft.

76

Section Corners to Sections 5,4,8,9.
Found 50" Pn Now 50" N. 59E 50.2 Shows scar (OBT)
20" Pine Now 28" S79E 68.0 Scribe visible but pitched over
20" Pine now 28" S 15W 36.3 Shows good scar
10" W. Oak Now dead N 47W 42.9 Opened for scribe rotten face
Some reverse scribe marks found

Also:

Brass Cap at Sec. Cor. Mkd:

General Land Office, 1918
T 31 S R 7 W

5 | 4
8 | 9

New Bearing Tree

13" D. Fir N 81 W 24.7 Scribe T 31 S R 7 W S 5 CS B^T

Note:

This Cor. Lies in E-W Fence line. Approx. 270" West of RR Tracks

6-19-69

John M. Powell
Frank Jones & Cliff Stone
December & January, 1967
1966
C. S. File No. 54/36

Howard W.
Johnstone
For: Rsbgr.Lbr.
Map File
M 33 - 49

John M. Powell
Frank W. Jones & W. Penley
6-19-69 C.S. File No. 54/36

FD. 2/6/81
H. Johnstone
M 81-62