

Douglas County Surveyor's Record of  
Government Corners Renewed

T 31 S T. S. R 7W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$  Section Corner to Sections 5 & 8  
Found - 18" B. oak now 23" N 22 E 33.7 Has rotten face.  
15" B. Oak now down & Rotten face. S 31 E 29.7 found fragments of  
scribing also:  
Brass cap firmly set at  $\frac{1}{4}$  Cor Mkd: General Land Office, 1918  
T 21 S R 7 W  
 $\frac{1}{4}$  S5  
S8

New Bearing Trees  
14" D. Fir N 15 W 18.3  
20" D. Fir S 60 W 13.2 Scribed  $\frac{1}{4}$  S 8 C S BT  
Note: This Cor lies in very old E - W Fence line 6-19-69

FD 3/22/84  
H. Johnstone

$\frac{1}{4}$  Section Corner to Sections 6 & 5  
Found - 10 " W. Oak Now 14" S 83W 35.6 Tree opened Scribe  
Mks. visible not legible rotting face.  
10" W. Oak Now 12" S 11 E 18.5. Shows good scar.  
Also:  
Brass Cap at  $\frac{1}{4}$  Cor. Mkd: General Land Office  $\frac{1}{4}$   
1918 S6/S5  
Renewal  
16" Cedar S 79 W 21.5 Scribed  $\frac{1}{4}$  S 6 CS BT. All trees tagged.  
6-20-69

FD. OK 2/83  
H. Johnstone  
M 9 3-55

Sections Corners to Sections 6, 5, 7, 8  
Found - 30" D. Fir now 33" N 31 E 33.7 Shows good scar  
16" Cedar Now 16" N 40 W 33.0 Shows good scar.  
36" D. Fir now down S 72 E. 37.0 Some pitched over scribing  
visible. No trace of S W BT  
Brass Cap at Sec. Cor. Mkd: General Land Office, 1918  
T 31 S R 7 W  
S 6 | S 5  
S 7 | S 8

New Bearing trees  
38" D. Fir S 45 W 91.0  
32" D. Fir S 61 E 74.5 Scribed T. 31 S R 7 W S 8 CS BT  
6-20-69

Sec. Corner to Secs. 12 & 13, T31-7 and Secs. 7 & 18, T31-6W.  
" Found - Hyde's Section Corner.  
36", now 41" D. Fir, S. 22° E. 7.9 ft., tree has been opened,  
scribe visible "BT". Ring count on this tree places it  
the correct time to be Hyde's corner.  
12", now 28" Cedar N. 27° W. 18.5 ft., center of tree burnt out.  
No trace of NE or SW. BT.  
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R  
Office A. P. 7 S 12 | S 7 6  
1967 W S 13 | S 18 W  
New BT's: 13" Cedar N. 64 $\frac{1}{2}$ ° W. 16.1 ft. mkd: T31S R7W S12 CS BT AP.  
15" Cedar S. 20° W. 29.8 ft. mkd: T31S R7W S13 CS BT AP.  
24" D. Fir N. 38° E. 23.4 ft. mkd: T31S R6W. S 7 CSBT AP.

$\frac{1}{4}$  Corner to Sec. 32, T31-7W. and Sec. 5, T32-7W.  
Found - 35" D. Fir Corner Tree, now Snag, " $\frac{1}{4}$ " faint bark scribe on  
south side of tree.  
32", now 38" D. Fir, N. 80° W. 23. k ft., no scribe found.  
36", now 38" Cedar, S. 85° E. 29.0 ft., faint bark scribe.  
Good distance for call on top of ridge about 660 feet.  
Set - Brass Cap on W. Side of County Surveyor's T 31 S R  
Corner Tree Mkd: Office, 1969 T 32 S R7W  $\frac{1}{4}$  S 32  
S 5  
New BT's: 19" Cedar S. 55° W. 17.7 ft. mkd: " $\frac{1}{4}$ " S 5 CS BT.  
13" D. Fir N. 20 $\frac{1}{2}$ ° E. 26.8 ft. mkd: " $\frac{1}{4}$ " S32 CS BT.

7/1/69

John M. Powell  
Frank Jones & W. Penley  
June, 1969 C. S. 54/36

John M. Powell & Crew  
June 5, 1967  
C.S. File No 54/31

J. Powell &  
Crew  
C.S. File  
No. 54/36