

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 7W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & W. Penley
June, 1968
C. S. File No. 54/36

C. S. FILE NO. 54/36 March, 1970

Sec. Corner to Secs. 6 & 7, T31-7W. and Secs. 1 & 12, T31-8W.

Found - GLO Brass Cap, properly marked in 1918.
10", now 14" D.Fir, S.20°E. 33.0 ft., shows good scar.
14", now 17" D.Fir, S.46°W. 13.9 ft., shows good scar.
16", now 25" D.Fir, N.19°W. 17.2 ft., shows good scar.
No trace of N.E. BT.

New BT: 16" D.Fir N. 3° E. 22.3 ft. mkd: "T31S R7W SC CS BT"
All other trees O.K. and Tagged.

82

1/4 Corner to Sections 6 and 7.

Found - G.L.O. Brass Cap, properly set in 1918
8", now 12" Live Oak, S.28°W. 9.9 ft., shows good scar.
No trace of S.W. Bearing Tree.

New BT: 6" D.Fir N. 63° E. 21.8 ft. mkd: "1/4 S6 CS BT".

6/23/69

83

1/4 Corner to Sections 14 and 15.

Found - 20" D.Fir S.30°E. 19.8 ft., now 42", shows bark scribe, "1/4 S BT".
12", now 26" D.Fir, N.36°W. 13.9 ft., shows good blaze. Do not open.
Old Post, down and out of place. See Ren. #2.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 7 W
Office, 1970 1/4 S 15 | S 14

New BT: 14" D.Fir S.51°E. 33.4 ft. mkd: "1/4 S14 CS BT".

This corner lies on south slope approx. 75 ft. E. of ravine, course S.
and 66 ft. north of creek, course N.W.

3/17/70

84

Section Corner to Sections 10 - 11 - 14 - 15.

Found - 54" D.Fir, now rotten stump, N.54°E. 31.7 ft., no scribe found.
40" D.Fir, now snag, S.16°E. 23.8 ft., found scribe. Ren. #1.
14" D.Fir, now 30", S.73°W. 35.0 ft., no scribe found.
60" D.Fir, now down, N.56°W. 37.6 ft., no scribe found.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 7 W
Office S 10 | S 11
1970 S 15 | S 14

New BT's: 42" D.Fir N. 7° E. 25.4 ft. mkd: "T31S R7W S11 CS BT".

9" D.Fir S.28°E. 24.1 ft. mkd: "T31S R7W S14".

14" D.Fir N.72°W. 62.4 ft. mkd: "T31S R7W S10 CS BT".

Reblzd.& Rescrlb: 30" D.Fir S.73°W. 35.0 ft. mkd: T31S R7W S15 CS BT.

3/18/70

85

1/4 Corner to Sections 10 and 15.

Found - 40", now 60" D.Fir, S.45°W. 5.3 ft., bark scribe visible, "1/4 S BT".
No trace of N.W. Bearing Tree nor Corner Tree. There has been
a fire through area.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 7 W
Office 1/4 S 10
1970 S 15

New BT: 38" D.Fir N.59°W. 6.8 ft. scribed "1/4 S10 CS BT".

Rebzd.& Resbd: 60" D.Fir S.45°W. 6.1 ft., scribed "1/4 S15 CS BT"
(New distance to center of tree)

3/18/70

86

1/4 Corner to Sections 19 and 20.

Found - 9", now 13" D.Fir, N.45°E. 4.0 ft., shows good scar.
14", now 27" D.Fir N.50°W. 29.0 ft., shows bark scribe "1/4 S".

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 7 W
Office, 1970 1/4 S 19 | S 20

Reblzd.& Resbd: 27" D.Fir N.50°W. 29.0 ft. scribed "1/4 S19 CS BT".

3/18/70

87

Section Corner to Sections 19 - 20 - 29 - 30.

Found - 1963 Cadastral B.L.M. Brass Cap, properly marked.
10", now 11" D.Fir S.82 1/2°W. 29.0 ft., shows good scar.
7", now 8" D.Fir N.19 1/2°W. 17.8 ft., shows good scar.

Orig. 21", now 24" D.Fir, N.56°E. 38.3 ft., very faint bark scribing

Orig. 25", now 27" D.Fir S.76 1/2°E. 33.0 ft., very faint bark scribing.

Reblzd.& Resbd: 24" D.Fir N.56°E. 38.3 ft. mkd: "T31S R7W S20 CS BT".

27" D.Fir S.76 1/2°E. 33.0 ft. mkd: "T31S R7W S29CS BT".

This corner lies westerly slope approx. 140.0 ft. East of Creek.

3/19/70

88