

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Secs. 30 & 31, T31-7 and Secs. 25 & 36, T31-8W. **89**
 Found - 12", now 48" Pine, S.68°E. 79.5 ft., tree opened for scribe.
 36", now 48" Pine, S.62°W. 165.0 ft., Open & find about 85 yrs.
 No trace of burl.
 42" Pine, now burnt stob, N.82°E. 126.7 ft.
 40" Pine, now burnt stob & hole, N.35°W. 105.0 ft.
 Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R
 Office 8 S 25 S 30 7
 1970 W S 36 S 31 W
 New BT's: 16" D.Fir S.89°W. 22.1 ft. mkd: T31S R8W S36 CS BT.
 14" D.Fir N.19°W. 22.5 ft. mkd: T31S R8W S25 CS BT.
 13" D.Fir N.24°E. 22.4 ft. mkd: T31S R7W S30 CS BT.
 16" D.Fir S.27°E. 17.6 ft. mkd: T31S R7W S31 CS BT.

4/30/70

Section Corner to Sections 17 - 18 - 19 - 20. **90**
 Found - Orig. Bearing Trees: See Ren. #23.
 15", now 30" D.Fir, N.62°E. 26.4 ft. Rescribed "S17 RE 4079 BT".
 12", now 14" D.Fir, S.68°E. 5.3 ft., Rescribed "S20 RE 4079 BT".
 26", now 33" D.Fir, S.24°W. 5.3 ft., rescribed "S19 RE 4079 BT".
 Some Original Scribe marks visible.

1962 BT: 10" D.Fir N.3°E. 14.0 ft. (Rec. N10E 14.0) shows pitched
 over scribing.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 7 W
 Office S 18 S 17
 1970 S 19 S 20

New BT: 10" D.Fir N.66°W. 9.9 ft. scribed "T31S R7W S18 CS BT".
 6/22/70

1/4 Corner to Sections 17 and 20. **91**
 Found - 7" L.Oak Corner Tree, now 7", shows good scar on north face.
 14", now 14" D.Fir S.32°W. 4.0 ft., shows old face & faint
 bark scribe.
 7" L.Oak, now 6", N.42°E. 10.6 ft., tree opened, rotted face,
 some scribe marks visible, but not legible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 7 W
 (Set on northerly side of Cor. Tree) Office 1/4 S 17
 1970 S 20

New BT: 18" D.Fir N.68°E. 26.0 ft. mkd: "1/4 S17 CS BT".
 Reblzd. & Resbd: 14" D.Fir S.32°W. 4.0 ft. scribed "1/4 S20 CS BT".
 6/22/70

1/4 Corner to Sections 9 and 10. **92**
 Found - 28", now 40" D.Fir Corner Tree, faint but good bark scribe,
 "1/4 S BT" scribe on S.W. side of tree.
 24", now 40" D.Fir, N.85°W. 36.3 ft., no bark scribe found,
 opened tree. No burl or evidence of face.
 16", now 18" W.Oak, S.78°E. 34.3 ft., tree rotted out, old
 axe work or evidence of.

Call to creek south 165.0 ft. hits good.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 7 W
 (Set under & on West Side of Cor. Tree) Office 1/4 S 9 S 10
 1971 S 9 S 10

New BT: 12" D.Fir N. 2° E. 30.6 ft. scribed "1/4 S10 CS BT".
 Reblzd. & Resbd: 40" D.Fir N.85°W. 26.3 ft. scribed "1/4 S9 CS BT".
 1/4/71

1/4 Corner to Sections 31 and 32. **93**
 Found-1963 C.S. Brass Cap bent over & under log. Ren. #36.
 Reset - Brass Cap for 1/4 Corner.
 Found-28", now 28" D.Fir N.36°E. 12.5 ft. scribe visible.
 S.W. Bearing Tree, logged.
 New BT: 10" D.Fir S.70°W. 233.60 ft. scribed 1/4 S31 CS BT.
 Note - This corner lies East of Road #32-7-6 in old
 clear cut unit.

5/22/72

John M. Powell
W. Penley
C.S. File No. 54/36

John M. Powell
Willie Penley
C.S. File No. 54/36

John M. Powell
W. Penley & J. Heritage
C. S. File 54/36

MAR 71

JAN. 1972

RE-NEWED CORNER NO. #110
 RE-NEWED CORNER NO. #113

PER FIELD NOTES 36.3 (1/25/71) 2.5