

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T.S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

94

1/4 Corner to Sec. 6, T31-7W. and Sec. 1, T31-8W.
Found - 1918 Gov't. Brass Cap under large Fir Windfall.
Bearing Trees per 1918 retracement.

40" Pine S. 52° E. 39 lks., shows scribe.
44" Fir N. 33° W. 49 lks., shows scar.

This corner found by Don E. Garrett, July, 1972, see note
in C. S. File No. 54/36.

Jan 1973

U.S. Plywood
Dennis A. Crowe
M 47-60
C.S. File 55/279
January, 1973

Section corner to Secs. 18 & 19, T31-7 and 13 & 24, T31-8.
Found - A diligent search was made yielding no acceptable evidence
of adequate corner monumentation.

Set - 36" Aluminum Cap, iron pipe, 24" into the ground.
BT's - 8" Ponderosa pine, scribed on the wood, bearing S.23°E., 21.5 ft.
8" Fir, scribed on the wood, bearing N.62°E., 19.5 ft.
No other acceptable accesories available.

SEE REN. #100

January, 1973

95

1/4 Corner to Sec. 3 and 10

Found - Both original bearing trees. It was found that the orig.
B.T.'s stand far enough apart that the record distances
as measured from these trees do not intersect. Therefore,
the following procedure was followed: A temporary point
was set at record bearing and distance from each B.T. The
distance between the two temporary points was divided in
half and at this point we

Set - A brass cap for the 1/4 corner mkd: County Surveyors S3 1/4
Office S10 1/4
1974 T31S R7W

From which orig. 10" now 14" D. Fir bears N. 68° E., 6³ ft.
(Rec. N. 60° E., 5³ ft.) scribing "S" visible on pre-
viously opened blaze
orig. 14" now 24" D. Fir bears S50° 30' W., 11⁸ ft.
(Rec. S45° W., 11² ft.). We open and find scribing "1/4"

New BT- 14" D. Fir bears S42° E., 17⁸ ft. scribed "1/4 S10 CSBT"
Note: Declination 20° East

4-25-74

Gary Langlitz
Pete Earle
CS File 56/51
4-25-74

JUN 75

Clell Goodwin
Gary Langlitz
Vic Cangie
Lenora Ladig
C.S. 57/36
10/2/75

Section Corner to Secs. 7, 8, 18, and 17:

Found: 1" Iron Pipe as described in renewal # 20

From Which: An orig. 14" Fir now a 30" stump bears N 17° E., 18.6 ft. Call:
N 13° E., 17.2 ft)

An Orig. 12" Fir now 28" stump bears S 44° E., 12.4 ft. as per Lecklider's
renewal (call: S46° E., 11.9 ft.)

An Orig. 15" Fir now 38" bears S 82° W., 29.2 ft. as per Lecklider's
renewal (call: S89° W., 31.7 ft.)

An orig. 16" Fir now 37" bears N 42° W., 25.0 ft. as per Lecklider's
renewal (call: N44° W., 24.4 ft) Lecklider's N.E. BT, a 20" Fir
bearing N 55° E., 12.0 ft. is now blown down.

New: At the Corner we set a brass cap on a 1" x 30" I Pipe stamped"

DOUGLAS CO. SURVEYOR
1975

T31S R7W

S 7	S 8
S18	S17

with the 1" iron pipe alongside

From which: a 5" Madrone scribed "T 31S R7W S8 CSBT" in a double blaze
bears N 63° E., 18.0 ft.

A 6" live oak scribed "31S R7W S 17 CSBT" in a double blaze bears
S 67° E., 22.1 ft. Compass Declination 20° East 10/2/75

1/75

1/4 Corner for Sec. 25; and Sec. 30 of T.31-6

Found - 3/4" x 24" I.P. at corner firmly set.
3" x 3" squared wooden post.

Ren. #18

Orig. 14" now 24" Fir bears N.48° E., 4.0 ft. (rec. N.47° E.)
Tree has bark scribing "1/4 S BT"

A 30" Cedar now 32" bears S.47° W., 15.2 ft. (rec. S.42° W.) Tree
has partially opened blaze, scribing visible "1/4".

Set - 1" x 30" I.P. with brass cap attached at 1/4 corner cap stamped:
"Douglas County Surveyor" T 31 S

1977

R	1	R
7	1/4	6
W	S25	S30 W

We place I.P. and wooden post beside brass cap.
No new BT's necessary.

Cap is set in mound of stone.

98