

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 7 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

99

Sec. Corner for 24 and 25; and Secs. 19 and 30 of T.31-6.
Found - 1 1/4" I.P. firmly set at sec. cor. as determined by Johnston
1962. See M 18 - 66. Ren. #6
6" now 10" D. Fir bears S.88°W., 30.6 ft. (Rec. 32.9 ft.) Tree
has well healed blaze. (single).
14" now dead, tipped out D. Fir bears S.63°E., 35.0 ft. Tree has
open double blaze scribed "T31S 6W S30 BT".
30" now 31" D. Fir bears N. 10°E., 54.5 ft. (rec. 55.1 ft.)
Tree has partially healed single blaze.
7" now 9" S. Pine bears N.55°W., 23.3 ft. (rec. 23.9 ft.)
Tree has well healed double blaze.
Set - I place 1" x 30" I.P. with brass cap attached at sec. cor. as
determined by Johnston, stamped "Douglas County Surveyor"

	T 31 S		
R	S24	S19	R
7	S25	S30	6
W	1977		W

New BT - A S. Pine 15" bears S.69°E., 53.3 ft. Tree double blazed and
scribed "T31S R6W S30 CS BT".

Note - All bearings and distances measured are to center of base of tree.

1/3/77
100

Section Corner for Secs. 18 and 19; and Secs. 13, 24 of T.31-8
Found - 1972 Alum cap and 3 BT's N.6°10'11"E., 47.37 ft. from true
Section corner. See Ren. #95

Set - 5/8" x 30" I.R. and Alum cap for Sec. Corner.
BT's - 5" Fir S.82°E., 19.3 ft.
5" Madrone S.65 1/2°W., 5.1 ft.
4" Madrone N.60°W., 3.3 ft.
9" Pine N.24°E., 30.8 ft.

3/8/77
101

1/4 Corner for Sec. 19 and Sec. 24 of T.31-8

Set - 5/8" x 40" I.R. and Alum cap.
BT's - 6" Fir N.81 1/2°E., 27.7 ft.
20" Fir N.83°W., 32.8 ft.

3/8/77
102

South 1/4 Corner for Sec. 18.

Set - Brass cap in concrete monument

BT's - 15" Fir, S.81°E., 52.2 ft.
7" Oak N.59°E. 79.4 ft.

RE-RENEWED, SEE CORNER NO. #129

3/8/77
103

1/4 Corner for Secs. 26 and 25.

Found - A 1" x 30" Iron pipe 24" in ground. Ren. #16
A 14" now 23" Live Oak bears N.32°W., 56.1 ft. with single chopped
out blaze. (OBT)
A 44" now 54" Pine stump (barked) bears S.7°E., 54.1 ft. (Rec.
S.10°E., 55.4 ft.)
A 6" now 10" D. Fir bears S.70 1/2°E., 11.0 ft. with double well
healed blaze.

Set - A 1" x 36" Iron pipe with brass cap set 7" above ground and marked
"Douglas County Surveyor" T 31 S R 7 W
1977 1/4

S 26 | S 25

Set - 1" x 30" Iron pipe under north edge of brass cap.
No new accessories. Note: Take left fork of Smith Cr. Rd. to end. Corner
bears NW + 800 ft., 50 ft. west of west edge of clear cut unit.

10/20/77

Larry E. Monrean, Doug. Co. Surveyors
Office
K. Cheney, R. L. Fayle
Jan. 3, 1977
C.S. 59/29

Howard Johnstone
For: Roseburg Lumber Company
March 8, 1977
M 65 - 5

R. B. Kimberl
M. W. Cline
Doug. Co. Surveyor
Office
Oct. 20, 1977
C.S. 59/40