

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 7 R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

115

Howard Johnstone
For: Roseburg Lbr.
February 10, 1983
M 93 - 55

1/4 Corner for Section 6; and Sec. 31 of T.30-7
Found - 1918 GLO brass cap and iron pipe.
24" W. fir, N.60°E., 50.2 ft.
20" W. fir, S.41°W., 20.5 ft.
New BTs- 5" yewood, S.62°E., 22.7 ft.
10" W. fir, N.46°E., 22.8 ft.

2/10/83

116

Section corner for Secs. 33 and 34; and Secs. 3 & 4 of T32-7
Found - 1964 BLM brass cap properly marked, projecting 4" above
ground.
Orig. 20" rotted and uprooted cedar snag, it's root hole bears
N.50°E., 16.5 ft.
1964 BT, a 30" D. fir bears N.17 3/4°E., 39.6 ft. with a healed
blaze.
1964 BT, a 26" D. fir bears S.59 3/4°E., 49.5 ft. with a healed
blaze.
1964 BT, a 10" uprooted D. fir snag, its root hole bears S.59°W.,
54.1 ft.
New BTs- 20" incense cedar bears S.82 1/2°W., 60.4 ft. scribed "T32S R7W
S4 BT" with a brass washer "LS 1941" nailed into lower blaze.
8" chinquapin bears N.15°W., 47.6 ft. scribed "T31S R7W S33 BT" with
a brass washer "LS 1941" nailed into lower blaze.
Distances to new bearing trees are measured to a nail in the root crown at
the side and center of the tree. I painted 6" red bands around new BTs and
all bearing tree faces red and attached BT tags.

117

Section corner for Secs. 32 and 33; and Secs. 5 & 4 of T.32-7
Found - 1964 BLM brass cap properly marked on a 2 1/2" I.P. projecting
2" above ground.
Orig. 34" D. fir stump bears S.36°E., 11.9 ft. with bark scribe
marks "T32S 7W S4 BT" visible.
Orig. 26" D. fir stump bears S.12°W., 37.8 ft. with bark scribe
marks "T32S R7W S5 BT" visible, (Rec. 39.8 ft.).
1964 BT, 19" D. fir stump bears N.79 1/2°E., 58.1 ft. with healed
blaze.
1964 BT, 18" D. fir stump bears N.54 1/2°W., 48.8 ft. with healed
blaze.
1982 BLM BTs in a survey not yet approved:
20" D. fir stump bears S.40°E., 51.0 ft. with scribe marks "T32S
R7W S4 BT" visible (Rec. 52.8 ft. from BT tag).
8" cedar bears N.58°W., 54.8 ft. with scribe marks "T31S R7W S32
BT" visible.
New BT - 8" tan oak bears N.45 1/2°E., 120.9 ft. scribed "T31S R7W S33
BT" with a brass washer stamped "LS 1941" nailed into lower
blaze.
I painted 6" red bands around new bearing trees and all bearing tree faces
red and attached BT tags. Distance to new BT measured to a nail in root
crown at the side and center of the tree.

118

1/4 Corner for Secs. 33 and sec. 4 of T.32-7
Found - 1966 County brass cap, properly mkd. on a 1" iron pipe, bent,
loosely set and disturbed during logging activity. Ren. #69
I reset the monument from the original bearing trees:
A 36" D. fir stump bears S.67 1/2° E., 30.4 ft. with scribe marks
"S4" visible on an opened blaze, (Rec. S.70°E. 29.7 ft.).
A 30" D. fir stump bears N.67 1/2°W., 35.0 ft. with bark scribe
marks "1/4 S" visible on a sawed out block (Rec. N.70°W., 34.3 ft
A 1966 BT, A 9" D. fir, 8 ft. high stump, partially uprooted, bears
N.42°E., 18.8 ft. with healed blaze.
1967 BLM BT, a 12" D. fir, uprooted stump, its root hole bears
N.65°E., 35.6 ft.
New BT - A 5" D. fir bears N.32 1/2°E., 67.6 ft. scribed "1/4 S33 BT" with a
brass washer "LS 1941" nailed into lower blaze.
Distance to new bearing tree to a nail in root crown at the side and center
of the tree. I painted 6" red bands around new bearing trees and all
bearing tree faces red and attached bearing tree tags.

Kristian O. DeGroot, LS 1941
For: Allen & Gibbons Logging, Canyonville, OR
Nov. 28, 1983
C.S. 58/229