

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

133

Mark Smalley
For: Kenneth Ford
July 1994
M 120-43

1/4 Cor. Secs. 35 & 36
Found - 1964 Cad. BCIP
48" Fir, S.80°E., 36.3', bark scribe.
18" Fir, S.55°W., 19.1', healed
New BTs-17" Fir, N.29°W., 30.2' "1/4 S BT"
9" Fir, S.86dW., 15.3', "1/4 S BT"

134

Mark Smalley
Roseburg Forest Prod
7/12/94
cs 63/154

SECTION CORNER TO 35, 36 & 1, 2 OF T32-7
FOUND - 1964 BCIP
BTs - 17" Fir, N.9°W. 21.1', good healed face
36" Fir, N.80°E. 31.7', O.B.T
14" Fir, S.20°E., 7.9', down, O.B.T
16" Fir, S.60°W., 9.9', good healed face, O.B.T
20" Fir, N.17°W., 80.52', good healed face, no rec.
New Accessories -
10" Cedar, S.79°W., 23.3', scribed "S2 BT"
corner is 200' east of 31-7-25.1 road

135

Douglas Co. Surveyor's Office
Randall Smith, Stephen Flause
Aug. 4, 1994 C.S. File 64/52

1/4 Corner for Sec. 36 and Sec. 31 of T.31-6.
Found - 1 1/2" I.D. iron pipe leaning 8" east of plumb.
Protrudes 5" above ground. (M33-49) See ren. #131.
-2 1/2" brass cap on a 1 1/2" O.D. by 36" long iron pipe is
found laying on top of ground near above set I.P.
BC/IP shows no evidence of having been set. (1966)
Accessories Found -
-20" now 28" dia. 3 ft. high D.Fir stump with evidence of
old bark scribing "1/4" and partially healed single blaze
with scribing visible "1/4 S36" bears N.34°W., 15.2 ft.
(agrees with rec.) O.B.T.
-16" now 19" dia. D.Fir with a fully healed double blaze, no
bark scribing visible, bears N.58°E., 15.8 ft. (agrees
with 1966 rec.) O.B.T.
-6" Yew wood with a single blaze scribed "1/4 BT" bears
N.44°E., 24.0 ft. (M120-43 agrees with rec.)
-30" D.Fir with a single blaze scribed "1/4 BT" bears
S.58°E., 23.5 ft. (M120-43 agrees with rec.)
-28" D.Fir with a single blaze scribed "1/4 BT" bears
S.38°E., 47.6 ft. (rec. S.35°E., 47.6 ft. M120-43)
Monument Set - 1 1/2" I.pipe is referenced and removed, measured 24"
long. 1966 DCSO BC/IP is set at referenced position, the
marks "RESET 1994" are added to brass cap. BC/IP protrudes
9" above ground. 24" iron pipe is set along north edge of
BC/IP, protrudes 7" above ground.
-Monuments are surrounded by a 24" dia. 9" high mound of
stone.

1/4 Cor. Secs. 35 & 36
Found - 1964 BCIP
48" Fir, S.80°E., 36.3', bark scribe.
18" Fir, S.55°W., 19.1', healed
New BTs-17" Fir, N.29°W., 30.2' "1/4 S BT"
9" Fir, S.86dW., 15.3', "1/4 S BT"

SECTION CORNER TO 35, 36 & 1, 2 OF T32-7
FOUND - 1964 BCIP
BTs - 17" Fir, N.9°W. 21.1', good healed face
36" Fir, N.80°E. 31.7', O.B.T
14" Fir, S.20°E., 7.9', down, O.B.T
16" Fir, S.60°W., 9.9', good healed face, O.B.T
20" Fir, N.17°W., 80.52', good healed face, no rec.
New Accessories -
10" Cedar, S.79°W., 23.3', scribed "S2 BT"
corner is 200' east of 31-7-25.1 road

1/4 Corner for Sec. 36 and Sec. 31 of T.31-6.
Found - 1 1/2" I.D. iron pipe leaning 8" east of plumb.
Protrudes 5" above ground. (M33-49) See ren. #131.
-2 1/2" brass cap on a 1 1/2" O.D. by 36" long iron pipe is
found laying on top of ground near above set I.P.
BC/IP shows no evidence of having been set. (1966)
Accessories Found -
-20" now 28" dia. 3 ft. high D.Fir stump with evidence of
old bark scribing "1/4" and partially healed single blaze
with scribing visible "1/4 S36" bears N.34°W., 15.2 ft.
(agrees with rec.) O.B.T.
-16" now 19" dia. D.Fir with a fully healed double blaze, no
bark scribing visible, bears N.58°E., 15.8 ft. (agrees
with 1966 rec.) O.B.T.
-6" Yew wood with a single blaze scribed "1/4 BT" bears
N.44°E., 24.0 ft. (M120-43 agrees with rec.)
-30" D.Fir with a single blaze scribed "1/4 BT" bears
S.58°E., 23.5 ft. (M120-43 agrees with rec.)
-28" D.Fir with a single blaze scribed "1/4 BT" bears
S.38°E., 47.6 ft. (rec. S.35°E., 47.6 ft. M120-43)
Monument Set - 1 1/2" I.pipe is referenced and removed, measured 24"
long. 1966 DCSO BC/IP is set at referenced position, the
marks "RESET 1994" are added to brass cap. BC/IP protrudes
9" above ground. 24" iron pipe is set along north edge of
BC/IP, protrudes 7" above ground.
-Monuments are surrounded by a 24" dia. 9" high mound of
stone.