

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

John M. Powell
Frank Jones & C. Stone
12/1/66
C. S. File No. 54/36

22

TOWNSHIP CORNER: T.31S.-R.7 & 8 W. and T.32S.-R.7 & 8 W.
Found - 8", now 13" Live Oak, S. 78° E. 40.3 ft., opened for scribe "T 6 2".
12" D.Fir, now rotten stob, N. 45° W. 64.0 ft.
No trace of N. E. nor S. W. Trees.

Set - Brass Cap at Township Corner Mkd:
County Surveyors Office, 1966

	T31S		
R8W	S 36	S 31	R7W
	S 1	S 6	

T. 32 S.

New BT's: 10" D. Fir S. 72° W. 33.6 ft. mkd. T32S R8W S 1 CS BT.
12" D. Fir S. 48½° E. 24.4 ft. mkd. T32S R7W S 6 CS BT.
8" Live Oak N. 53° E. 46.6 ft. mkd. T31S R7W S31 CS BT.
6" Live Oak N. 48° W. 4.6 ft. mkd. S36 CS BT.

Note - This corner lies about 33.0 ft. East of creek on steep, West slope.
12/1/66

23

¼ Corner to Sec. 30, T31-7W & Sec. 25, T31-8W.
Found - 36", now 48" D. Fir, S. 25° W. 30.4 ft., bark scribed, faint.
26", now 32" D. Fir, S. 85° E. 30.4 ft., shows old face,
opened for scribe "1S". (Find this bear. & dist. to be.
S.89°E. 26.4 ft.)

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

	T 31 S		
R8W	¼ S 25	S 30	R7W

New BT's: 13" D. Fir N. 55½° W. 26.0 ft. mkd. ¼ S 25 CS BT.
10" D. Fir S. 63° E. 36.5 ft. mkd. ¼ S 30 CS BT.
12/15/66

24

Sec. Corner to Sections 19 & 30, T31-7 & Secs. 24 & 25, T31-8.
Found - Stone at Corner, 4 notches, North & 2 notches, South.
26", now 34" D. Fir, N. 66° E. 40.9 ft., no scribe visible,
old face faint.
14", now 20" D. Fir, S. 65° E. 7.9 ft., bark scribe, faint.
28", now 34" D. Fir, S. 45° W. 39.6 ft., bark scribed.
20", now 24" D. Fir, N. 42° W. 13.2 ft., bark scribed.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966

	T 31 S		
R8W	S 24	S 19	R7W
	S 25	S 30	

Reblzd.&Rescbd: 20" D. Fir S. 65° E. 7.9 ft. mkd. T31S R7W S30 CSBT.
34" D. Fir N. 66° E. 40.9 ft. mkd. T31S R7W S19 CS BT.
12/15/66

25

¼ Corner to Sec. 12, T31-8W. & Sec. 7, T31-7W.
Found - 42", now 62" D. Fir S. 75° E. 22.4 ft., faint scribe visible.
No trace of S. W. BT.

Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office, 1966

	R	T 31 S		R
	8	¼ S 12	S 7	7
	1966	W		W

New BT's: 8" W. Fir N. 89½° E. 53.2 ft. mkd. ¼ S7 CS BT.
10" W. Fir N. 85° W. 32.9 ft. mkd. ¼ S12 CS BT.
12/28/66

26

¼ Corner to Sections 4 and 3.
Found - Orig. 26" Fir, now stump, N. 42° E. 14.5 ft., shows scar.
Orig. 12", now 19" W. Fir N. 30° W. 13.9 ft., found scribing
on rotten face.

Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office, 1966

	T31S R8W		
	¼ S 4/S 3		

New BT's: 5" D. Fir N. 19° E. 18.8 ft. mkd. ¼ S 3 CS BT.
38" D. Fir N. 23° W. 24.0 ft. mkd. ¼ S 4 CS BT.

Note - This corner lies south of creek about 90.0 ft.
12/30/66

27

¼ Corner to Sections 28 and 33.
Found - 56" D. Fir N. 55° E. 25.1 ft., faint ¼ notch on bottom of face.
(Dist. is from face of tree)

No trace of Laurel South 9.2 ft.
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office, 1966

	T 31 S R 8 W		
	¼	S 28	
		S 33	

New BT: 9" Laurel South 26.9 ft. mkd. ¼ S33 CS BT.
Reblzd.&Rescbd: 56" D. Fir N. 55° E. 27.1 ft. (Dist. to center)
scribed ¼ S28 CS BT. 1/6/67