

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

28

Section Corner to Secs. 32 & 33, T31-8W. & Secs. 5 & 4, T32-8W.  
Found - Orig. 12", now 15" Laurel N. 35° E. 23.1 ft., opened for  
scribing, none(rotted)  
Orig. 30" S. Pine, now Stump, S. 50° E. 75.0 ft.  
Orig. 8", now 10" Laurel S. 40° W. 22.4 ft., opened for  
scribe, "W" and other marks, not legible.  
Orig. 24" Fir, gone but found stump hole at N. 25° W. 46.9 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office  
1967

T 31 S	R 8 W
S 32	S 33
S 5	S 4
T 32 S	

New BT's: 18" D. Fir S. 23 $\frac{1}{4}$ ° W. 13.3 ft. mkd. T32S R8W S5 CS BT.  
9" Laurel S. 75° E. 29.2 ft. mkd. T32S R8W S 4 CSBT.  
9" Laurel N. 70° E. 32.4 ft. mkd. T31S R8W S33 CS BT.  
12" Laurel North 16.0 ft. scribed T31S R8W S32 CS BT.  
Jan. 6, 1967

29

Sec. Cor. to Secs. 33 & 34, T31-8W. & Secs. 4 & 3, T32-8W.  
Found - Orig. 30", now 51" D.Fir, S. 23° W. 23.8 ft., faint  
bark scribe "32 8 B".  
Orig. 22", now " D.Fir N. 70° W. 27.7 ft. Has been  
rescribed but pitched over.  
Orig. 20", now " S. Pine, S. 75° E. 70.6 ft., shows good scar.  
Orig. 20" S. Pine, now dead, N. 78° E. 36.3 ft., scribe  
visible "T31S R8 S34".  
Stone, 3 v on E. and W. faces.  
Also Iron Pipe at Section Corner.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office  
(Set B.C. alongside Iron Pipe & Stone) 1967

T 31 S	R 8 W
S 33	S 34
S 4	S 3
T 32 S	

Reblazed & Rescribed: 51" D.Fir S.23° W. 23.8 ft. mkd. T32S R8W S4 CS BT.  
No trees in section 34.

30

$\frac{1}{4}$  Corner to Sec. 33, T31-8W. & Sec. 4, T32-8W.  
Found - Orig. 14", now 17" Laurel, N. 65° E. 15.2 ft., opened for  
scribing, rotten.  
Orig. 14", now 18" Laurel, S. 15° W. 16.5 ft., opened for  
scribing "T".  
13" Fir, now down, S. 39 $\frac{1}{2}$ ° E. 45.3 ft., scribed, pitched over.  
Also Iron Pipe at  $\frac{1}{4}$  Cor., See Ren. #16, T32-8W.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office  
1967

T 31 S	R 8 W
$\frac{1}{4}$ S 33	
S 4	
T 32 S	

Reblzd. & Rescbd: 38" Double Laurel S. 15° W. 16.5 ft. mkd.  $\frac{1}{4}$ S 4 CS BT.  
New BT: 15" Laurel N. 68° E. 22.8 ft. mkd.  $\frac{1}{4}$  S 33 CS BT.  
Note - As in original notes, corner lies about 33.0 ft. west of  
ridge top.

31

$\frac{1}{4}$  Corner to Sections 29 and 28.  
Found - No trace of stone at corner.  
13" Fir, now stump, S. 80° E. 29.0 ft., bark scribed " $\frac{1}{4}$ S" visible.  
16" Fir, now stump, S. 75° W. 8.6 ft., nothing visible on this tree.  
(find bear. to be N.82°W.  
Post at corner. Using 2 distances & 1 bearing, I renew.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1967

T 31 S	R 8 W
$\frac{1}{4}$ S 29/S 28	

New BT's: 14" Chinquapin S. 8° W. 56.6 ft. mkd.  $\frac{1}{4}$  S29 CS BT.  
18" Cedar S. 59 $\frac{1}{2}$ ° E. 112.2 ft. mkd.  $\frac{1}{4}$  S 28 CS BT.  
Note - This corner lies about 40 ft. north of skid road & 130.0 ft.  
south of draw.

John M. Powell  
Frank Jones & Cliff Stone  
January, 1967  
C. S. File No. 54/36