

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 8 W. R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 97401

32

Sec. Cor. to Secs. 34 & 35, T31-8W. & Secs. 3 & 2, T32-8W.

Found - Pieces of Stone at Sec. Cor.

14", now 27" D.Fir, N. 82° E. 34.2 ft. (recorded 32.6 ft.)
old axe work, no scribe visible.

14", now 21" D.Fir, S. 65° E. 27.1 ft., shows good scar.

16", now 36" D.Fir S. 28° W. 19.8 ft., bark scribe visible.

13", now 30" D.Fir, N. 35° W. 27.1 ft., bark scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

T 31 S	R 8 W
S 34	S 35
S 3	S 2
T 32 S	

Reblazed & Rescribed: 27" D.Fir N. 82° E. 34.2 ft. mkd. T31S R8W S35 CS BT.

36" D.Fir S. 28° W. 19.8 ft. mkd. T32S R8W S3 CS BT.

30" D.Fir N. 35° W. 27.1 ft. mkd. T31S R8W S34.

Note - Best way to reach corner is north on railroad to yellow tag on small fir.

33

1/4 Corner to Sec. 34, T31-8 and Sec. 3, T32-8W.

Found - 44", now 50" D.Fir, S. 2° E. 39.6 ft., faint "BT" visible,
also notch below main face.

No trace of 7" Fir N. 20° W. 19.8 ft.

Iron Pipe at 1/4 corner, (unrecorded)

Tree with face but no scribing at N. 10° E. 16.1 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

T 31 S	R 8 W
1/4 S 34	
S 3	

New BT's: 10" D.Fir S. 37° E. 18.4 ft. mkd. 1/4 S 3 CS BT.

10" D.Fir N. 10° E. 16.1 ft. mkd. 1/4 S34 CS BT.

Note - As in orig. notes, spring branch 132.0 ft. east of 1/4 corner.

John M. Powell
Frank Jones & Cliff Stone
January, 1967
C. S. File No. 54/36

Sec. Corner to Sections 16 - 17 - 20 - 21.

*Fvd. O.K. by S.P. NESS
Dec. 1981 M89-65*

34

Found - 1958 County Surveyor's Brass Cap at Corner, properly marked, Ren. #8.

Orig. 10", now 22" Fir, S. 11° E. 15.8 ft., shows good scar.

34" R.Fir N. 32 1/2° W. 10.9 ft. mkd. T31S R8W S17 CS BT.

16" R.Fir, broken & dead, S. 53° W. 33.0 ft. mkd. T31S R8WS20 CS BT.

6" R.Fir N. 35° E. 56.6 ft. mkd. T31S R8W S16 CS BT.

New BT: 22" D. Fir S. 44° W. 36.7 ft. mkd. T31S R8W S20 CS BT.

Note - This corner lies 155.0 ft. west of Dutchman Lookout Road.

- FO OK, APR 1995, 1995-0046

1/4 Corner to Sections 18 and 19.

FV BC & BT 4/2008 M156-4

35

Found - 15" D.Fir, now 30", N. 21° E. 9.2 ft. (from face) faint bark
scribe, "S" BT.

C. Woodruff

No trace of S.E. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

T 31 S	R 8 W
1/4 S 18	
S 19	

New BT's: 14" D.Fir N. 89° W. 7.0 ft. mkd. 1/4 S 18 CS BT.

30" D.Fir S. 44 1/2° E. 25.3 ft. mkd. 1/4 S19 CS BT.

36

Sec. Cor. to Sections 17 - 18 - 19 - 20.

Found - 22", now 38" D.Fir, N. 49° E. 57.4 ft. (bearing S.B. N. 39° E.)
bark scribed "T31S" R8 BT"

14", now 24" D. Fir S. 67 1/2° E. (record S. 61° E) 9.2 ft., bark
scribed "T31S R8 S20 BT"

36", now 39" D.Fir, S. 57° W. (record S. 64° W.) 19.8 ft., faint
scribe visible "BT".

6" Dogwood, now snag, N. 26° W. 8.6 ft., opened for scribe "BT".

Renewed Corner by using 1 bearing and 4 distances.

Set - Brass Capd at Cor. Mkd: County Surveyor's Office 1967

T 31 S	R 8 W
S 18	S 17
S 19	S 20

New BT's: 12" Cedar N. 2° W. 26.5 ft. mkd. T31S R8W S18 CS BT.

7" W.Fir N. 34° E. 15.3 ft. mkd. T31S R8W S17 CS BT.

9" Hemlock S. 45 1/2° W. 37.2 ft. mkd. T31S R8W S19 CS BT.

RE-RENEWED SET CORNER NO #81