

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 8 W. R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97101

1/4 Corner to Sections 17 and 18.  
Found - No trace of 10" Laurel as it lies in clear cut unit.  
10", now 11" D. Fir N. 84° E. 9.2 ft., faint bark scribe "BT",  
other marks but not legible.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 8 W  
Office, 1967 S 18 | S 17  
New BT's: 14" D. Fir N. 51° E. 20.0 ft. mkd. 1/4 S17 CS BT.  
7" D. Fir N. 68° W. 20.5 ft. mkd. 1/4 S18 CS BT.  
Note - This corner lies about 460 ft. south & 250 ft. E. of creek.  
To determine if 11" D. Fir was old enough, I notch to count  
rings which were almost too close together to count. Definitely old enough.

42  
FD BC of BT  
4-2008 Woodcut  
M156-5

SECTION  
Corner to Section 31, T31-8W. & Sec. 36, T31-9W.  
Found - 30" D. Fir, now stump, N. 26° W. 34.3 ft., shows good scar  
and faint bark scribe "31S".  
No trace of N.E. Laurel  
G.L.O. Brass Cap marked in 1918.  
New BT's: 5" Laurel N. 13° W. 26.0 ft. mkd. S36 CS BT.  
5" Laurel S. 42° E. 21.2 ft. mkd. S 1 CS BT.

43

1/4 Corner to Sec. 32, T31-8W. & Sec. 5, T32-8W.  
Found - 5/8" Iron Rod (not 1/2" I. Pipe) at 1/4 Corner. See Ren. #3.  
NO trace of Original Stone.  
Orig. 52" D. Fir, now down, N. 9° E. 34.3 ft.  
Orig. 40", now 54" D. Fir, S. 32° W. 49.5 ft., old axe work visible,  
snag top.  
Call of 33.0 ft. from creek hits very good.  
Renewal BT. - 14" Laurel N. 15° W. 8.1 ft. scribe visible "3642 BT".  
New BT: 20" D. Fir S. 9° W. 23.5 ft. mkd. 1/4 S 5 CS BT.  
Note - This corner lies west of creek 33.0 ft.

44

Sec. Cor. to Secs. 32 & 31, T31-8W. & Secs. 5 & 6, T32-8W.  
Found - No trace of original corner.  
5/8" I. Rod at Corner (not 1/2" I. Pipe) See Ren. #2.  
12", now 13" Tan Oak, S. 10° E. 11.1 ft. scribed 3642 BT.  
6", now 7" Tan Oak, S. 29° W. 28.6 ft. scribed 3642 BT.  
6", now 7" Tan Oak, N. 81 1/2° W. 21.8 ft. scribed 3642 BT.  
5" Tan Oak, now down, N. 59 1/2° E. 6.3 ft.  
New BT's: 8" Tan Oak N. 7° E. 30.3 ft. mkd. T31S R8W S32 CS BT.  
20" D. Fir S. 4 1/2° E. 17.7 ft. mkd. T32S R8W S5 CS BT.  
Note - This corner lies on steep, east slope and about 300 ft. west of  
Hayes Creek.

45

Sec. Cor. to Sections 1 = 2 - 11 - 12.  
Found - Orig. 15", now 29" D. Fir, N. 30° W. 30.2 ft., faint bark scribe.  
Orig. 24", now 44" D. Fir, S. 40° E. 4.0 ft., faint bark scribe.  
Orig. 15", now 22" Laurel, S. 25° W. 17.2 ft., rotten center.  
(All distances to approx. face)  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 8 W  
Office S 2 | S 1  
1967 S 11 | S 12  
New BT's: 15" Cedar S. 51° W. 12.5 ft. mkd. T31S R8W S11 CS BT.  
14" Cedar N. 29° W. 16.7 ft. mkd. T31S R8W S2 CS BT.  
25" D. Fir N. 30° E. 47.0 ft. mkd. T31S R8W S 1 CS BT.

46

Sec. Cor. to Secs. 1 & 2, T31-8W. & Secs. 35 & 36, T30-8W.  
Found - Wood Post at Corner, See Ren. #6.  
3", now 6" D. Fir, N. 82° W. 6.2 ft., shows scar. (REC. S. 72° W.)  
7", now 8" Laurel, N. 6° W. 17.2 ft., bark scribed.  
10", now 12" Laurel, S. 78 1/2° E. 13.2 ft., bark scribed "T31SR8 RE27418"  
8", now 9" Laurel, N. 51° E. 17.9 ft., bark scribed.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 8 W  
Office S 35 | S 36  
1967 S 2 | S 1  
T 31 S

47

RE-RENEWED, SEE CORNER

62

(continued over)

John M. Powell  
Frank Jones & Cliff Stone  
January, 1967  
C. S. File No. 54/36