

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

John M. Powell
& Crew
C.S. File
No.
54/36

1/4 Corner to Sec. 31, T31-8W. & Sec. 6, T32-8W. 54
Found - Orig. 30" Fir, now Stub, S. 10° W. 7.9 ft.
Orig. 30" Fir, now stump, N. 34° W., (record N.30°W.) 23.1 ft.,
scribe visible.
1 1/4" Iron Pipe at 1/4 Corner, See Ren. #15.
40", now 42" Fir, S. 58° E. 39.7 ft. scribed 1/4 S BT.
New BT: 8" Tan Oak N. 31 1/2° W. 64.0 ft., mkd. 1/4 S31 CS BT.
Note - This corner lies 185.0 ft. East of creek.

John M.
Powell
&
Crew
C.S. File
No.
54/32

1/4 Corner to Sec. 18, T31-8W. & Sec. 13, T31-9W. 55
Found - GLO Brass Cap Mkd: R9W 1/4 S13 | S18 R8W
1962
37" D. Fir, now broken Snag, N. 53 3/4° E. 11.9 ft., bark
scribed "1/4 S18 BT."
31" D. Fir, now stump, S. 48 3/4° W. 9.2 ft., Stump out of ground,
scribe visible "S13".
New BT;s: 14" D. Fir N. 77° E. 18.8 ft. mkd. 1/4 S18 CS BT.
6" Live Oak S. 14° W. 56.6 ft. mkd. 1/4 S13 CS BT.
Note - This corner lies East of Elk Valley Road approximately 150.0 ft.
March 17, 1967

MICROFILM TO HERE 10/67

John M. Powell
Frank Jones & W. Penley
C.S. File No. 54/36

1/4 Corner to Sections 6 and 7. 56
Found - Stone mkd "1/4", also unrecorded 3/4" I. Pipe.
26", now 48" D. Fir, N. 12° E. 38.3 ft., tree partly opened,
no scribe visible, starting to show burl.
72" D. Fir, now 7' stump, S. 10° W. 25.1 ft., bark scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R8W
Office 1/4 S 6
1968 S 7
New BT's: 8" W. Fir S. 75° W. 23.3 ft. mkd. 1/4 S7 CS BT.
6" W. Fir N. 9° E. 9.1 ft. mkd. 1/4 S6 CS BT.
3/7/68

Section Corner to Secs. 1 & 12, T31-8W. and Secs. 6 & 7, T31-7W. 57
Found - G.L.O. Brass Cap at corner properly marked in 1918.
10", now 14" D. Fir, S. 20° E. 33.0 ft., shows good scar.
14", now 17" D. Fir, S. 46° W. 13.9 ft., shows good scar.
16", now 25" D. Fir, N. 19° W. 17.2 ft., shows good scar.
No trace of NE BT.
New BT: 16" D. Fir N. 3° E. 22.3 ft. mkd: T31S R7W S6 CS BT.
All other trees 0. K. & Tagged.
6/23/69

1/4 Corner to Sections 14 and 23. 58
Found - No trace of Corner Stake., See Ren. #1.
22", now 23" S. Pine, S. 40° E. 11.9 ft., opened for scribe.
34", now 36" S. Pine, N. 20° W. 21.1 ft., shows scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 8 S
Office 1/4 S 14
1969 S 23
New BT: 10" D. Fir S. 20° W. 13.0 ft. mkd: "1/4 S23 CS BT".
This corner lies about 350 ft. est of high ridge which runs about N-S.
6/18/69

Section Corner to Sections 22 - 23 - 26 - 27. 59
Found - Corner Stone, firmly in place, with 2 notches on the East.
Orig. 15", now 24" D. Fir, N. 10° W. 10.6 ft., scribe visible. 500300
Orig. 14", now 22" D. Fir, S. 32° W. 42.9 ft. (Rec. S357), tree burnt, no scribe.
Orig. 12", now 19" D. Fir, S. 55° E. 15.3 ft. (Rec. 17.2), scribe visible.
Orig. 14", now 17" D. Fir, N. 68° E. 21.4 ft. (Rec. N70E 17.2) scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 8 W
(Set Alongside Corner Stone) Office S 22 | S 23
1970 S 27 | S 26
Reblzd. & Reschd: 24" D. Fir N. 10° W. 10.6 ft. mkd: "T31S R8W S22 CS BT".
22" D. Fir S. 32° W. 42.9 ft. mkd: "T31S R8W S27 CS BT".
19" D. Fir S. 55° E. 15.3 ft. mkd: "T31S R8W S26 CS BT".
17" D. Fir N. 68° E. 21.4 ft. mkd: "T31S R8W S23 CS BT".
500300 3/24/70

FD-BC-2
4 B.T.S.
1972 BLM
ADMIN. SURVEY
SEE GTS
FILES

RE-RECORDED