

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

60

Section Corner to Sections 21 - 22 - 27 - 28.

Found - No trace of Corner Stone.

Orig. 22", now 36" D. Fir, S. 5° E. 30.4 ft., no scribe visible.  
Orig. 15", now 20" D. Fir, S. 8° W. 37.6 ft., scribe visible, other faint mks.  
Orig. 4" Live Oak, now stob, N. 37° E. 13.2 ft.  
Orig. 28", now 45" D. Fir, N. 67° W. 5.9 ft. (Rec. N25W), no scribe found.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1970

T 31 S	R 8 W
S 21	S 22
S 28	S 27

New BT's: 10" D. Fir N. 66° E. 16.5 ft. mkd: "T31S R8W S22 CS BT".  
10" D. Fir N. 26° W. 34.8 ft. mkd: "T31S R8W S21 CS BT".  
Reblzd. & Rescbd: 36" D. Fir S. 5° E. 30.4 ft. mkd: T31S R8W S27 CS BT.  
20" D. Fir S. 8° W. 37.6 ft. mkd: T31S R8W S28 CS BT.

3/24/70

Fd. B.C. & 5 BTs  
1972 Blm  
ADMIN. SURVEY  
SEE GIS FILES

John M. Powell  
& Crew  
C.S. File No. 54/36

Sec. Cor. to Secs. 30 & 31, T31-7W. and Secs. 25 & 36, T31-8W.

61

Found - 12", now 48" Pine, S. 68° E. 79.5 ft., tree opened for scribe "BT".  
36", now 48" Pine, S. 62° W. 165.0 ft., Open Pine, about 85 years,  
No trace of burl

42" Pine, nor burnt stob, N. 82° E. 126.7 ft.  
40" Pine, now burnt stob, & Hole, N. 35° W. 105.0 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1970

R	T 31 S	R
8	S 25	S 30 7
W	S 36	S 31 W

New BT's: 16" D. Fir S. 89° W. 22.1 ft. mkd: T31S R8W S36 CS BT.  
14" D. Fir N. 19° W. 22.5 ft. mkd: T31S R8W S25 CS BT.  
13" D. Fir N. 24° E. 22.4 ft. mkd: T31S R7W S30 CS BT.  
16" D. Fir S. 27° E. 17.6 ft. mkd: T31S R7W S31 CS BT.

4/30/70

MARCH 71

Sec. Cor. to Secs. 35 & 36, T30-8W and Secs. 1 & 2, T31-8W.

62

Found - 5", now 5" D. Fir, S. 14 1/2° W. 19.8 ft., pitched over scribe, Ren#47.  
8", now 8" Laurel N. 6° W. 17.2 ft., scribe visible.  
12", now 12" Laurel, N. 51° E. 17.9 ft., scribe visible.  
9", now 9" Laurel, N. 51° E. 17.9 ft., scribe visible.

Also found Brass Cap, out of ground.

Reset Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

T30S	R8W	S35	S36
T31S	R8W	S 2	S 1

New BT's: 7" D. Fir S. 83 1/2° E. 23.4 ft. scribed "T31S R8W S1 CS BT".  
6" D. Fir N. 19° E. 17.0 ft. scribed T30S R8W S36 CS BT".

3/31/71

J. M. Powell  
& Crew  
C.S. File No. 53/67

1/4 Corner to Sec. 36, T30-8W and Sec. 1, T31-8W.

63

Found - 4X4 Post at 1/4 Corner, See Ren. #5.

16", now 19" D. Fir, S. 24° W. 18.1 ft., no scribe visible on face.  
6", now 8" W. Fir, N. 31° E. (Rec. N36E) 21.8 ft., open for scribe "BT".  
I do not find Orig. Pines, as noted. Do find Pine Stob S. 25° E. 14.9 ft.,  
(Record 11.9') This stob badly burnt & decayed.

No trace of N.E. BT. - The burn in this area is very old, I doubt if original evidence was ever found.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1971

T 30 S	R 8 W
	S 36
T 31 1/4 S	S 1

Reblz. & Rescbd: 19" D. Fir S. 24° W. 18.1 ft. scribed "1/4 S 1 CS BT".

3/31/71

JAN. 1972

1/4 Corner to Sections 10 and 15.

64

Found - Gov't. Brass Cap under large 30" D. Fir Log.

8" Hemlock, now down, N. 16° W. 29.0 ft. scribe visible.  
9" W. Fir, now dead, S. 24° W. 38.9 ft., scribe partly visible.

New Bearing Trees:

16" Cedar S. 69° W. 77.8 ft. scribed "1/4 S15 CS BT".  
13" Hemlock N. 38° W. 52.7 ft. scribed "1/4 S10 CS BT".

Note - This corner lies on steep N. slope, also in old logged unit.

5/22/72

John M. Powell  
& Crew  
CS File No. 54/36