

Douglas County Surveyor's Record of  
Government Corners Renewed

T 31 T. S. R 8 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

71

Section Corner for Secs. 3, 2, 10 and 11.

Found - 1961 GLO Brass cap properly marked.

An orig. 14" now 24" Cedar bears S.66°E., 30.1 ft. Tree is alive with open blaze and cruiser mark "I".

A 6" now 10" Hemlock bears S.56°E., 29.7 ft. Tree is alive with well healed blaze.

A 8" now 11" Dead Fir snag bears N.13 1/2°E., 183.5 ft. "T31S R8W S2 BT" visible in unhealed blaze.

A 18" now 27" Hemlock bears S.85°W., 81.8 ft. Tree is alive with visible scribe in healed blaze.

Found no trace of N.W. tree.

New BT - A 6" Alder bears N.4°E., 19.9 ft. scribed "T31S R8W S2 CS BT" in double blaze.

6/17/76

72

1/4 Corner for Secs. 22 and 27.

Found - The orig. NW bearing tree, an orig. 12" now 22" D. Fir, alive and in good condition, with scribing "1/4" visible on previously opened blaze.

The orig. corner monument, a Chinquapin post and the SW BT are gone.

At the corner point as determined by the record measurements from the found Orig. BT, an orig. 12" now 22" D. Fir as described above, bearing N.45°W., 25.7 ft.

We set - A 1" x 30" I. Pipe, " in the ground with brass cap attached mkd: Douglas Co. Surveyor T 31 S R 8 W 1/4 1976 S 22 S 27

New BT - A 22" D. Fir bears S.9°E., 45.7 ft. scribed "1/4 S27 CS BT" on a double blaze.

10/19/76

73

1/4 Corner, Secs. 21 and 22

Found - Stone laying on surface with an apparent "x" marked on top. Found no other marks on stone. Stone measured 21" x 12" x 8" (Rec. 20" x 10" x 8"). Call to the South recorded as 72.6 ft. to creek. The distance from stone to creek measures approx. 121 ft.

No scribing found on possible bearing trees.

DID NOT SET CAP.

10/19/76

74

Section corner for Secs. 13 and 24; and Secs. 18, 19 of T.31-7

Found - 1972 Alum cap and 3 BT's, N.6°1-11"E., 47.37 ft from true Sec. Corner. See Ren. #66

Set - 5/8" x 30" I.R and Alum Cap for Sec. Cor.

BT's - 5" Fir, S.82°E., 19.3 ft.

5" Madrone S.65 1/2°W., 5.1 ft.

4" Madrone N.60°W., 3.3 ft.

9" Pine N.24°E., 30.8 ft.

3/8/77

75

1/4 Corner for Sec. 24 and Sec. 19 of T31-7.

Set - 5/8" x 40" I.R. and Alum Cap.

BT's - 6" Fir, N.81 1/2°E., 27.7 ft.

20" Fir, N.83°W., 32.8 ft.

3/8/77

76

1/4 Corner for Secs. 21 and 22.

Set - 5/8" x 42" I.R. & Alum cap with orig. stone marked 1/4 from Orig. 8" Oak BT.

BT's - 8" Oak, S.10°E., 9.9 ft. Orig.

7" Oak, N.40°W., 8.6 ft. Orig. (down)

10" Oak, N.84°E., 17.6 ft.

See Ren. #73

30" Madrone, N.26°W., 16.0 ft.

11/22/77

M. Lenroa Ladig  
K. Cheney; Peter  
Earle, Doug. Co  
Surveyors Office  
June 17, 1976  
C.S. 59/15

Gary L. Langlitz  
P. L. Earle  
Karen Cheney  
Douglas Co. Surveyor  
C.S. 59/24  
Oct. 19, 1976

L.E. Monrean  
M. Tompkins  
Oct. 19, 1976  
C.S. 59/24

Howard Johnstone  
For: Roseburg Lbr. Co  
March 8, 1977  
M 65 - 5

Howard Johnstone  
For: Roseburg Lbr. Co  
Nov. 22, 1977  
M 65 - 49