

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R. 8 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

83
 1/4 Corner to Sec. 19 in T. 31S R8W, and Sec. 24 in T.31S R.9W
 Found - 3" dia. 1962 BLM Resurvey brass cap on 2 1/2" outside dia. I.P.
 firmly set & protruding 6" above ground.
 An orig. 24" dia. now 34" dia. breast high Douglas Fir w/fully
 healed double blaze bears N.71°E., 48.2 ft. (Rec. N.71°E.,
 47.5 ft., a face measurement)
 Bearing trees from BLM Resurvey renewal:
 12" now 19" diameter breast high Douglas Fir w/fully healed dbl.
 blaze bears N.18 1/4°E., 7.6 ft. (as per record)
 12" now 17" diameter breast high Douglas Fir w/fully healed dbl.
 blaze bears N.86 1/2°W., 40.8 ft. (Rec. N.86 1/2°W., 41.6 ft., dis-
 tance to center of trunk level with cap)
 Both trees have a small upper blaze & a large lower blaze.
 New BT- 4" diameter breast high Douglas Fir scribed "X BT" on a dbl.
 blaze bears S.63°W., 16.8 ft.
 Monument is near east edge of random border clear cut & is approx. 100 ft.
 westerly from BLM forest access road in east half of Section 19.

Douglas County
 Surveyor's Office
 Randall W. Smit
 Stephen J. Flau
 Nov. 1992
 C.S. 64/35

84
 C 1/4 Sec. 28
 Found - 1981 ACIR (Ren. 79)
 14" Fir, S.33°E., 14.3', burned.
 17" Fir, N.13°E., 22.5', burned.
 Set - 6' steel post, 6' North of the corner.
 No other Green trees available.
 Note - BTs were burned in recent fire.

Mark Smalley, L.S. 2354
 For: Roseburg Forest Products
 12/13/94
 C.S. File 63/154

85
 1/4 Cor. Secs. 27 & 28
 Found - 1977 Cad. BCIP
 24" Cedar, N.70°E., 9.2'. fair condition.
 23" Cedar, N.86° 3/4"W., 30.7', tall stump.
 New BTs-20" Fir, S.77°E., 35.0', scribed "1/4 S27 BT".
 16" Madrone, N.64°e., 20.9', scribed "1/4 S27 BT".
 17" Fir, N.9°E., 24.4', scribed "1/4 S27 BT".

86
 SE COR. SEC. 8
 Mon. FD.- 1960 BLM Cad. IPBC
 Bt's Fd.- 29" Fir snag, N.10°E., 50 lks. poor healed face
 10" Fir snag, N.14 1/2°W., 55 lks. dead
 17" W.Fir, S.40 1/4°W., 76 lks. good healed face
 New Bt's- 7" Fir, N.30°E., 23.8' scribed "S 9 BT"
 10" Fir, S.69°E., 47.2, scribed "S 16 BT"

Mark Smalley
 Dec. 13, 1996
 C.S. 65/13-91&J

87
 SW COR. SEC. 8
 Mon. FD.- 1973 BLM CAD. IPBC.
 Bt's Fd.- 27" Fir, N.75°E., 77 lks. good partially healed scribe
 visible.
 37" Fir, N.2°W., 50 lks. good healed
 37" Fir Stump, S.52°E., 34 lks. with metal cap
 20" rotten Fir stump, S.49°W., 38 lks.
 New Bt's- 6" Fir, S.48°W., 36.3' scribed "S 18 BT"
 6" Fir, S.1°E., 35.6' scribed "S 17 Bt"

See previous Ren # 17

FD BC & BTs
 4/2008 C Woodruff
 M/56-5