

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

Center of Section 6. 31
Found - 4" square post established by C. S. Lehmanowsky in 1956. ^{#162}
The 30" Fir B.T. S. 72° W., 26.7 feet is now an uproot.
New BT's: 46" D. Fir N. 36° W., 74.1 feet, "S 6 B.T."
36" D. Fir S. 71° E., 59.6 feet., "S 6 B.T. 473".

32
^{Also #27}
 $\frac{1}{4}$ Corner between Sections 5 and 6.
Found - The Orig. 18" Fir B.T., N. 32° W. 41.5 ft., now a snag.
The Fir for the corner and other Orig. BT are now uproots. ^{see #27}
From the Orig. B.T., standing in place, I set a 1 $\frac{1}{2}$ " pipe for the $\frac{1}{4}$
Corner and Scribe: 22" D. Fir S. 27° E. 57.4 feet "S 5 B.T." 142

33
Sec. Cor. to Secs. 31 & 32, T30-9W and Secs. 5 & 6, T31-9W.
Found - the Original Stone.
The Orig. Fir, 30", N. 44° E. and the Fir, 30", S. 22° E. are both snags.
The Orig. Fir, 34", S. 21 $\frac{1}{2}$ ° W. is now a short stub, badly decayed.
There is no evidence of the Orig. 8" Fir.
Drive a 1 $\frac{1}{2}$ " Pipe at the South Side of the Original Stone & Scribes:
8" D. Fir S. 60° W. 34.4 feet "S 6 B.T. 473"
10" Oak S. 51° E., 20.4 feet "S 5 B.T." 38

34
North $\frac{1}{4}$ Corner of Section 6.
Found - The Original Stone with the chisel marks faintly showing.
The Orig. Fir, 15", S. 40 $\frac{1}{2}$ ° E. is now 30" in diam. and is plainly scribd.
The Original Hemlock B.T. is gone.
I scribe: White Cedar, 9", N. 22° W., 26.3 ft. "S 31 B.T.".

35
Section Corner to Secs. 2 & 1, T31-9W. & Secs. 35 & 36, T30-9W.
Found - Orig. 50", now 60" D. Fir Stump S. 50° W. 12.5 ft., shows "31S R9W
S2" bark scribe & BT scar.
Orig. 10", now 24" D. Fir Stump S. 12° E. 16.5 ft., shows faint scar.
24" D. Fir N. 56° W. 11.8 ft., open & shows "30" in approx 60 years,
not as recorded.
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 35 | S 36
Office, 1964 T31S R9W S 2 | S 1
New BT's: 24" D. Fir N. 56° W. 11.8 ft. Mkd: T30S R9W S35 CS BT.
24" D. Fir Stump S. 12° E. 16.5 ft. Mkd: T31S R9W S1 CS BT. (Orig. BT.)
12" W. Fir N. 38° E. 19.5 ft. Mkd: T30S R9W S36 CS BT.
Note - This corner lies approx. 50.0 ft. East of new 12 Mile Creek Road.
7/18 - Fd. O.K. VRT. C.S. 56/34

36
 $\frac{1}{4}$ Section Corner to Sections 16 and 21.
Found - Orig. 10" Yew, down, N. 60° E. 44.2 ft.
Set - 1 $\frac{1}{2}$ " Iron Pipe, from which:
New BT's: 60" Fir Stump N. 41° 00' E. 71.3 ft., scribed.
34" Green Fir S. 54° 30' E. 64.3 ft., scribed.
M 20 - 16 July 1965

37
 $\frac{1}{4}$ Cor. to Sec. 1, T31-9W. & Sec. 36, T30-9W.
Found - 10" D. Fir, down & rotten, N. 10° W. 3.3 ft.
24" D. Fir, down & rotten, S. 85° E. 26.4 ft., open tree for
scribe, "BT" found. T30S
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's $\frac{1}{4}$ S 36 R9W
Office, 1965 S 1
T31S
New BT's: 8" Cedar N. 13° E. 27.7 ft. scribed T30S R9W $\frac{1}{4}$ S36 CS BT.
5" D. Fir S. 37° W. 72.0 ft. scribed S 1 CS BT.
This corner is located in bottom of small ravine.

38
Sec. Cor. to Secs. 5-6, T31-9W. & Secs. 31-32, T30-9W.
Found - 1 $\frac{1}{2}$ " I. Pipe & Original Stone, See Ren. #33. ^{#164}
8" D. Fir, now 11", S. 60° W. 24.4 ft. scribed S 6 BT.
10" Oak, now 10", S. 51° E. 20.4 ft. scribed S 5 BT. (This tree Found
to be Chinquapin, not Oak) T30S
Set - Brass Cap at Cor. Mkd: Co. Surveyor S 31 | S 32 R9W
Office, 1965 S 6 | S 5
No other trees available to scribe. T31S

Forest J. LaFlamme
For Georgia Pacific Corp.
August 12, 1963
C. S. File No. 51/265

Vernon R.
Tracy & Crew
Oct. 6, 1964
C. S. File
No. 53/53

Coos Head
Timber Co.
By: C. A.
Stephens
C.S. #51/178

John M. Powell
J. Brady & F. Jones
November 1965
C.S. File No. 53/53