

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97331

44

T. H. Mehl, III
The Robert Dollar Co.
Oct. 12, 1966
C. S. File No. 55/15

Sec. Cor. to Secs. 18 & 19, T31-9W. & Secs. 13 & 24, T31-10W.
Found - Corner in poor condition.

- 48" Fir BT - S. 35° E. 8.6 ft., now high stump.
- 8" Cedar BT - N. 65° E. 31.7 ft., removed in logging
- 40" Fir BT - S. 32° W. 18.5 ft., now high stump.
- 24" Fir BT - N. 88° W. 21.8 ft., now snag stump.

For the Cor., I set a 1 1/2" x 30" Iron Pipe, 28 in. in the ground.

- New BT's: 5" Hemlock N. 26° W. 8.2 ft., scribed S13 RS749 BT.
 - 4" Hemlock N. 6° E. 5.1 ft., scribed X (at breast ht.) BT.
 - 12" White Fir S. 30 1/2° W. 52.5 ft., scribed S24 RS749 BT.
 - 13" Cedar S. 25 1/2° E. 51.9 ft., scribed S19 RS749 BT.
- Ref. done with staff compass & chain. Mag. Var. 19 1/2° E.

John M.
Powell &
Crew
C. S. File
No. 54/36

Corner to

T31S	R9W	S 31	R8W
T32S	S 1	S 6	

- Found - G.L.O. Brass Cap at Corner, but out of ground.
 - 16", now 28" D. Fir, S. 10° E. 43.6 ft., shows good scar.
 - 30" D. Fir, S. 10° W. 46.2 ft., find dist. to be 54.0 ft., shows good scar.
 - 60", now 55" D. Fir, N. 14° W. 19.1 ft., shows bark scribing.
- Reset Brass Cap at Section Corner.
All BT's. tagged and all right.
This corner lies South of Read 50.0 ft. in part of fill.

12 - 21 - 66
45
46

SECTION

- Corner to Sec. 36, T31-9W. and Sec. 31, T31-8W.
- Found - 30" D. Fir, now stump, N. 26° W. 34.3 ft., shows good scar & faint bark scribe "31S".
- No trace of N. E. Laurel.
- Found G.L.O. Brass Cap marked in 1918.
- New BT's: 5" Laurel N. 13° W. 26.0 ft. mkd. S36 CSBT.
- 5" Laurel S. 42° E. 21.2 ft. mkd. S 1 CS BT.

Jan. 19, 1966

- 1/4 Corner to Sec. 31, T31-9W. & Sec. 36, T31-8W.
- Found - 7/8" Drill Steel at 1/4 Corner, See Ren. #5.
- Orig. 24", now 30" D. Fir, N. 42° E. 15.8 ft., bark scribe "1/4" and rescribe "1/4 S BT". This tree is leaning badly with windfall against it.
- 6", now 8" D. Fir, N. 61° W. 25.1 ft., shows good scar.
- New BT: 6" D. Fir S. 68° E. 4.8 ft. mkd. 1/4 S 31 CS BT.

SEE ALSO #195 47
48

- 1/4 Corner to Sections 11 and 14.
- Found - Part of Stone at 1/4 Corner.
- 16", now 22" D. Fir, S. 30° E. 17.2 ft., opened for scribing.
- 30", now 36" D. Fir, N. 25° E. 5.3 ft., shows good scars.
- Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office 1967
- T 31 S R 9 W
1/4 S 11
S 14
- New BT's: 7" Cedar S. 22° E. 43.5 ft. mkd. 1/4 S14 CS BT.
- 10" Cedar N. 34° E. 14.3 ft. mkd. 1/4 S11 CS BT.

- Sec. Corner to Sections 11 - 12 - 13 - 14.
- Found - Orig. Post, scribed S14 S13 R9W.
- 36", now 52" Cedar, S. 50° W. 15.2 ft., opened for scribe "31".
- 24" Fir, now snag, N. 45° E. 38.9 ft., shows good scar.
- 16" Cedar, now burnt stob, N. 12° W. 21.1 ft. (dist. S₁₄ B₁₄ 24.4 ft.)
- 36" Cedar, now stump S. 35° E. 29.7 ft.

- Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967
- T 31 S R 9 W
S 11 | S 12
S 14 | S 13

- New BT's: 10" D. Fir S. 28° E. 21.5 ft. mkd. T31S R9W S13 CS BT.
- 7" D. Fir N. 12° W. 21.3 ft. mkd. T31S R9W S11 CS BT.
- 6" Laurel N. 35° E. 24.2 ft. mkd. T31S R9W S12 CS BT.

John M. Powell
Frank Jones & Cliff Stone
February, 1967
C. S. File No. 54/32

90 7/20/66
M 161-7
C. Woodruff