

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S.    T. S.    R. 9 W.    R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

50

$\frac{1}{4}$  Corner to Sections 24 and 25.  
Found - Orig. 16", now 22" D. Fir, S. 25° E. 52.1 ft., scribe visible.  
Orig. 16", now 22" D. Fir, N. 15° W. 33.8 ft., (Record N. 20° W.  
37.6 27.6 ft.) shows good scar.

(Renew cor. by using bear. & dist. from 1 tree, not being able to get two bearings to agree.)

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967  
T 31 S R 9 W  
 $\frac{1}{4}$  S 24  
S 25

Note - No new bearing trees needed.

**RE-RENEWED, SEE CORNER NO. #168**

51

$\frac{1}{4}$  Corner to Sections 1 and 12. *FD. OK BY K DeGroot, 6/01, M137-13*  
Found - Orig. 16", now 25" Cedar, N. 46 $\frac{1}{2}$ ° W. 29.7 ft., scribe visible  
(Record bearing N. 61° W.)  
Orig. 16", now 29" W. Fir, S. 84° W. 15.2 ft., scribe visible.  
(Record bearing S. 63° W.)

This tree has been opened, ring count indicates original. Bearing being so far off, I use the two dist. to renew corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967  
T 31 S R 9 W  
 $\frac{1}{4}$  S 1

New BT: 17" Cedar S. 37° W. 13.9 ft. mkd.  $\frac{1}{4}$  S12 CS BT.

52

Sec. Corner to Sections 1 - 2 - 11 - 12.  
Found - Orig. 24", now 29" Cedar, N. 50° E. 23.1 ft., opened for scribe "R9".  
Orig. 36", now 37" Fir, N. 70° W. 11.9 ft., shows good scar.  
Orig. 36", now 42" Fir, S. 57° W. 39.6 ft., shows good scar.  
(Record bearing S. 63° W.)

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967  
T 31 S R 9 W  
S 2 | S 1  
S 11 | S 12

New BT: 8" W. Fir S. 26° E. 87.4 ft. mkd. T31S R9W S12 CS BT.

53

Sec. Cor. to Sections 3 - 4 - 9 - 10.  
Found - 7/8" Hex. Rod, I do not hit anything but 1 bearing from this point. Ren. #6.  
Orig. 10", now 13" Cedar, N. 21° E. 21.1 ft., scribe visible.  
(Record bearing N. 40° E.)  
Orig. 30", now down Cedar, N. 39° W. 37.6 ft. (Record Bear. N. 14° W.)  
Orig. 24" D. Fir, now stob, S. 30° W. 5.3 ft., tree has burnt face.  
(Record bearing S. 41° W.)  
Orig. 18", now 22" D. Fir, S. 72° E. 5.3 ft., shows good scars.  
(Record bearing S. 42° E.)

By using intersection of all 4 distances, I set Brass Cap Mkd:  
County Surveyor's Office 1967  
T 31 S R 9 W  
S 4 | S 3  
S 9 | S 10

New BT's: 12" Hemlock S. 84° W. 144.2 ft. mkd. T31S R9W S9 CSBT.  
6" W. Fir N. 41° W. 133.5 ft. mkd. T31S R9W S4 CS BT.  
Note - 7/8" Hex Rod is 2.0 ft. N. 10° W.

54

$\frac{1}{4}$  Corner to Sections 4 and 9.  
Found - 48" D. Fir Corner Tree, opened north side of tree, " $\frac{1}{4}$ " S" found.  
14", now 20" Cedar S. 18° W. (Record S. 18° E.) 26.4 ft., no scribing found.  
8" Cedar N. 80° W. 10.6 ft., no scribing found, looks as though it has been axed off.

Set - Brass Cap on N.E. side of Corner Tree Mkd: County Surveyor's Office 1967  
T 31 S R 9 W  
 $\frac{1}{4}$  S 4  
S 9

New BT's: 9" Cedar N. 37 $\frac{1}{2}$ ° W. 44.0 ft. mkd.  $\frac{1}{4}$  S 4 CS BT.  
8" Cedar S. 21 $\frac{1}{2}$ ° W. 23.0 ft. mkd.  $\frac{1}{4}$  S 9 CS BT.

# 189

John M. Powell  
Frank Jones & E. West  
February, 1967  
C. S. File No. 54/32