

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 31 S. T. S. R. 9 W. R. W. W. M.

ROSE-CHAPMAN CO., EUGENE, ORE. 21881

55

Sec. Corner to Sections 14 - 15 - 22 - 23.
Found - Pieces of Stone at Corner.
Orig. 12", now 29" D.Fir, N. 45° E. 84.5 ft., shows good scar.
Orig. 8", now 13" D.Fir, S. 8° E. 26.4 ft.
Orig. 20", now 36" D.Fir, S. 75° W. 39.6 ft. (slope distance).
Orig. 20", now Dead D.Fir, N. 28° W. 20.5 ft., opened for scribing,
found scribe marks but rotten, not legible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

T 31 S	R 9 W
S 15	S 14
S 22	S 23

New BT: 44" D. Fir N. 2½° W. 34.7 ft. mkd. T31S R9W S15 CS BT.

56

Sec. Corner to Sections 23 - 24 - 25 - 26.
Found - Orig. 16", D.Fir, now Stob, N. 38° E. 38.3 ft., scribe visible
Orig. 18", now 24" D.Fir, S. 60° E. 44.2 ft., shows good scar.
Orig. 10", now 18" D.Fir, S. 46° W. 39.6 ft., shows good scar.
Orig. 10" D. Fir, now stump, N. 25° W. 16.5 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967

T 31 S	R 9 W
S 23	S 24
S 26	S 25

New BT's: 8" D.Fir N. 17½° W. 21.2 ft. mkd. T31S R9W S23 CS BT.
5" Chinquapin N. 17° E. 21.4 ft. mkd. T31S R9W S24 CS BT.

57

¼ Corner to Sections 25 and 26.
Found - ¾" I. Pipe, 18" underground, See Ren. #28
Orig. D.Fir, now down, N. 70° W. 16.5 ft., opened for scribe "6".
42" Fir, now down, S. 66½° W. 3.8 ft., scribe marks visible,
but pitched over.
40" Fir, now down, N. 19½° E. 18.0 ft. scribe visible "25½ S RS424 BT.
Ren. #28- 6", now 10" D.Fir, S. 81½° W. 117.4 ft. (Record 108.4'), shows
good scar.
By using Orig. BT., I. Pipe, and 2 down trees, I renew:
Set - Brass Cap at Cor. Mkd. County Surveyor's Office, 1967

T 31 S	R 9 W
¼ S 26	¼ S 25

New BT" 4" Live Oak N. 48° E. 39.5 ft. mkd. ¼ S25 CS BT.
Note - This corner lies 50.0 ft. north of Road.

58

¼ Corner to Sections 3 and 2.
Found - Orig. 16x12x10 Stone with "¼" on W. face.
Orig. 10", now 12" Laurel N. 32° E. 22.4 ft. (Record N. 52° E.)
"BD" scribe visible.
Orig. 16" Laurel N. 19° W. (Record N. 24° W.) 17.8 ft., shows
good scar, rotten center.
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office, 1967

T 31 S	R 9 W
¼ S 3	¼ S 2

New BT's: 6" Laurel N. 51° E. 14.4 ft. mkd. ¼ S 2 CS BT.
8" Laurel N. 77° W. 29.9 ft. mkd. ¼ S 3 CS BT.
Note - This corner lies 22.0 ft. south of ridge top.

RE-RENEWED, SEE CORNER #166

59

¼ Corner to Sections 3 and 10. *FD. OK BY C. SWEEDEN JAN, 2003*
Found - 6" Hemlock Corner Tree, now 8", opened for scribe "S".
Orig. 8", now 16" Hemlock S. 36° E. (Record S. 9° E.) 3.3 ft.,
scribe marks visible but mostly covered.
Orig. 16", now 18" Hemlock, N. 63° W. (Record N. 36° W.) 6.6 ft.,
scribing visible "S3 ¼ S BT".
Set - Brass Cap on N. Side of Corner Tree Mkd: County Surveyor's Office, 1967

T 31 S	R 9 W
¼ S 3	¼ S 10

New BT's: 12" Hemlock N. 42° E. 30.4 ft. mkd. ¼ S 3 CS BT.
Note - I open tree for ring count which places these trees about 1900,
rings too close for accurate count.

John M. Powell
Frank Jones & E. West
February, 1967
C. S. File No. 54/32