

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner to Sections 9 and 10. 66
 Found - Corner Stone mkd: "1/4" and 3/4" I. Pipe, See Ren. #23.
 24" Fir Stump N. 26° E. 13.2 (record N54E.) scribing, "BT".
 8" Fir Stob S. 86 1/2° W. (record S.55W) 28.4 ft., scribing, "BT".
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
 Office, 1967 1/4 S 9 S 10
 New BT's: 14" D. Fir N. 39° E. 42.8 ft. mkd. 1/4 S10 CS BT.
 8" W. Fir N. 19° W. 19.3 ft. mkd. 1/4 S 9 CS BT.
 Note - This corner lies 75 ft. east of a jeep road.

1/4 Corner to Sections 27 and 34. Also Witness Corner. #178 67
 Found - 8" D. Fir, now 14", N. 40° E. 31.2 ft. opened for scribing "4".
 No trace of S. E. BT.
 Set - 3/4" I. Rod at 1/4 Corner as this corner falls in Road.
 Brass Cap for Wit. Cor. Mkd: County Surveyor's T 31 S R 9 W
 Wit. Cor. 20" N. to 1/4 S 27
 1967 S 34
 New BT's: 15" D. Fir N. 30° E. 51.4 ft. mkd. 1/4 S 27 W.C. CS BT.
 27" D. Fir S. 27° W. 14.7 ft. mkd. 1/4 S34 W.C. CS BT.

Section Corner to Sections 10 - 11 - 14 - 15. 68
 Found - 8", now 10" Yew, Rotten, N. 68° E. 14.5 ft., scribe visible.
 8" D. Fir, now down, S. 35° E. 15.8 ft., scribe visible.
 Do not find S.W. BT.
 10" D. Fir, now stump, N. 85° W. 29.0 ft.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
 Office S 10 | S 11
 1967 S 15 | S 14
 M141-39 SET STEEL POST 1.0' WEST
 JAN. 2003 BY C. SWEEDEN.
 New BT's: 8" Hemlock S. 28° W. 24.3 ft. mkd. T31S R9W S15 CS BT.
 21" Cedar S. 50° E. 35.0 ft. mkd. T31S R9W S14 CS BT.
 18" D. Fir N. 56 1/2° W. 39.9 ft. mkd. T31S R9W S10 CS BT.
 11" Yew N. 79° E. 14.5 ft. mkd. T31S R9W S11 CS BT.

1/4 Corner to Sections 10 and 11. 69
 Found - Orig. 6" Corner Tree, now down, scribing visible "S10 1/4 S". 185
 10" D. Fir, now down, S. 20° E. 11.2 ft., shows good scar.
 10" W. Fir, now down, S. 85° W. 5.3 ft., scribe visible,
 stump shows "BT" log "1/4 S".
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
 Office, 1967 1/4 S10 | S11
 New BT's: 24" D. Fir S. 19° E. 55.3 ft. mkd. 1/4 S11 CS BT.
 20" D. Fir N. 71° W. 94.9 ft. mkd. 1/4 S10 CS BT.

1/4 Corner to Sections 14 and 13. 70
 Found - Corner Stone Mkd. "1/4" at the corner point.
 16" Fir Stump S. 80° W. 33.0 ft. scribing "1/4".
 N. E. Fir gone
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R9 W
 Office, 1967 1/4 S 14 | S 13
 New BT's: 10" D. Fir N. 8° W. 28.8 ft. mkd. "1/4 S14 CS BT.
 30" D. Fir S. 25° E. 6.3 ft. mkd. 1/4 S13 CS BT.

Sec. Corner to Sections 13 - 14 - 23 - 24. 71
 Found - Unrecorded 1" Iron Pipe at section corner. See ALSO
 Orig. 12", now 15", S. 30° E. 6.6 ft. scribe marks visible, but
 not legible.
 Orig. Cedar, now dead, N. 18° E. 17.2 ft. scribe visible. #194
 No trace of S.W. nor N.W. BT's.
 Unrec. Trees: 8" W. Fir N. 84° W. 61.1 ft., scribe marks visible.
 10" Cedar S. 45° W. 41.4 ft. scribe visible.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 31 S R 9 W
 (alongside I.P.) Office S 14 | S 13
 1967 S 23 | S 24
 New BT's: 12" D. Fir N. 15° E. 69.3 ft. mkd. T31S R9W S13 CS BT. See M161-7 7/2010

John M. Powell
 Frank. Jones & C. Stone
 February and March, 1967
 C. S. File No. 54/32